



SLIMLED - LONGUEUR STANDARD



Corps aluminium/Diffuseur polycarbonate opalin, **65 LED/m, 17,2W/m.**
Avec connecteurs. Installation multiposition. **Longueur maxi. par circuit : 6 m.**



III 24V DC IP20 IK08 850°

P (w)	Nb. LED	L (mm)	Teinte	Code
6	20	310	● 3000 K	2909
12	40	620	● 3000 K	2908
18	60	930	● 3000 K	2907
24	80	1240	● 3000 K	2922
30	100	1550	● 3000 K	2924
36	120	1860	● 3000 K	2926
6	20	310	○ 6500 K	2919
12	40	620	○ 6500 K	2918
18	60	930	○ 6500 K	2917
24	80	1240	○ 6500 K	2923
30	100	1550	○ 6500 K	2925
36	120	1860	○ 6500 K	2927

ACCESSOIRES



Désignation Code
x1 équerre de fixation orientable **0857**



Désignation Code
x1 équerre de fixation **0848**



Désignation Code
Embout de branchement avec câble d'alimentation **2914**
L (35 mm) x l (19 mm)




Désignation Code
Embout de fermeture **0589**
L (15 mm) x l (13 mm)



Désignation Code
Câble alimentation 3 m **0624**

Câble de prolongement Code
100 mm **2376**
500 mm **2384**

Alimentation 24VDC.



RUBAN LED