

## Features

Use: Indoor  
 Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK  
 Emission: DIRECT  
 Optics: MICROPRISMATIZED  
 Colour: CAPPUCCINO  
 Dimming: PUSH, DALI  
 Emergency: NO  
 L: 1120mm  
 A: 53mm  
 H: 69mm  
 Made in: ITALY  
 Warranty: 5 years  
 Weight: 2.8kg

## Tech data

Luminaire input power: 28.5W  
 Luminaire luminous flux: 2355lm  
 IP: 40  
 Insulation class: I  
 Supply voltage: 220-240V 50/60Hz  
 UGR: <19  
 SELV: Si

## Source

Light source: LED  
 Source power: 24W  
 Colour temperature: 4000K  
 CRI: >90  
 Colour tolerance: 3 Step MacAdam  
 LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
 CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

## Average luminance


Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

[View more product info](#)



## COMPLETION ACCESSORIES


---



HERO: MOD.CIECO ANG.SX 150 CAP

108677.21


---



HERO: MOD.CIECO 1120 CAP

108679.21


---



HERO: MOD.CIECO 1680 CAP

108681.21

---



HERO: COPPIA TESTATE CAP

108684.21

---



HERO: MOD.CIECO 1400 CAP

108680.21

---



HERO: MOD.CIECO 250 CAP

108676.21


---



HERO: MOD.CIECO ANG.DX 150 CAP

**108678.21**

## MOUNTING ACCESSORIES




KIT ALIMENTAZIONE L1200 5P BIA

**108921.01**



HERO: SOSPL3000 1PZ. TESTA/CODA

**108685.99**



KIT ALIMENTAZIONE L3000 5P BIA

**108922.01**




HERO: SPESS. CARTONG. 10MM 2PZ.

**108689.99**



HERO: SOSPL3000 1PZ. UNIONE

**108686.99**




ALL-TRACK: COPPIA ADATT. 3P+DALI NER

**106723.02**

# HERO


108654.21 + 108910.99

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



KIT ALIMENTAZIONE L1200 5P CAP

**108921.21**



ALL-TRACK: COPPIA ADATT. 3P+DALI BIA

**106723.01**



HERO: KIT INCASSO LED (1X)

**108688.99**



KIT ALIMENTAZIONE L3000 5P CAP

**108922.21**



HERO: STAFFA PARETE "L" CAP

**108687.21**



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.