

Offset Blade fuse-links gG 550VAC

LOW VOLTAGE IEC FUSES

BS FUSE-LINKS

The fuse complies with standard EN 60269-2 section II and standard BS 88 part 2. These fuses are designed for : “General purpose use” protection (gG type). This fuse range insures an excellent current limitation for all overloads on a large range of applications. Their size cannot allow exchange by other fuses of higher rating in their range. They are screwed into fuseholders or bolted directly onto busbars, or in fuse interruptors disconnectors.

FEATURES & BENEFITS

- Excellent current limitation for all overloads

APPLICATIONS

- These fuses are designed for : “General purpose use” protection (gG type)

STANDARDS

- EN 60269-2 section II



Offset Blade fuse-links gG 550VAC

PRODUCT RANGE

Type F2 550VAC

Catalog number	Rated voltage AC (IEC)	Rated current I_n	Pre-arcing I^2t	Clearing I^2t at Rated Voltage	Rated breaking capacity AC	Power dissipation at I_n
BES55V10	550 V	10 A	70 A ² s	350 A ² s	80 kA	1.2 W
BES55V16	550 V	16 A	120 A ² s	550 A ² s	80 kA	1.6 W
BES55V2	550 V	2 A	1 A ² s	5 A ² s	80 kA	0.9 W
BES55V20	550 V	20 A	250 A ² s	1250 A ² s	80 kA	1.7 W
BES55V25	550 V	25 A	420 A ² s	2100 A ² s	80 kA	2 W
BES55V32	550 V	32 A	670 A ² s	3350 A ² s	80 kA	2.9 W
BES55V36	550 V	36 A	700 A ² s	4000 A ² s	80 kA	2.8 W
BES55V4	550 V	4 A	7.6 A ² s	38 A ² s	80 kA	1.5 W
BES55V6	550 V	6 A	28 A ² s	40 A ² s	80 kA	1.8 W