

# YG8U14-150UA3XLEAX

Sensor/actuator cable

**PLUG CONNECTORS AND CABLES** 





#### Ordering information

Туре	Part no.
YG8U14-150UA3XLEAX	2118299

Other models and accessories → www.sick.com/Sensor\_actuator\_cable



#### Detailed technical data

#### Technical specifications

reclinical specifications		
Connection type head A		Female connector, M8, 4-pin, angled, A-coded
Connection type head B		Flying leads
Locking plug connector		Screw connection
Connector material		TPU
Connector color		Black
Locking nut material		Zinc die-cast, nickel-plated
Seal material		FKM
Tightening torque		0.4 Nm
Width across flats		9
Cable		15 m, 4-wire, PUR, halogen-free
Jacket material		PUR, halogen-free
Jacket color		Black
Cable diameter		4.5 mm
Conductor cross section		0.25 mm <sup>2</sup>
Shielding		Unshielded
Bending radius		
	Flexible use	> 10 x cable diameter
Station	nary position	> 5 x cable diameter
Drag cha	ain operation	> 10 x cable diameter
Bending cycles		10,000,000
Nominal voltage, cable		300 V AC
Test voltage, cable		2,500 V AC
Reference voltage		
		50 V AC
		60 V DC
Rated impulse voltage		1.5 kV
Current loading		≤ 4 A
Traversing speed		3 m/s

Travelling distance	10 m
Acceleration	≤ 10 m/s²
Signal type	Sensor/actuator cable
Torsion force	180°/1 m
Torsion cycles	2,000,000
Cycles per minutes	35
Application	Zones with oils and lubricants Drag chain operation Robot
Authorizations	UL CE
UL File No.	E335179
Enclosure rating	IP65 / IP66K / IP67
Operating temperature	
Flexible use	-25 °C +80 °C
Stationary position	-40 °C +80 °C
Drag chain operation	-25 °C +80 °C
Head	-25 °C +85 °C
Contamination rating	3
Insulation resistance	100 ΜΩ
Overvoltage category	III
Specific insulation resistance	30 mΩ
Thermal resistance, piping	Flame retardant according to UL 1581, horizontal flame test/CSA FT2 / IEC 60332-1, IEC 60332-2-2


#### Classifications

ECLASS 5.0	19030312
ECLASS 5.1.4	19030312
ECLASS 6.0	27060304
ECLASS 6.2	27060304
ECLASS 7.0	27060304
ECLASS 8.0	27060304
ECLASS 8.1	27060304
ECLASS 9.0	27060304
ECLASS 10.0	27060304
ECLASS 11.0	27060304
ECLASS 12.0	27060304
ETIM 5.0	EC000830
ETIM 6.0	EC000830
ETIM 7.0	EC003249
ETIM 8.0	EC003249
UNSPSC 16.0901	26121604

# YG8U14-150UA3XLEAX | Sensor/actuator cable

PLUG CONNECTORS AND CABLES

## Dimensional drawing (Dimensions in mm (inch))



## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

# **WORLDWIDE PRESENCE:**

Contacts and other locations -www.sick.com

