

## Features

Use: Indoor  
Type of installation: SUSPENDED, CEILING MOUNTED  
Emission: DIRECT  
Optics: OPAL  
Colour: CAPPUCCINO  
Dimming: WITH ACCESSORY  
Emergency: NO  
L: Ø 962mm  
A: 40mm  
H: 40mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 6.5kg

## Tech data

Luminaire input power: 66.1W  
Luminaire luminous flux: 4459lm  
IP: 40  
Insulation class: III  
Supply voltage: MAX 1.8A  
UGR: <19  
SELV: No

## Source

Light source: LED  
Source power: 62W  
Source luminous flux: 9606lm  
Colour temperature: 4000K  
CRI: >90  
LED lifespan: 50000h

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



# HALOS ACOUSTIC

109906.21

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948

## MOUNTING ACCESSORIES

---



HALOS: ROSONE ALIM. REMOTA CAPP

**105157.21**

---



HALOS: ROSONE DOPPIA ALIM. REMOTA CAPP

**105158.21**

---



HALOS: KIT 4 CAVI SOSPENSIONE L.3000

**105159.99**

---




CAVO ALIMENTAZIONE L=3000 3X1.5 TRASP

**109001.00**

## ELECTRICAL ACCESSORIES

---



HALOS: ALIMENTATORE ON/OFF

**105147.99**

---



HALOS: ROSONE ALIM. ON/OFF CAPP

**105149.21**

---



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.



HALOS: ROSONE-N ALIM. ON/OFF CAPP


**105151.21**



HALOS: ROSONE-N DOPPIA ALIM ON/OFF CAPP

**105155.21**

## DIMMABLE ACCESSORIES



HALOS: ALIMENTATORE DALI/PUSH

**105148.99**



HALOS: ROSONE ALIM. DALI/PUSH CAPP

**105150.21**



HALOS: ROSONE-N ALIM. DALI/PUSH CAPP

**105152.21**



HALOS: ROSONE-N DOPPIA ALIM D/PUSH CAPP

**105156.21**