


LPSS333R3433E SELECTOR SWITCH ACTUATOR KEY Ø22MM PLATINUM SERIES METAL, 3 POSITION, 1 - 0 -2 WITH DIFFERENT KEY CODE. WITHDRAL AT 2



Product designation				Selector switch actuator key - 3 position
Product type designation General characteristics				LPSS33
Colour				Black
Type of positions				Selector switch
· · · · ·				Aluminium and
Material				zinc alloy
IEC degree of protection	n			IP66, IP67 and IP69K
Mechanical features				
Mechanical life			cycles	1000000
Fixing				Without mounting adapter
Mounting adapter				LPXAU120M
UL technical data				
UL degree of protection				Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-25
		max	°C	+70
	Storage temperature			
		min	°C	-40
D:		max	°C	+85
Dimensions				
31 (1.22")	- <u>-</u> 22.3 (0.88")			



кеу		
Certifications and cor	npliance	
Compliance		
	CSA C22.2 n° 14	
	IEC/EN/BS 60947-1	
	IEC/EN/BS 60947-5-1	
	UL508	
Certificates		
	cULus	
ETIM classification		
ETIM 8.0		EC002611 - Control switch