

## Informations générales

Extended Product Type:	LS31P91B11
Id du produit:	1SBV010191R1211
EAN:	3471522001214
Description catalogue:	LS31P91B11 Limit Switch
Description:	LS31P91B11 Limit Switch

## Catégories

Produits » Produits basse tension » Produits de Contrôle, Protection et sécurité machines » Capteurs » Interrupteurs de position

## Ordering

EAN:	3471522001214
Quantité minimum:	1 piece
Nombre des douanes tarif:	85369085

## Dimensions

Product Net Width:	30 mm
Poids net:	0.080 kg

## Container Information

Niveau de l'unité d'emballage 1:	1 piece
Package Level 1 Width:	202 mm
Package Level 1 Height:	35 mm
Package Level 1 Length:	32 mm
Package Level 1 Gross Weight:	0.08 kg
Package Level 1 EAN:	3471522001214

## Environmental

Température de l'air ambiant:	Operation -25 ... +70 °C Storage -30 ... +80 °C
Resistance to Shock acc. to IEC 60068-2-27:	Half-sine Pulse for 11 ms, No Change in Contact Position 50 m/s <sup>2</sup>
Resistance to Vibrations acc. to IEC 60068-2-6:	25g (10 to 500 Hz) no change in position of contacts greater than 100 µs

## Technical UL/CSA

Pilot Duty of Contact Elements acc. UL508:	A600 Q600
Flammability According to UL94:	V0

## Additional Information

Action Type of the Contact Element (acc. to IEC 60947-5-1):	snap action contacts
Actuation Speed:	acc. to IEC 60947-5-1 Max. 1.00 m/s acc. to IEC 60947-5-1 Min. 0.00 m/s
Actuation Torque:	acc. to IEC 60947-5-1 Min. 0.12 N·m
Actuator Type:	spring rod
Angular Head Adjustment:	adjustable head every 90°
Angular Lever Adjustment:	none
Climatic Withstand:	according to IEC 68-2-3 and salty mist according to IEC 68-2-11
Connecting Capacity:	AWG 20 ... AWG 14 0.5 ... 2.5 mm <sup>2</sup>
Connecting terminals (delivered in open position):	M3.5 (+,-) pozidriv 2 screw with cable clamp
Consistency (Measured over 1 Million Operations):	0.1 mm
Contact Element Form (acc. to IEC 60947-5-1):	Zb
Courant thermique conventionnel à l'air libre (I <sub>th</sub> ):	acc. to IEC 60947-5-1, q = 40 °C 10.0 A
Degree of Protection:	acc. to IEC 60529 IP65
Electrical Shock Protection acc. to	Double insulation - Class II

<b>IEC 536:</b>	
<b>IIT Publishing Status:</b>	Level 0 - Information enabled
<b>Maximum Electrical Switching Frequency:</b>	3600 cycles per hour
<b>Durabilite mecanique:</b>	5 million
<b>Mounting by Screws (not supplied):</b>	2 x M4 screws
<b>Mounting Position:</b>	all positions are authorised
<b>Movement to be Detected:</b>	Multidirectional Translation Movement
<b>Number and Type of Bottom Cable Glands:</b>	Pg 11 Cable Gland
<b>Number of Auxiliary Contacts NC:</b>	1
<b>Number of Auxiliary Contacts NO:</b>	1
<b>Quantité:</b>	1 piece
<b>Positive Opening Operation of NC Contact(s):</b>	No
<b>Product Main Type:</b>	LS30
<b>Nom du produit:</b>	Limit Switch
<b>Fréquence assignée (f):</b>	Supply Circuit 50 Hz Supply Circuit 60 Hz
<b>Tension assignée de tenue aux chocs (U<sub>imp</sub>):</b>	6 kV
<b>Tension assignée d'isolement (U<sub>i</sub>):</b>	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V
<b>Courant assignée d'emploi AC-15 (I<sub>e</sub>):</b>	(130 V) 5.5 A (230 V) 3.1 A (240 V) 3 A (24 V) 10 A (400 V) 1.8 A
<b>Courant assignée d'emploi DC-13 (I<sub>e</sub>):</b>	(110 V) 0.6 / 66 A (24 V) 2.8 / 67.2 A (250 V) 0.27 / 67.5 A
<b>Resistance Between Contacts:</b>	25 mΩ
<b>Standards:</b>	IEC 60947-1, IEC 60947-5-1, EN 60947-1, EN 60947-5-1, UL 508 and CSA C22-2 N°14
<b>Terminal Marking:</b>	according to EN 50013

#### Certificates and Declarations (Document Number)

<b>Declaration of Conformity - CE:</b>	1SBD250881C2000
<b>Data Sheet, Technical Information:</b>	1SBC001699R1002

#### Classifications

<b>ETIM 4:</b>	EC001829 - Position switch modular
<b>ETIM 5:</b>	EC001829 - Position switch modular
<b>ETIM 6:</b>	EC001829 - commutateur de position de série
<b>UNSPSC:</b>	39121500

