

TWISTER 3000 K / 4000 K

LAMPE

DOWNLIGHT
ENCASTRÉ DÉCO

SPOT SUR RAIL
SPOTIERIE

RÉGLLETTE
MODULE LED

RUBAN
PROFILÉ

APPLIQUE
PLAFONNIER
SUSPENSION

PROJECTEUR
EXTÉRIEUR

7200 lm


4500 lm

2400 lm

1100 lm




70 W



50091	4000 K	70 W	110°
h (m)	E _{max} (lx)	d (m)	
1	2870	2,86	
2	718	5,7	
3	319	8,6	
4	179	11,4	
5	115	14,3	




45 W



50090	4000 K	45 W	110°
h (m)	E _{max} (lx)	d (m)	
1	1687	2,86	
2	422	5,7	
3	187	8,6	
4	105	11,4	
5	67	14,3	




25 W



50089	4000 K	25 W	110°
h (m)	E _{max} (lx)	d (m)	
1	981	2,86	
2	245	5,7	
3	109	8,6	



12 W



50088	4000 K	12 W	110°
h (m)	E _{max} (lx)	d (m)	
1	422	2,86	
2	106	5,7	
3	47	8,6	

FIXATION MÂT



Embout de fixation pour projecteur TWISTER : **25W - 45W - 70W - 100W**. A installer sur les mâts de Ø60 mm (p. 448). Exclusivement pour montage vertical.

Couleur	Code
noir	50114

Corps aluminium noir/Verre de protection. Précâblage H05RN-F long. 0,8 m. Ailettes de refroidissement en aluminium. LED CREE MHB.

P (W)	Lumens	Poids (kg)	Code
4000 K			
12	1100	0,82	50088
25	2400	1,2	50089
45	4500	2,2	50090
70	7200	3,7	50091
3000 K			
N 25	2250	1,2	50348
N 45	4200	2,2	50349
N 70	6800	3,7	50350