

PRODUCT-DETAILS

JSHD4-5

JSHD4-5 Three-position handheld device - Top part



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | JSHD4-5 |
| Code de produit | 2TLA020006R2500 |
| EAN | 7350024459760 |
| Description courte | JSHD4-5 Three-position handheld device - Top part |
| Description longue | <p>The JSHD4-5 is a top part of a three-position device JSHD4. It has LEDs and a top button. It must be used with one of the following bottom parts: AB, AD, AH, AJ, AK, AL. Anti-tamper can be chosen as option with all except bottom part AK.</p> <p>Three-position devices are used to allow a limited movement of the machine when the operator is in the dangerous area, for example during troubleshooting, test running and programming.</p> |

Commande

| | |
|-------------------|--|
| Quantité minimum | 1 pièce |
| Code douanier | 85369095 |
| Groupe de produit | JSHD4 |
| Type de produit | Three-position handheld device - Top part |
| Sub-Function | 1 top auxiliary button |
| Sub-Function 2 | Holder for Eva (home position) with bottom part AL Anti-tamper available as option (not with AK bottom) |
| Status Indicator | Oui |

Downloads Préférés

| | |
|--|-----------------|
| Fiche produit, informations techniques | 2TLC010001C0202 |
| Instructions et manuels | 2TLC172072M0201 |
| Wiring Diagram | 2TLC010143D0201 |
| CAD Dimensional Drawing | 2CDC001079B0201 |
| Marketing Video | 2TLC010018N0201 |

Dimensions

| | |
|----------------------|----------|
| Produit Longueur Net | 340 mm |
| Produit Hauteur Net | 157 mm |
| Produit Largeur Net | 56 mm |
| Poids net | 0.139 kg |

Safety Information

| | |
|------------------------|--|
| Performance Level (PL) | Up to e |
| B10d Value | Operations to Bottom Position 968 000 Operations to Middle Position 2 million |

Technique

| | |
|--|---|
| Interface de communication | Contacts |
| Configuration Connexion | Depends on bottom part |
| Maximum Switching Current | Circuit principal 0.02 mA |
| Maximum Switching Voltage | Circuit principal 30 V |
| Minimum Switching Capacity | Main Circuit 8 mA, 10 VDC |
| Number of Contacts CO | 2 |
| Number of Contacts NC | 0 |
| Number of Contacts NO | 0 |
| Rated Operational Current DC-12 (I_{θ}) | (24 V) 0.02 A |
| Tension | 24 V DC |
| Informations techniques | Operating force: Approx. 15 N for three-position button (ON), Approx. 45 N for three-position button (OFF), Approx. 2.5 N for top/front pushbutton; Mechanical service life: 1 million cycles, top to middle position, 100 000 cycles, middle to bottom position, and top/front push button |

Technique UL/CSA

| | |
|-----------------------|---|
| Enclosure Type UL/CSA | 1 |
|-----------------------|---|

Environnement

| | |
|------------------------------|--------------------------|
| Température de l'air ambiant | Operation -10 ... +70 °C |
| Indice de protection | IP65 |

| | |
|-------------------|--|
| Matériau | Handle: Polyamide and Noryl Rubber: Neoprene |
| REACH Declaration | 2CMT2022-006480 |
| Informations RoHS | 2CMT2022-006499 |
| Statut RoHS | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Certificats et Déclarations (Numéro de document)

| | |
|-------------------------------------|-------------------------|
| CQC Certificate | No certification needed |
| Certificat ecULus | 2TLC010062D0201 |
| Declaration of Conformity - CCC | No declaration needed |
| Déclaration de Conformité - CE | 2TLC172022D0201 |
| Declaration of Conformity - UKCA | 2TLC010152D0201 |
| SEMKO Certificate | 2TLC172032D0201 |

Emballage

| | |
|--------------------------------|---------------|
| Emballage Niveau 1 Unités | 1 pièce |
| Emballage Niveau 1 Largeur | 0.286 m |
| Emballage Niveau 1 Longueur | 0.126 m |
| Emballage Niveau 1 Hauteur | 0.103 m |
| Emballage Niveau 1 Poids | 0.283 kg |
| Emballage Niveau 1 EAN | 7350024459760 |

Classifications

| | |
|---|----------------------------------|
| eClass | V11.0 : 27371238 |
| ETIM 7 | EC002571 - Agreement switch |
| ETIM 8 | EC002571 - Agreement switch |
| ETIM 9 | EC002571 - Agreement switch |
| Code de catégorie granulaire IDEA (IGCC) | 5219 >> Switch part or accessory |
| UNSPSC | 39122221 |
| Code de classification d'objet | B |

Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Produits pour la sécurité → Commandes → Poignée à trois positions JSHD4

