


PRODUCT-DETAILS

TR/U-CG

TR/U-CG RTC



Informations générales

| | |
|------------------------------|-----------------|
| Extension du type de produit | TR/U-CG |
| Code de produit | 2CKA006300A1647 |
| EAN | 4011395297315 |
| Description courte | TR/U-CG RTC |

| | |
|--------------------|--|
| Description longue | <p>Ordering possible only in connection with the design ID. Makes possible the individual configuration via a web configuration tool: tacteo-configurator.my.busch-jaeger.de. Individual configuration with logos and/or ICONs and/or colours according to customer specifications. Support of KNX functions through innovative colour concept (yellow=lighting, blue=blind, orange=RTC, magenta=scene and white=neutral/no function assigned) or standard illumination red/green. With integrated proximity function. The controller is a constant room temperature controller for ventilator convectors (fan coils) in 2-pipe and 4-pipe systems and conventional heating or cooling systems. The fan stage can be switched manually or in automatic mode. Class of temperature controller 1 Contribution to space heating energy efficiency 1,0%. With integrated KNX bus coupler. Number of bus subscribers: 1 with separate 24 V auxiliary power supply</p> |
|--------------------|--|

Installation

| | |
|-------------------------|--------------------|
| Instructions et manuels | No document needed |
|-------------------------|--------------------|

Technique

| | |
|--|--------------------|
| Fiche produit, informations techniques | No document needed |
|--|--------------------|

| | |
|------------------------|--|
| Compatible Bus Systems | KNX (TP) |
| Product Range | KNX |
| Design Range | tacteo |
| Type de montage | Surface Mounted |
| Poids de la batterie | 0 g |
| Application Function | Blind / Shutter / Shading Control Electrical Load and Light Control Room Climate Control |

Environnement

| | |
|---|---|
| Température de l'air ambiant | Operation -5 ... +45 °C |
| Indice de protection | IP20 |
| Statut RoHS | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
| Informations RoHS | 9AKK104295D8727 |
| REACH Declaration | 2CKA309999E9999 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

Dimensions

| | |
|----------------------|---------|
| Produit Largeur Net | 86 mm |
| Produit Hauteur Net | 86 mm |
| Produit Longueur Net | 34 mm |
| Poids net | 212.6 g |

Certificats et Déclarations (Numéro de document)

| | |
|--------------------------------|-----------------|
| Déclaration de Conformité - CE | 2CKA100000E4195 |
|--------------------------------|-----------------|

Classifications

| | |
|----------------|--|
| ETIM 8 | EC001101 - Room temperature controller for bus system |
| ETIM 9 | EC001101 - Room temperature controller for bus system |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 9032 10 20 |
| eClass | V11.0 : 27143133 |

Catégories

Produits basse tension → Home and Building Automation → KNX → User Operation → ABB tacteo® → Thermostats

