

Features

Use: Indoor
Type of installation: TRACK
Emission: ADJUSTABLE
Optics: SPOT
Beam: 15 - 38°
Colour: WHITE
Dimming: ON/OFF
Emergency: NO
L: 230mm
A: Ø90mm
H: 175mm
Warranty: 5 years
Weight: 1.3kg

Tech data

Luminaire input power: 42W
IP: 20
Insulation class: II
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 38W
Colour temperature: 3000K
CRI: >90
LED lifespan: 30000h L70 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

SCREENS



DALÌ : LENTE 55° PER 40W


106119.00

COMPLETION ACCESSORIES



DALÌ : INSERTO ORO OPACO PER 40W

106120.15



DALÌ : HONEYCOMB PER 40W

106121.02