

Features

Use: Indoor
Type of installation: RECESSED, SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL
Colour: CAFFE
Dimming: WITH ACCESSORY
Emergency: NO
L: Ø 1440mm
A: 40mm
H: 40mm
Made in: ITALY
Warranty: 5 years
Weight: 7.5kg

Tech data

Luminaire input power: 66.1W
Luminaire luminous flux: 4459lm
IP: 40
Insulation class: III
Supply voltage: MAX 1.8A
UGR: <19
SELV: No

Source

Light source: LED
Source power: 62W
Source luminous flux: 9606lm
Colour temperature: 4000K
CRI: >90
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

MOUNTING ACCESSORIES



ARK: KIT INCASSO PER 1440

109808.99




HALOS: ROSONE ALIM. REMOTA CAFFE

105157.20



HALOS: ROSONE DOPPIA ALIM. REMOTA CAFFE

105158.20



HALOS: KIT 4 CAVI SOSPENSIONE L.3000


105159.99



CAVO ALIMENTAZIONE L=3000 3X1.5 TRASP

109001.00

ELECTRICAL ACCESSORIES



HALOS: ALIMENTATORE ON/OFF

105147.99



HALOS: ROSONE-N ALIM. ON/OFF CAFFE


105151.20



HALOS: ROSONE-N DOPPIA ALIM ON/OFF CAFFE

105155.20

DIMMABLE ACCESSORIES



HALOS: ALIMENTATORE DALI/PUSH

105148.99



HALOS: ROSONE-N ALIM. DALI/PUSH CAFFE

105152.20



HALOS: ROSONE-N DOPPIA ALIM D/PUSH CAFFE

105156.20