



| | |
|----------------------------------|-------------------------------|
| Product designation | Surge Protection Device (SPD) |
| Product type designation | SG2 |
| Operating voltage type | AC |
| Application | AC Power lines |
| Number of poles | 2P |
| Number of DIN modules | 1 |
| SPD according to IEC/EN 61643-11 | YES |

Electrical features

| | | |
|---|---------|--------------------|
| IEC Maximum continuous voltage U_c | V | 320 |
| IEC Maximum discharge current I_{max} 8/20 (L-N/N-PE) | kA | 15 |
| IEC Rated discharge current (IEC) I_n 8/20 (L-N/N-PE) | kA | 5 |
| IEC Voltage protection level U_p (L-N/N-PE) | kV | <1.5 |
| IEC Follow current I_f (N-PE) rms | A | No |
| Tripping time t_a (L-N/N-PE) | ns | <25 |
| Thermal insulation protection | | YES |
| IEC Backup protection fuse with supply fuse >63A (L-N/N-PE) | Class/A | 63A Gg |
| IEC Maximum short circuit current at 50Hz | kA | 6 |
| Status indicator - operating / end of life | | Frontal indication |


Ambient conditions

| | | | |
|-----------------------|-----|----|------|
| Operating temperature | min | °C | -40 |
| | max | °C | +85 |
| Max altitude | | m | 2000 |


Mechanical features

| | | |
|--------------------------------------|-----------------|-------------------|
| Fixing | | Din rail |
| Conductor section Flexible max (IEC) | mm ² | 4 (L,N) / 25 (PE) |
| Conductor section Rigid max (IEC) | mm ² | 6 (L,N) / 35 (PE) |
| Weight | g | 144 |

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

IEC/EN 61643-11

Certificates

EAC

ETIM classification

ETIM 8.0

EC000941 -
Surge protection
device for power
supply systems