




OUTDOOR RESIDENTIAL/COMMERCIAL AREAS

EXTRO



EXTRO RANGE - MULTIFUNCTIONAL ILLUMINATION DEVICES - IP55 - CLASS I						
Ballast	Voltage	Lamp power	Lamp	Lamp holder	Colours	
					Graphite Grey	White
 KCG ELECTROMAGNETIC	230 V - 50 Hz	2 x 18 W	FSD	2G11	GW 82284	GW 82212
		70 W	SE ⁽¹⁾	E27	GW 82281 S	GW 82214 S
		80 W	QE		GW 82283 Q	GW 82218 Q
		100 W	ME		GW 82282 M	GW 82216 M
		MAX 100 W	IA/IB/FBT		GW 82206	GW 82202
 EVG ELECTRONIC	220/240 V - 50/60 Hz	2 x 26-32 W	FSM	GX24q-3	GW 82286	GW 82242
		1 x 26-32 W			GW 82246 ⁽²⁾	GW 82247 ⁽²⁾
 EVG ELECTRONIC EMERGENCY						

NOTE:

⁽¹⁾ Use lamp with built-in ignitor

⁽²⁾ Emergency version NiCd batteries for high temperature. 1 Hours autonomy luminous flux 135/90 lm

COMPLEMENTARY ITEMS		Materiale	Height	Colours	
				Graphite Grey	White
WALL INSTALLATION	Swivel bracket	Die-cast aluminium		GW 82290	GW 82255
	Angle bracket			GW 82291	GW 82253
INSTALLATION ON COLUMNS	Single luminaires support column	Extruded aluminium	1,3 m	GW 82292	GW 82259
	Single luminaires support column		3,0 m	GW 82293	GW 82263
	Support column for single device complete with IP55 plates for 3 system range modules		1,3 m	GW 82294	GW 82273
	Double luminaire support column		1,3 m	GW 82295	GW 82261
	Rectangular base for support 1300 Height		3,0 m	GW 82296	GW 82265
INSTALLATION ON POLE Ø 60 mm	Pole mounting singles swivel bracket	Die-cast aluminium		GW 82298	GW 82257
	Pole mounting double swivel bracket			GW 82299	GW 82270
STEEL POLES Ø 60 mm	Cylindrical poles	Galvanized steel	1,0 m	GW 86775	
			2,0 m	GW 86776	
			3,0 m	GW 86777	
			5,0 m	GW 86778	
	Round base for fixing steel poles height max 2 m			GW 82289	
FIBERGLASS POLES Ø 60 mm	Cylindrical fiberglass poles	Fiberglass		GW 86771	
				GW 86772	
				GW 86773	
SPARE PARTS	Tempered glass			GW 88272	