

SORAA GU10 230V 5.4W DIMMER COMPATIBILITY LIST - International

Manufacturer	Brand	Model	Edge Trigger	Dim (%)	Note
AURORA		AU-DSP400X	L	1 Lamp: 51% 2,3 Lamps: 20%	Please See Footnote
AURORA		AU-DSP651	L	16%	Please See Footnote
Berker		2830 10	L	NC	Please See Footnote
Berker		2861-10	L	25%	Please See Footnote
Berker		286710	T	31%	
Busch		2247 U	L	1 Lamp: 15% 2,3 Lamps: 56%	Please See Footnote
Busch		2250 U	L	1,3 Lamps: 20% 2 Lamps: 52%	Please See Footnote
Busch		6513 U-102	T	44%	
Busch		6523 U102	L	4%	Please See Footnote
Click		MD9042	L	21%	Please See Footnote
Diginet		DGLCDM400	T	13%	
Electron		DMR.730	T	0%	
Electron		DMR.731	T	0%	
Elko		315GLE PH	T	1,2 Lamps: NC 3 lamps: 16%	
Eltako		EUD61NPN-UC	T	12%	
Feller		40.600RL	L	1 Lamp: 38% 2,3 Lamps: 12%	Please See Footnote
Feller		40300.RC	T	1 Lamp: NC 2,3 Lamps: 15%	
Feller		40420.RLC	Adaptive	NC	
Fibaro		FGD212 EU v3.2	T	32%	
Futronix		P400	L	NC	Please See Footnote
GIRA		0307 00 102	T	31%	
GIRA		2262 00 / 100	L	7%	Please See Footnote
GIRA		System 2000-2390 00/100	L	16%	Please See Footnote
Govena		ProLED250	L	28%	Please See Footnote
Helvar	452	DALI Rotary	Adaptive T	12%	
Helvar	454	DALI Slider	T	10%	
Hamilton		H-LEDSTAT	T	16%	
iLight		SCI0405S	L	NC	Please See Footnote
iLight		SCT0405S	T	1,2 Lamps: 27% 3 Lamps: 19%	
JUNG		225 NV	L	25%	Please See Footnote

SORAA GU10 230V 5.4W DIMMER COMPATIBILITY LIST - International

Manufacturer	Brand	Model	Edge Trigger	Dim (%)	Note
JUNG		225 TDE	T	33%	
JUNG		266 G DE	L	1,2 Lamps: 19% 3 Lamps: 58%	Please See Footnote
JUNG		1224 LED UDE	T	14%	
JUNG		1271 LED DE	L	23%	Please See Footnote
Legrand		450P	Adaptive	NC	
Legrand		665114 A 14W3731	L	20%	Please See Footnote
Legrand		AR400A3PM	T	32%	
Legrand		EM400A3P	T	32%	
Lunatone	DALI PD	86458619 (25W LED)	T	2%	
Lunatone	DALI PD	86458619-300 (300W LED)	T	4%	
Lutron	Grafik eye	QSGR-6PCE	L	NC	Please See Footnote
Lutron	Grafik eye	QSGR-6PCE+NGRX-ELVI-CE	T	0%	
Lutron	Grafik eye	QSNE-4A-D	T	21%	
Lutron	Grafik eye	QSNE-4A-D	L	22%	Please See Footnote
Lutron	LCP128	CCP-1L1A-240FT-LCP-CGP1319	T	10%	
Lutron	LCP128	CCP-1L1A-240FT-LCP-CGP1319	L	57%	Please See Footnote
Lutron	Lyneo	LSSI-501B-FAW-M	L	71%	Please See Footnote
Lutron	Rania	RNDU-252B-FAW-M	T	NC	
Lutron	Rania	RNDU-425B-FAW-M	T	NC	
Maintronic		DAD1200 DALI	T	46%	
MARBO	Crabtree	DV21912	L	1 Lamp: 47% 2,3 Lamps: 14%	Please See Footnote
Merten		MEG5131-0000 (SBD400R-1)	L	10%	Please See Footnote
Merten		MEG5133-0000 (SBD600RL)	L	12%	Please See Footnote
Merten		MEG5136-0000 (SBD315RC)	T	1 Lamp: NC 2,3 Lamps: 16%	
MK	K1501 WHILV	47543SL	L	NC	Please See Footnote
MK	K1511 WHILV		L	NC	Please See Footnote
MK	K1522 WHILV	43395PL	L	49%	Please See Footnote
MK	K1523WHILV	52470SL	L	20%	Please See Footnote
MK	K1526		L	54%	Please See Footnote
Mode Lighting	Evolution	EVO-SGP	T		

SORAA GU10 230V 5.4W DIMMER COMPATIBILITY LIST - International

Manufacturer	Brand	Model	Edge Trigger	Dim (%)	Note
Mode Lighting	Evolution	EVO-SGP	L	NC	Please See Footnote
Mode Lighting	Mirage	MP-10-01	L	93%	Please See Footnote
Panasonic		WEG57813	L	1,2 Lamps: 15% 3 Lamps: 35%	Please See Footnote
Philips	Dynalite	DGLM402	L	NC	Please See Footnote
Philips	Dynalite	DGTM402	T	40%	
Philips	Dynalite	DGLED401	T	1,2 Lamps: 22% 3 Lamps: 20%	
Rako		RMT500	T	0%	
Schneider		GD1G2W4	L	67%	Please See Footnote
Schneider		SBD315RC	T	1 Lamp: NC 2,3 Lamps: 16%	
Siemens		5TC8 263	L	10%	Please See Footnote
Vadsbo		LD 220 (E 13 774 40)	T	3%	
Varilight		HQ7W	L	1,2 Lamps: 20% 3 Lamps: 38%	Please See Footnote
Varilight		IQP401W	L	NC	Please See Footnote
Varilight	V-Pro	JQP401W	T	NC	
Vossloh Schwabe		554591	T	6%	
Vossloh Schwabe		554592	T	6%	
Zano		WH400	L	1 LampL 27% 2,3 Lamps: 15%	Please See Footnote
Zano		ZGRIDLED	T	NC	
Zano		ZGRID500	L	32%	Please See Footnote

Notes: Compatibility tests are conducted by Soraa only as guidance for the user

All tests are conducted under bench conditions; results may differ from test results depending on conditions at the application site

Results may vary due to variability in component choices and manufacturing processes by the transformer manufacturer

This lamp may emit a low level of audible noise when used with some leading edge dimmers. Testing with the intended dimmer is recommended to ensure acceptable audible levels at the application site.

	Dims to < 20%
NC	Not compatible
Blank cell	Not tested