

SORAA GU10 230V 7.5W - DIMMER COMPATIBILITY - International

| Manufacturer | Brand | Model | Edge Trigger | Dim (%) | Note |
|---------------|-------------|------------------|--------------|--------------------------------|---------------------|
| Europe | | | | | |
| AURORA | | AU-DSP400X | L | 18% | Please See Footnote |
| AURORA | | AU-DSP651 | L | 12% | Please See Footnote |
| Berker | | 2830 10 | L | 1 Lamp: N C 2,3 Lamps: 0% | Please See Footnote |
| Berker | | 2861-10 | T | NC | |
| Berker | | 286710 | T | 1,2 Lamps: 24% 3 Lamps: 20% | |
| Busch | | 2247 U | L | 8% | Please See Footnote |
| Busch | | 2250 U | L | 1 Lamp: N C 2,3 Lamps: 6% | Please See Footnote |
| Busch | | 6513-102 | T | NC | |
| Busch | | 6523 U102 | L | 4% | Please See Footnote |
| Click | | MD9042 | L | 21% | Please See Footnote |
| Clipsal | | 32E450UDM (*) | T | NC | |
| Clipsal | | 32ELEDM (*) | T | NC | |
| DIGINET | | DGLCDM400 | T | 9% | |
| Electron | | DMR.730 | T | 0% | |
| Electron | | DMR.731 | T | 0% | |
| ELKO | | 315GLE PH | T | 1 Lamp: N C 2,3 Lamps: 13% | |
| Eltako | | EUD12NPN-UC | T | 11% | |
| Eltako | | EUD61NPN-UC | T | 10% | |
| FELLER | | 3314.12.FMI.61 | T | NC | |
| FELLER | | 40200.LED.FMI.61 | T | NC | |
| FELLER | | 40300.RC | T | 1 Lamp: N C 2,3 Lamps: 13% | |
| FELLER | | 40420.RLC | T | NC | |
| FELLER | | 40600.RL | L | 13% | Please See Footnote |
| Fibaro | Dimmer 2 | FGD-212 | Adaptive T | 18% | |
| GIRA | | 0307 00 102 | T | 1 Lamp: 23% 2,3 Lamps: 20% | |
| GIRA | | 2262 00 / 100 | L | 9% | Please See Footnote |
| GIRA | System 2000 | 2390 00 | L | 15% | Please See Footnote |
| Govena | | ProLED225 | L | 16% | Please See Footnote |
| HAMILTON | | H-LEDSTAT | T | 1 Lamp: N C 2,3 Lamps: 13% | |
| Helvar | Digidim | 452 (DALI) | Adaptive T | 15% | |
| Helvar | | 454 (DALI) | T | 16% | |
| JUNG | | 1224 LED UDE | T | 23% | |
| JUNG | | 1271 LED DE | L | 20% | Please See Footnote |

SORAA GU10 230V 7.5W - DIMMER COMPATIBILITY - International

| Manufacturer | Brand | Model | Edge Trigger | Dim (%) | Note |
|---------------|-----------------------------------------------------|------------------------|--------------|--------------------------------|---------------------|
| Europe | | | | | |
| JUNG | | 225 NV | L | 24% | Please See Footnote |
| JUNG | | 225 TDE | T | 24% | |
| JUNG | | 266 GDE | L | 19% | Please See Footnote |
| Legrand | | 665114 A 14W3731 | L | 20% | Please See Footnote |
| Lunatone | DALI PD | 86458619 | T | 2% | |
| Lunatone | DALI PD | 300 86458619-300 | T | 3% | |
| Lutron | Energy Savr Node QS (for Quantum and QS systems) | QSNE-4A-D | T | 17% | |
| Lutron | Energy Savr Node QS (for Quantum and QS systems) | QSNE-4A-D | L | 1,2 Lamps: 15% 3 Lamps: 23% | Please See Footnote |
| Lutron | Grafik eye QS | QSGR-6PCE | L | NC | Please See Footnote |
| Lutron | Grafik eye QS | QSGR-6PCE+NGRX-ELVI-CE | T | 0% | |
| Lutron | Homeworks | LQSE-4A-D (*) | T | 17% | |
| Lutron | Homeworks | LQSE-4A-D (*) | L | 1,2 Lamps: 15% 3 Lamps: 23% | Please See Footnote |
| Lutron | LCP128 | LP-RPM-4A-230 | T | 0% | |
| Lutron | LCP128 | LP-RPM-4U-240 | L | NC | Please See Footnote |
| Lutron | LYNEO | LSSI-501 | L | 1,2 Lamps: 9% 3 Lamps: NC | Please See Footnote |
| Lutron | RANIA | RNDU-252B-FAW-M | T | NC | |
| Lutron | RANIA | RNSU-452B-FAW-M | T | NC | |
| Maintronic | | DAD1200 | T | NC | |
| MARBO | Crabtree | DV21912 | L | 16% | Please See Footnote |
| Merten | SBD400R-1 | MEG5131-0000 | L | 15% | Please See Footnote |
| Merten | SBD600RL | MEG5133-0000 | L | 9% | Please See Footnote |
| Merten | SBD315RC | MEG5136-0000 | T | 1 Lamp: N C 2,3 Lamps: 13% | |
| MK | K1501 WHILV | 47543SL | L | 1 Lamp: N C 2,3 Lamps: 20% | Please See Footnote |
| MK | K1511 WHILV | 524675L | L | 1 Lamp: N C 2,3 Lamps: 7% | Please See Footnote |
| MK | K1522 WHILV | 43395PL | L | NC | Please See Footnote |
| MK | K1523WHILV | 52470SL | L | 19% | Please See Footnote |
| MK | K1526WHI | 50067778 | L | 27% | Please See Footnote |
| Mode Lighting | Evolution | EVO-SGP | L | NC | Please See Footnote |
| Mode Lighting | Mirage | MP-10-01 | L | NC | Please See Footnote |
| Mode Lighting | Mirage / Tiger / Evolution | TRAILING EDGE CARD | T | 0% | |
| Panasonic | | WEG57813 | L | 6% | Please See Footnote |
| Philips | Dynalite | DGLM402 | L | NC | Please See Footnote |

SORAA GU10 230V 7.5W - DIMMER COMPATIBILITY - International

| Manufacturer | Brand | Model | Edge Trigger | Dim (%) | Note |
|---------------|----------|-----------------------------|--------------|-------------------------------|---------------------|
| Europe | | | | | |
| Philips | Dynalite | DGTM402 | T | NC | |
| Philips | Dynalite | DGLED401 | T | 20% | |
| Rako | | RDT500 with control RCP07-W | T | 0% | |
| Rako | | RMT500 with control RCP07-W | T | 0% | |
| Schneider | | GD1G2W4 | L | 18% | Please See Footnote |
| Schneider | | SBD315RC | T | 1 Lamp: N C 2,3 Lamps: 11% | |
| Schneider | | REG-K/2x230/300W | T | NC | |
| Siemens | | 5TC8 263 | L | 16% | Please See Footnote |
| Tridonic | | DALI-PCD 1-300 one4all | Adaptive-T | 24% | |
| VADSBO | | LD220 | T | 2% | |
| Varilight | | HQ7W 120W | L | 19% | Please See Footnote |
| Varilight | | IQP401W | L | NC | Please See Footnote |
| Varilight | V-PRO | JQP401W | T | 3% | |
| Zano | | WH400 | L | 17% | Please See Footnote |
| Zano | | ZGRIDLED | T | NC | |

Notes:

Compatibility tests are conducted by Soraa (unless stated otherwise) only as guidance for the user

All tests are conducted under bench conditions; results may differ from test results depending on conditions at the application site
Results may vary due to variability in component choices and manufacturing processes by the dimmer manufacturer

This lamp may emit a low level of audible noise when used with some leading edge dimmers. Testing with the intended dimmer is recommended to ensure acceptable audible levels at the application site.

Regards compatibility tests conducted by dimmer manufacturer, please contact the manufacturer for more details and/or reports.

(*) Test results with this dimmer added to the compatibility list as of Revision D

| | |
|------------|-----------------------------------------------|
| --% | Dims to < 20% (of the measured light output) |
| --% | Dims to 20-30% (of the measured light output) |
| NC | Not compatible (or dims to >30%) |
| Blank cell | Not tested |