

CleanSpace™ WORK HEPA Particulate Filter (Pk 3)



| PRODUCT CODE | CS3022WORK |
|-----------------------------|--|
| PRODUCT NAME | CleanSpace WORK HEPA Particulate Filter (Pk 3) |
| DESCRIPTION | CleanSpace WORK HEPA particulate filters are suitable for protection against airborne particulates (dust mists, fumes) with a particulate filtration efficiency \geq 99.97%. |
| | CleanSpace WORK filters are compatible with the CleanSpace WORK power unit (CS3001WORK). |
| | IMPORTANT: When selecting a CleanSpace filter please consult a Health and Safety specialist for advice on the appropriate respiratory equipment and filter use. |
| APPROVALS | Standard & Classification |
| | NIOSH PAPR |
| FEATURES | Convenient to use Filter and filter cover integrated into a single item Easy to fit and remove from the power unit No requirement for a filter adaptor AirSensit® Technology assists with optimal filter usage |
| SPECIFICATIONS | Packaged Weight & Dimensions: 0.33 lbs (150g), 180mm x 160mm x 45mm (3 Pack) Product Weight & Dimensions: 0.08 lbs (38g), 43mm x 47mm x 130mm (single filter) Filtration performance: ≥ 99.97% filtration efficiency for particulates Sold in a pack of 3 filters |
| MATERIALS | Borosilicate microfibre media ABS (acrylonitrile butadiene styrene) Plastic Casing Polyurethane Seal |
| USE & STORAGE CONDITIONS | Use temperature range: -10°C to +45°C (14°F to +113°F) at < 90% relative humidity Storage conditions: +10°C to +30°C (+50°F to +86°F) at < 75% relative humidity Store away from direct sunlight, grease and oil Packaged Shelf life: 3 years from manufacturing date |
| APPLICATIONS | Suitable for environments which require respiratory protection against airborne particulate contaminates |
| | |

North America (Toll Free): +1 877-256-7723 (1877CLNSPCE)

 $\underline{orders USA@clean space technology.com}$

Uncontrolled if downloaded or printed from the internet.







DATA SHEET (NIOSH)





Examples (use is not limited to these examples):

- Construction Cutting and grinding concrete, stone, brickwork, steel; sanding plaster, handing cement or other fine dusts
- Woodwork Cutting, turning or sanding timber
- Agriculture mowing, reaping and mulching operations; processing or handling animal feeds, grain
 or other dusty substances
- Restoration, maintenance and cleaning

CleanSpace WORK is suitable for applications where decontamination is required. Following decontamination operations the filter must be replaced.

LIMITATIONS

CleanSpace respirators are air filtering, fan assisted, positive pressure systems and designed to be worn in environments where there is sufficient oxygen to breathe safely. Do not use CleanSpace WORK in environments that are immediately dangerous to life or health (IDLH), to protect against gases/vapors, or in oxygen enriched or deficient atmospheres.

EDUCATION

Contact ordersUSA@cleanspacetechnology.com or visit the CleanSpace website for details.

WARRANTY

Visit www.cleanspacetechnology.com/warranty to read important Warranty information and complete the Warranty Registration Online Form for CleanSpace Products. Consumable parts are warranted up to the point of use, provided they have been stored correctly and are within their expiry date.

CleanSpace recommends filters are replaced regularly.

North America (Toll Free): +1 877-256-7723 (1877CLNSPCE)

ordersUSA@cleanspacetechnology.com

Uncontrolled if downloaded or printed from the internet.



