

# **Red Hot<sup>®</sup> Burn Protection Apron** #BP1055



# PRODUCT INFORMATION

| PRODUCT                    | Red Hot <sup>®</sup> Apron (35")                    | Red Hot <sup>®</sup> Apron (42")                    |
|----------------------------|---|---|
| Item stock no.             | BP1055-35   | BP1055-42   |
| UPC number (c.u.)          | 618206 06601  | 618206 06602  |
| Unit of measure            | Sold individually                                   | Sold individually                                   |
| Minimum order qty<br>(MOQ) | 24 Aprons<br>*Bundled when shipped with other items | 24 Aprons<br>*Bundled when shipped with other items |
| Gross weight (MOQ)         | 25 lbs (11.34 kg)                                   | 29 lbs (13.2 kg)                                    |
| Dimensions (MOQ)           | 20 x 16x 12 in<br>(50.8 x 40.6 x 30.5 cm)           | 20 x 16x 12 in<br>(50.8 x 40.6 x 30.5 cm)           |
| Cu. Ft. (MOQ)              | 2.22 ft <sup>3</sup>                                | 2.22 ft <sup>3</sup>                                |
| Country of origin          | USA   | USA   |
| Harmonization code         | 6211.43.0091  | 6211.43.0091  |



# DESCRIPTION

Our Red Hot Apron was developed to protect users against burn injuries from splattering oils, hot liquids, steam and hot equipment.

Goal: Reduce exposure to costly litigation and medical expenses from workplace burn injuries.

Polypropylene webbing

Color: Red

- **Commercial Fishing**
- Degreasing

# **COMPOSITION & PHYSICAL DETAILS**

#### Body

- PVC coated Polyester and Nylon knit 0
- Color: Black 0
- Dimensions (approximate) 0
  - BP1055-35: 35 in x 24 in (89 cm x 61 cm)
  - BP1055-42: 42 in x 24 in (107 cm x 61 cm)

#### **APPLICATIONS** Food Processing 0

- **Food Preparation** 0
- 0 Janitorial
- 0
- General Industrial 0
- 0

#### Adjustable Buckle

- High impact plastic (POM)  $\cap$
- Color: Black 0

## **PERFORMANCE & REGULATORY**

- Complies with 21 CFR, parts 170-199 for direct for contact applications. Ο
- Confirms to CFR 1303 for lead content of 11 for HACCP 0
- 0 CAL TB117 Flammability Standard: Passed This test is a small scale flammability standard for concealed, resilient materials. Standard 16 CFR, part 1632, class B: Passed 0
- This Federal standard prescribes a test to determine the ignition resistance of materials/fabrics used in mattresses and mattress pads. The ignition source is SRM 1196 (Standard Reference Material cigarette), available from the National Institute of Standards and Technology.

Strapping

0

0

- AATCC Standard 147-1988, Antibacterial Activity Assessment: 0
  - Staphylococcus Aureus: 100% inhibition
  - Klebsiella Pneumoniae: 100% inhibition
- Fed. Std. 191-5512: 200 psi 0

This test method is intended for determining the resistance of coated cloth to the passage of water under high pressure.





### CARE

Hand wash with a mild soap (preferably antibacterial) and warm water. If using the product around food, always use a food safe soap. To dry, wipe outer surfaces with a clean, dry towel and hang until completely dry. **ATTENTION**: Do not dry clean. Do not machine wash or dry. Do not use bleach.

# SHELF LIFE

This product is non-perishable.



- 1. Products that provide "cut resistance" and "cut protection" or "puncture resistance" and "puncture protection" do not completely prevent or eliminate the potential for cuts or punctures.
- 2. This product is not intended or tested to provide protection against powered blades, serrated or other sharp or rotating equipment and should not be used around such equipment.
- 3. This product may contain natural rubber latex which may cause allergic reactions in some individuals.
- 4. Products that provide "abrasion resistance" or "abrasion protection" do not completely prevent or eliminate the potential for abrasion-related injuries.
- 5. Products that provide "chemical resistance" or "chemical protection" do not completely prevent or eliminate the potential for injury due to chemical exposure.
- 6. Products that provide "resistance" to oil or grease or which are "oil repellant" do not completely prevent or eliminate the potential for oil or liquid penetration or absorption.
- 7. Products that provide protection or resistance against heat or cold are not intended for use in extreme temperatures use only as specified.

Spellbound Development Group, Inc. recommends product users to always use caution and care when handling tools, devices and other products used in the workplace. Always wear the appropriate personal protective equipment. Any information or data provided in this datasheet is based upon Spellbound Development Group, Inc.'s current knowledge and understanding of the subject matter, and is offered solely as a possible suggestion for use in making your own decisions or product choices.

Spellbound Development Group, Inc. recommends product users conduct all appropriate testing or other evaluations to determine the suitability of Spellbound Development Group, Inc.'s products for a particular purpose or use within a particular environment. It is the responsibility of a product user to assess the level of risk and to determine the protective equipment required and suitability for the use intended by the user. Spellbound Development Group, Inc. may, from time to time, revise the information on this data sheet as new information, knowledge or experience becomes available. According to current OSHA regulations, the employer has the final responsibility for selecting personal protective equipment suitable for the use intended.

#### WARRANTY

Spellbound Development Group, Inc. and CrewSafe do not warrant, expressed or implied that our products eliminate losses due to injuries and accidents. We do not claim or warrant, expressed or implied, that our products are intended to prevent or reverse any upward or downward trend associated with losses in the workplace.

Spellbound Development Group, Inc. and CrewSafe warrant its products to be free of defects in material and workmanship for 90 days after shipment from Spellbound Development Group, Inc. and or CrewSafe. Should a defect be found within this first 90 day period, Spellbound Development Group, Inc. and/or CrewSafe shall replace the product with like or similar product at their cost.

Products purchased from an <u>authorized</u> Spellbound Development Group, Inc. distributor must be returned to the distributor. Spellbound Development Group, Inc.'s and CrewSafe's liability under this warranty is limited to the replacement of defective product, and in no event shall it be liable for consequential or indirect damages or losses.

This warranty shall not apply to product subjected to accidental damage, misuse, alteration, or deterioration due to extended storage or exposure. Nor shall it apply to product requiring normal replacement due to wear.

This warranty constitutes Spellbound Development Group, Inc.'s and CrewSafe's exclusive limited warranty, there being no other warranties, expressed or implied, including any warranty of merchantability or fitness for a particular purpose.

#### CONFIDENTIAL

The information contained in this document is the property of Spellbound Development Group, Inc., and represents proprietary information to which Spellbound Development Group, Inc. retains exclusive rights. This information is issued in strict confidence and possession of it does not convey permission to present it to any third party. Such permission is granted only by specific law. Intellectual rights, copyright & confidential information rights are retained by Spellbound Development Group, Inc.