

# Cut, Abrasion, Puncture, and Heat Resistant Cowhide Leather Drivers Style Gloves with Aralene® Liner

## DESCRIPTION

These cut-resistant, heat-resistant, and flame-resistant driver's gloves feature an Aralene® (enhanced aramid fiber) cut-resistant inner liner. The premium-grade beige grain cowhide leather shell has a gunn-cut pattern. These gloves have a keystone thumb for an ergonomic fit and an open cuff. This glove is sewn with aramid fiber and is great for industrial jobs and work requiring cut protection.

## INDUSTRY

|             |               |
|-------------|---------------|
| Automotive  | Manufacturing |
| Steel Mills | Construction  |
| Maintenance | Mining        |

## FEATURES

- Premium-grade grain cowhide leather shell
- Sewn with aramid fiber for added durability and cut and heat resistance
- Ergonomic keystone thumb improves durability, comfort, and dexterity while reducing hand fatigue
- Overcast color on hem for easy size identification
- Open cuff allows for easy donning and removal
- EN 407 Levels: X3XXXX
- Tested to ASTM F2675
- Arc Rating (ATPV) = 35 Cal/cm²
- Heat Attenuation Factor (HAF) = 94%
- NFPA 70E Arc Flash PPE Category: 3



## ITEM CR3200

## SIZES 6(XS)-11(2XL)

### Meets ANSI/ISEA 105-2016 standard

- Cut Level A4
- ASTM F2992-15 Results = 1,704 grams
- Abrasion Level 5
- Puncture Level 3
- Puncture Results: 62 Newtons



## SPECIFICATIONS

| SHELL            | COLOR         | GRADE             | LINER             | CUFF                          | THUMB                           | CUT      | ASTM F2992-15 RESULTS | ABRASION | PUNCTURE |
|------------------|---------------|-------------------|-------------------|-------------------------------|---------------------------------|----------|-----------------------|----------|----------|
| Grain Cowhide    | Beige         | Premium           | Aralene®          | Open                          | Keystone                        | Level A4 | 1,704 Grams           | Level 5  | Level 3  |
| PUNCTURE RESULTS | EN 407 LEVELS | ASTM F2675 TESTED | ARC RATING (ATPV) | HEAT ATTENUATION FACTOR (HAF) | NFPA 70E ARC-FLASH PPE CATEGORY |          |                       |          |          |
| 62 Newtons       | X3XXXX        | YES               | 35 CAL/CM²        | 94%                           | 3                               |          |                       |          |          |

## PACKAGING

|                         | QUANTITY | 6(XS)          | 7(S)           | 8(M)           | 9(L)           | 10(XL)         | 11(2XL)        |
|-------------------------|----------|----------------|----------------|----------------|----------------|----------------|----------------|
| PAIR UPC                | 1        | NA             | NA             | NA             | NA             | NA             | NA             |
| INNER PACK UPC          | 12/PACK  | 810292022457   | 816679013681   | 816679013674   | 816679013667   | 816679013698   | 810292024734   |
| CASE GTIN               | 6PK/CASE | 10810292022454 | 00810292027568 | 00810292027575 | 00810292027582 | 00810292027599 | 10810292024731 |
| CASE WEIGHT (IN POUNDS) |          | 19.8           | 27             | 31             | 39             | 37             | 34             |
| OVERCAST COLOR          |          | Purple         | Red            | Green          | Brown          | Blue           | Yellow         |

13915 Radium St NW  
Ramsey, MN 55303

763-450-0110  
Sales@GlobalGlove.com

GlobalGlove.com

**Global Glove**  
& Safety Manufacturing, Inc.

