

PM30 SERIES

ANSI/ASA S3.19-1974 | CE/UKCA EN 352:2020

NRR 27dB | SNR 30.4dB

Height Adjustment to Fit Most // Fold-away Padded Headband //
Soft foam ear cups // Custom Imprinting Available

- PM3010 Black
- PM3011 Gray
- PM3022 OD Green
- PM3031 Hi-Vis Lime

Earmuff Breakdown

Headband: Polyoxymethylene (POM)
Headband Adjustment: Polyoxymethylene (POM)
Headband Cushion: Polyurethane (PU) Foam + Polyvinyl Chloride (PVC)
Ear Cup and Volume Ring: Polystyrene (PS)
Ear Cushion: Polyurethane (PU) Foam + Polyvinyl Chloride (PVC)
Foam Insert: Polyurethane

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov

Packaging

Inner Polybag: 1 unit
Case: 40 units
Made in Taiwan



NRR ATTENUATION									
FREQUENCY (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
MEANS	20.9	21.9	31.6	40.9	38.7	39.5	38.2	39.0	38.5
STANDARD DEVIATION (dB)	2.4	1.9	3.0	3.1	2.8	2.1	3.0	3.4	2.6

NRR 27dB

SNR ATTENUATION								
FREQUENCY (Hz)	63	125	250	500	1000	2000	4000	8000
MEAN ATTENUATION (dB)	17.8	18.0	22.3	27.2	37.4	33.9	37.4	38.4
STANDARD DEVIATION (dB)	3.5	2.6	2.9	3.1	3.3	2.2	3.5	5.1
APV (dB)	14.3	15.4	19.3	24.1	34.0	31.7	33.9	33.3

SNR: 30.4dB H: 33.0dB M: 37.8dB L: 21.3dB