

PRODUCT SPECIFICATION & TECHNICAL DATASHEET

UFR87 - Bizflame 88/12 Classic FR Coverall

Collection: Bizflame[™] 88/12 **Range:** Flame Resistant

Shell Fabric: Bizflame 88/12: 88%

Cotton, 12% Nylon 237g

Product information

This durable coverall offers guaranteed flame resistance for the life of garment. Suitable for a range of end uses, this item provides protection against radiant and convective heat. Ample storage options are available with a selection of practical pockets.

Standards

ASTM F1959/F1959M-12 (ATPV 8.2 CAL/CM² (HAF 69.1%)) ASTM F1506 NFPA® 2112 NFPA® 70E

Bizflame[™] 88/12

Bizflame 88/12 guarantees high performance and maximum comfort. The high cotton content provides an ultra soft hand feel while the high tenacity nylon offers excellent abrasion and tear resistance.

Flame Resistant

This industry leading flame resistant range provides multi-standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.

Features

- Dual hazard protection
- Durable, strong and long lasting brass zipper
- Two back patch pockets
- · Chest pockets
- Fold down collar
- Side elastic waist for ultimate wearer comfort



Navy, S-6XL Gray, Khaki, S-3XL



PRODUCT SPECIFICATION & TECHNICAL DATASHEET


UFR87 - Bizflame 88/12 Classic FR Coverall Commodity Code:

Test House

Cert No: MH62650

Wash care





Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	DUN14
UFR87GRRS	Grey	43.0	28.0	50.0	0.9480	0.0602	5036108373963	15036108858443
UFR87GRRM	Grey	43.0	28.0	50.0	0.9850	0.0602	5036108373956	15036108858436
UFR87GRRL	Grey	43.0	28.0	50.0	0.9690	0.0602	5036108373949	15036108858429
UFR87GRRXL	Grey	43.0	28.0	50.0	1.0660	0.0602	5036108373970	15036108858450
UFR87GRRXXL	Grey	43.0	28.0	50.0	1.0920	0.0602	5036108373987	15036108858467
UFR87GRRXXXL	Grey	43.0	28.0	50.0	1.1530	0.0602	5036108373994	15036108858474