

#C5001 Installation Instructions 1973-1980 Chevy/GM 1/2, 3/4 Ton 4wd T-Case Drop Kit

# Read and understand all instructions and warnings prior to installation of product and operation of vehicle.

Zone Offroad Products recommends this system be installed by a professional technician. In addition to these instructions, professional knowledge of disassembly/ reassembly procedures and post installation checks must be known. Minimum tool requirements include the following: Assorted metric and standard wrenches, hammer, hydraulic floor jack and a set of jack stands. See the "Special Tools Required" section for additional tools needed to complete this installation properly and safely.

#### >> PRODUCT SAFETY WARNING

Certain Zone Suspension Products are intended to improve off-road performance. Modifying your vehicle for off-road use may result in the vehicle handling differently than a factory equipped vehicle. Extreme care must be used to prevent loss of control or vehicle rollover. Failure to drive your modified vehicle safely may result in serious injury or death. Zone Offroad Products does not recommend the combined use of suspension lifts, body lifts, or other lifting devices.

You should never operate your modified vehicle under the influence of alcohol or drugs. Always drive your modified vehicle at reduced speeds to ensure your ability to control your vehicle under all driving conditions. Always wear your seat belt.

#### >>> TECHNICAL SUPPORT

*Live Chat* provides instant communication with Zone tech support. Anyone can access live chat through a link on www.zoneoffroad.com .

*www.zoneoffroad.com* may have additional information about this product including the latest instructions, videos, photos, etc.

Send an e-mail to tech@zoneoffroad.com detailing your issue for a quick response.

888.998.ZONE Call to speak directly with Zone tech support.

#### »Pre-Installation Notes

- 1. Special literature required: OE Service Manual for model/year of vehicle. Refer to manual for proper disassembly/reassembly procedures of OE and related components.
- 2. Adhere to recommendations when replacement fasteners, retainers and keepers are called out in the OE manual.
- 3. Larger rim and tire combinations may increase leverage on suspension, steering, and related components. When selecting combinations larger than OE, consider the additional stress you could be inducing on the OE and related components.
- 4. Post suspension system vehicles may experience drive line vibrations. Angles may require tuning, slider on shaft may require replacement, shafts may need to be lengthened or trued, and U-joints may need to be replaced.
- 5. Secure and properly block vehicle prior to installation of Zone Offroad Products. Always wear safety glasses when using power tools.
- 6. If installation is to be performed without a hoist, Zone Offroad Products recommends rear alterations first.
- 7. Due to payload options and initial ride height variances, the amount of lift is a base figure. Final ride height dimensions may vary in accordance to original vehicle attitude. Always measure the attitude prior to beginning installation.

#### **Difficulty Level**

easy 1 2 3 4 5 difficult

Estimated installation: 0.5 hours

## **Special Tools Required**

\_\_\_\_\_rev053113

None

### **Kit Contents**

Qty Part

- 2 T-Case Drop Spacer
- 1 Bolt Pack

## **Installation Instructions**

- 1. Locate the 2 bolts at each frame rail mounting the transmission crossmember. Support the transfer case with a hydraulic jack and remove the 4 transmission crossmember bolts. Hardware will not be reused.
- 2. Carefully lower the transfer case until the new provided spacers can be placed between the frame and the crossmember. Fasten the crossmember with the provided hardware and torque to 40 ft-lbs. Be sure the watch the clearance between the distributor cap and firewall while lower the transfer case.
- 3. With the transfer case lowered, check the engine compartment for proper clearances at the firewall and fan shroud.
- 4. Check the front driveshaft for proper clearances.