



#J5005 Installation Instructions 1993-1998 Jeep Grand Cherokee ZJ 3/4" Transfer Case Drop

Read and understand all instructions and warnings prior to installation of product and operation of vehicle.

Zone Offroad Products recommends this system be installed by a professional technician. In addition to these instructions, professional knowledge of disassembly/ reassembly procedures and post installation checks must be known. Minimum tool requirements include the following: Assorted metric and standard wrenches, hammer, hydraulic floor jack and a set of jack stands. See the "Special Tools Required" section for additional tools needed to complete this installation properly and safely.

» **PRODUCT SAFETY WARNING**

Certain Zone Suspension Products are intended to improve off-road performance. Modifying your vehicle for off-road use may result in the vehicle handling differently than a factory equipped vehicle. Extreme care must be used to prevent loss of control or vehicle rollover. Failure to drive your modified vehicle safely may result in serious injury or death. Zone Offroad Products does not recommend the combined use of suspension lifts, body lifts, or other lifting devices.

You should never operate your modified vehicle under the influence of alcohol or drugs. Always drive your modified vehicle at reduced speeds to ensure your ability to control your vehicle under all driving conditions. Always wear your seat belt.

» **TECHNICAL SUPPORT**

Live Chat provides instant communication with Zone tech support. Anyone can access live chat through a link on www.zoneoffroad.com.

www.zoneoffroad.com may have additional information about this product including the latest instructions, videos, photos, etc.

Send an e-mail to tech@zoneoffroad.com detailing your issue for a quick response.

888.998.ZONE Call to speak directly with Zone tech support.

» **PRE-INSTALLATION NOTES**

1. Special literature required: OE Service Manual for model/year of vehicle. Refer to manual for proper disassembly/reassembly procedures of OE and related components.
2. Adhere to recommendations when replacement fasteners, retainers and keepers are called out in the OE manual.
3. Larger rim and tire combinations may increase leverage on suspension, steering, and related components. When selecting combinations larger than OE, consider the additional stress you could be inducing on the OE and related components.
4. Post suspension system vehicles may experience drive line vibrations. Angles may require tuning, slider on shaft may require replacement, shafts may need to be lengthened or trued, and U-joints may need to be replaced.
5. Secure and properly block vehicle prior to installation of Zone Offroad Products. Always wear safety glasses when using power tools.
6. If installation is to be performed without a hoist, Zone Offroad Products recommends rear alterations first.
7. Due to payload options and initial ride height variances, the amount of lift is a base figure. Final ride height dimensions may vary in accordance to original vehicle attitude. Always measure the attitude prior to beginning installation.

rev061013

Kit Contents

Qty	Part
4	Transfer Case Drop Spacer
1	Bolt Pack
1	Loctite

Important Verify you have all of the kit components before beginning installation.

INSTALLATION INSTRUCTIONS

1. Park the vehicle on a clean, flat surface and block the rear wheels for safety.
2. Support the transfer case with a hydraulic jack.
3. Loosen but do not remove the 4 bolts (2 per side) mounting the transmission crossmember to the frame.
4. Remove the passenger's side crossmember bolts and lower the transfer case about 1". Position the provided transfer case drop spacers between the frame rail and the crossmember with the hollow side towards the frame. Ensure the spacers will seat flat and align the holes in the crossmember with the holes in the spacers. Loosely fasten with 10mm bolts flat washers and lock washers.
5. Repeat drop spacer install on the driver's side. With all bolts installed go back and remove one at a time and apply Loctite to the threads. Reinstall the bolts and torque to 30 ft-lbs.
6. Check the transfer case shift level operation. The linkage may need to be adjusted in some cases.
7. Check all hardware for proper torque. Check after 500 miles.