WELD MOUNT® AT-1050 PART A

Revision Date 07/11/2023

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name Product code	:	WELD MOUNT® AT-1050 PART A 100000026068
Manufacturer or supplier's	deta	ails
Company	:	H.B. Fuller Engineering Adhesives
Address	:	9001 W Fey Drive Frankfort, IL, 60423
Telephone	:	1-815-464-5606
Medical Emergency Phone N	uml	per (24 Hours): 1-888-853-1758
Transport Emergency Phone	Nur	mber (CHEMTREC): 1-800-424-9300
Recommended use of the c	her	nical and restrictions on use
Recommended use	:	Adhesive
Restrictions on use	:	For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Physical state	liquid
Color	light brown
Odor	characteristic

GHS Classification

Flammable liquids	:	Category 2
Skin irritation	:	Category 2
Serious eye damage	:	Category 1
Skin sensitization	:	Category 1
Specific target organ toxicity -	:	Category 3 (Respiratory system)
single exposure		
Specific target organ toxicity -	:	Category 2 (Kidney)
repeated exposure		

2

GHS label elements

Hazard pictograms

Signal Word



WELD MOUNT® AT-1050 PART A

Version 1.0

Revision Date 07/11/2023

Hazard Statements:

H225 Highly flammable liquid and vapor. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation. H373 May cause damage to organs (Kidney) through prolonged or repeated exposure. **Precautionary Statements:**

Prevention: P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ eye protection/ face protection.

Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P314 Get medical advice/ attention if you feel unwell. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. **Storage:** P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep container tightly closed.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Carcinogenicity:

IARC	Group 1: Carcinogenic to humans		
	Quartz (SiO2)	14808-60-7	
OSHA	equal to 0.1% is on OSHA's lis	present at levels greater than or tof regulated carcinogens.	
NTP	Known to be human carcinogen		
	Quartz (SiO2)	14808-60-7	

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Substance / Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
methyl methacrylate	80-62-6	30 - 50
Quartz (SiO2)	14808-60-7	30 - 50
maleic acid	110-16-7	5 - 10
ethylene glycol	107-21-1	5 - 10
2,6-di-tert-butyl-p-cresol	128-37-0	5 - 10
methacrylic acid	79-41-4	1 - 5
mequinol	150-76-5	1 - 5

WELD MOUNT® AT-1050 PART A

Version 1.0	Revision Date 07/11/2023		
α,α-dimethylbenzyl hydrope Actual concentration is with			
SECTION 4. FIRST AID MEASU	RES		
General advice	: Show this material safety data sheet to the doctor in attendance.		
If inhaled	: Move to fresh air. Keep patient warm and at rest. Consult a physician after significant exposure.		
In case of skin contact	: Wash off immediately with soap and plenty of water. Call a physician if irritation develops or persists.		
In case of eye contact	: Rinse immediately with plenty of water, also under the eyelids. Seek medical advice.		
If swallowed	 If swallowed, call a poison control center or doctor immediately. Do not induce vomiting without medical advice. Drink plenty of water. 		

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Carbon dioxide (CO2) Sand Foam
Unsuitable extinguishing media	: Water
Hazardous combustion products Specific extinguishing methods	: No hazardous combustion products are known
Further information	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for fire-fighters	: Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and	: Refer to protective measures listed in sections 7 and 8. Ensure adequate ventilation.
emergency procedures Environmental precautions	: Prevent product from entering drains.
	Do not flush into surface water or sanitary sewer system.

WELD MOUNT® AT-1050 PART A

Version 1.0	Revision Date 07/11/2023
Methods and materials for containment and cleaning up	 Ventilate the area. Soak up with inert absorbent material. Use neutralizing agents. Shovel or sweep up.
SECTION 7. HANDLING AND STO	DRAGE
Local/Total ventilation	: Use only with adequate ventilation.
Advice on safe handling	: Wear personal protective equipment. Do not get on skin or clothing. Keep away from heat and flame.
Conditions for safe storage	: Keep containers tightly closed in a dry, cool and well- ventilated place. Store in original container.
Materials to avoid	: Do not store together with oxidizing and self-igniting products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methyl methacrylate	80-62-6	TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
		TWA	100 ppm 410 mg/m3	OSHA Z-1
		TWA	100 ppm 410 mg/m3	OSHA P0
		PEL	50 ppm 205 mg/m3	CAL PEL
		STEL	100 ppm 410 mg/m3	CAL PEL
Quartz (SiO2)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWÁ (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3

WELD MOUNT® AT-1050 PART A

Version 1.0

Revision Date 07/11/2023

	TWA	0.1 mg/m3	OSHA P0
	(Respirable	_	
	fraction)		
	TWA	0.05 mg/m3	OSHA Z-1
	(Respirable	Ŭ	
	dust)		
	PEL	0.05 ma/m3	CAL PEL
	(Respirable	5	
	· ·		
		0.1 mg/m3	OSHA P0
		<u>-</u>	
107-21-1	C	50 ppm	OSHA P0
	С		ACGIH
	C (Vapor)		CAL PEL
	- (-1 -)		-
	TWA (Vapor)		ACGIH
	STEL		ACGIH
	(Vapor)		
	STEL	10 mg/m3	ACGIH
	(Inhalable	- J	
	'		
128-37-0		2 mg/m3	ACGIH
	(Inhalable		
	(Inhalable fraction and		
	fraction and		
		10 mg/m3	OSHA P0
	fraction and vapor)	10 mg/m3 10 mg/m3	OSHA P0 CAL PEL
79-41-4	fraction and vapor) TWA	10 mg/m3	
79-41-4	fraction and vapor) TWA PEL	10 mg/m3 20 ppm	CAL PEL
79-41-4	fraction and vapor) TWA PEL TWA	10 mg/m3 20 ppm 20 ppm	CAL PEL ACGIH
79-41-4	fraction and vapor) TWA PEL TWA	10 mg/m3 20 ppm 20 ppm 70 mg/m3	CAL PEL ACGIH
79-41-4	fraction and vapor) TWA PEL TWA TWA	10 mg/m3 20 ppm 20 ppm 70 mg/m3 20 ppm	CAL PEL ACGIH OSHA P0
79-41-4	fraction and vapor) TWA PEL TWA TWA	10 mg/m3 20 ppm 20 ppm 70 mg/m3 20 ppm 70 mg/m3	CAL PEL ACGIH OSHA P0
	fraction and vapor)TWAPELTWATWAPELTWAPEL	10 mg/m3 20 ppm 20 ppm 70 mg/m3 20 ppm	CAL PEL ACGIH OSHA P0 CAL PEL
		(Respirable fraction)TWA (Respirable dust)PEL (Respirable dust)PEL (Respirable dust)TWA (respirable dust fraction)107-21-1CCCCCCSTEL (Vapor)STEL (Inhalable fraction, Aerosol only)128-37-0	(Respirable fraction)(Respirable dust)TWA0.05 mg/m3(Respirable dust)0.05 mg/m3PEL dust)0.05 mg/m3TWA dust)0.1 mg/m3TWA (respirable dust fraction)0.1 mg/m3107-21-1C50 ppm 125 mg/m3CVapor)40 ppm 100 mg/m3CVapor)25 ppmSTEL (Vapor)50 ppm 100 mg/m3STEL (Inhalable fraction, Aerosol only)10 mg/m3128-37-0TWA2 mg/m3

Personal protective equipme	nt	
Respiratory protection	:	Use respiratory protection unless adequate risk management measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Filter type	:	Combined particulates and organic vapor type
Hand protection Material	:	Impervious gloves

WELD MOUNT® AT-1050 PART A

Version 1.0	Revision Date 07/11/2023
Eye protection	: Tightly fitting safety goggles Ensure that eyewash stations and safety showers are close to the workstation location.
Skin and body protection	: Long sleeved clothing Preventive skin protection
Protective measures	: Avoid contact with skin.
Hygiene measures	: Avoid contact with skin, eyes and clothing.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Color Odor Odor Threshold	 liquid light brown characteristic no data available
рН	: is not determined
Melting point/freezing point	: is not determined
Boiling point/boiling range	: 101 °C
	is not determined
Flash point Evaporation rate	 10 °C Not applicable is not determined
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit	: Upper flammability limit is not determined
Lower explosion limit	: Lower flammability limit is not determined
Vapor pressure	: is not determined
Density	: 1.40 g/cm ³ (20 °C)
Solubility(ies) Water solubility	: is not determined
Partition coefficient: n- octanol/water	: no data available
Autoignition temperature	: is not determined
Viscosity Viscosity, kinematic	: is not determined

SECTION 10. STABILITY AND REACTIVITY

Chemical stability

WELD MOUNT® AT-1050 PART A

/ersion 1.0	Revision Date 07/11/2023
Hazardous decomposition products	: Nitrogen oxides (NOx) Sulfur oxides
ECTION 11. TOXICOLOGICAL	INFORMATION
	INFORMATION
cute toxicity	INFORMATION : Acute toxicity estimate : 2,935 mg/kg Method: Calculation method

Method: Calculation method

: LD50 Oral Rat: 708 mg/kg

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method

Components:

methyl methacrylate:	
Acute inhalation toxicity	: LC50 Rat: 4632 ppm
	Exposure time: 4 h
	Test atmosphere: vapor

maleic acid: Acute oral toxicity

Acute dermal toxicity		LD50 Dermal Rabbit: 1,560 mg/kg
Acute definal toxicity	•	ED50 Definal Rabbit. 1,500 mg/kg

ethylene glycol:Acute oral toxicity: LD50 Oral Rat: 4,000 mg/kg

2,6-di-tert-butyl-p-cresol:	
Acute oral toxicity	: LD50 Oral Rat: 6,000 mg/kg

methacrylic acid: Acute inhalation toxicity : LC50 Rat: 7.1 mg/l Exposure time: 4 h Test atmosphere: dust/mist

α,α -dimethylbenzyl hydroperoxide:

Acute ora	al toxici	ty		: LD50 Oral Rat: 382 mg/kg

WELD MOUNT® AT-1050 PART A

Version 1.0	Revision Date 07/11/2023
Acute inhalation toxicity	: LC50 Rat: 220 ppm Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	: LD50 Dermal Rat: 500 mg/kg
Skin corrosion/irritation	
No data available	
Serious eye damage/eye irritat	ion
No data available	
Respiratory or skin sensitizati	on
No data available	
Germ cell mutagenicity	
No data available	
Carcinogenicity	
No data available	
Reproductive toxicity	
No data available	
STOT-single exposure	
No data available	
STOT-repeated exposure	
No data available	
Aspiration toxicity	
No data available	

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

<u>Components:</u> methyl methacrylate :	
Toxicity to fish	 LC50 (Oncorhynchus mykiss (rainbow trout)): > 79 mg/l Exposure time: 96 h Test Method: flow-through test
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 69 mg/l Exposure time: 48 h Test Method: static test
maleic acid :	

SAFETY DATA SHEET

WELD MOUNT®	AT-1050 PART A
-------------	-----------------------

Version 1.0	Revision Date 07/11/2023
Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 5 mg/l Exposure time: 96 h Test Method: static test
2,6-di-tert-butyl-p-cresol:	
Toxicity to fish	 LC50 (Oryzias latipes (Japanese medaka)): 5 mg/l Exposure time: 48 h Test Method: static test
Toxicity to algae	 EC50 (Desmodesmus subspicatus (green algae)): > 0.42 mg/l Exposure time: 72 h Test Type: flow-through test
α,α-dimethylbenzyl hydrop	eroxide :
Toxicity to fish	 LC50 (Oncorhynchus mykiss (rainbow trout)): 3.9 mg/l Exposure time: 96 h Test Method: static test
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 7 mg/l Exposure time: 24 h Test Method: static test
Persistence and degradability	
No data available Bioaccumulative potential	
Mobility in soil	
No data available	
Other adverse effects	
No data available	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal r	nethods
------------	---------

Waste from residues	 Do not dispose of together with household waste. Do not dispose of waste into sewer. To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended, as industry best practice. Consult state, local or provincial authorities for more restrictive requirements.
	resultive requirements.

SECTION 14. TRANSPORT INFORMATION

International Regulations

WELD MOUNT® AT-1050 PART A

Version 1.0

Revision Date 07/11/2023

IATA-DGR

:	UN 1133
:	Adhesives
:	3
:	II
:	Flammable Liquids
:	
:	353
÷	UN 1133
	ADHESIVES
	0
÷	3
-	3
:	F-E, S-D
:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR UN/ID/NA number Proper shipping name	: UN 1133 : Adhesives
Class	: 3
Packing group	: II
Labels	: FLAMMABLE LIQUID
ERG Code	: 128
Marine pollutant	: no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards	 Flammable (gases, aerosols, liquids, or solids) Respiratory or skin sensitization Specific target organ toxicity (single or repeated exposure) Skin corrosion or irritation Serious eye damage or eye irritation
	Serious eye damage or eye irritation

WELD MOUNT® AT-1050 PART A			
Version 1.0	Revision Date 07/11/2023		
SARA 302	: This material does not contain any co EHS TPQ.	omponents with a section 302	
SARA 313	: The following components are subject by SARA Title III, Section 313:	: The following components are subject to reporting levels established by SARA Title III, Section 313:	
	methyl methacrylate ethylene glycol	80-62-6 107-21-1	
Clean Air Act			
The following chemical 61):	(s) are listed as HAP under the U.S. Clean	Air Act, Section 112 (40 CFR	
methyl meth ethylene glyd		80-62-6 107-21-1	
US State Regulations			
California Prop 65	Please contact Supplier for more	e information.	
The ingredients of the TCSI	is product are reported in the following in On the inventory, or in compliance		
TSCA	All substances listed as active on	the TSCA inventory	
AIIC	On the inventory, or in compliance	On the inventory, or in compliance with the inventory	
DSL	All components of this product are	All components of this product are on the Canadian DSL	
ENCS	On the inventory, or in compliance	e with the inventory	
ISHL	On the inventory, or in compliance	e with the inventory	
KECI	On the inventory, or in compliance	e with the inventory	
PICCS	On the inventory, or in compliance	e with the inventory	
IECSC	On the inventory, or in compliance	e with the inventory	
NZIOC	On the inventory, or in compliance	e with the inventory	
CHINV	On the inventory, or in compliance	On the inventory, or in compliance with the inventory	
REACH Inventories Legend⊺S	On the inventory, or in compliance SCA (USA), DSL (Canada), REACH(Europe		

Inventories LegendTSCA (USA), DSL (Canada), REACH(Europe), AIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)


WELD MOUNT® AT-1050 PART A

```
Version 1.0
```

Revision Date 07/11/2023

SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Office - phone: 1-651-236-5842 - email: msds.request@hbfuller.com



The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.

Further information

WELD MOUNT® AT-1050 PART B

Version 1.0

Revision Date 07/11/2023

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name Product code	: WELD MOUNT® AT-1050 PART B : 100000026069		
Manufacturer or supplier's	details		
Company	: H.B. Fuller Engineering Adhesives		
Address	: 9001 W Fey Drive Frankfort, IL, 60423		
Telephone	: 1-815-464-5606		
Medical Emergency Phone Number (24 Hours): 1-888-853-1758			
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300			
Recommended use of the chemical and restrictions on use			
Recommended use	: Activator		

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	paste
Color	light brown
Odor	characteristic

GHS Classification

Flammable liquids Skin irritation Skin sensitization Specific target organ toxicity - single exposure	:	Category 2 Category 2 Category 1 Category 3 (Respiratory system)
Specific target organ toxicity - repeated exposure	:	Category 2 (Kidney)
GHS label elements		
Hazard pictograms	:	
Signal Word	:	Danger

Hazard Statements:

WELD MOUNT® AT-1050 PART B

Version 1.0

Revision Date 07/11/2023

H225 Highly flammable liquid and vapor. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H373 May cause damage to organs (Kidney) through prolonged or repeated exposure.

Precautionary Statements:

Prevention: P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ eye protection/ face protection.

Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P314 Get medical advice/ attention if you feel unwell. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. **Storage:** P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep col. P405 Store locked up.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Carcinogenicity:	
------------------	--

IARC	Group 1: Carcinogenic to humans	
	Quartz (SiO2)	14808-60-7
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.	
NTP	Known to be human carcinogen	
	Quartz (SiO2)	14808-60-7

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

CAS-No.	Concentration [%]
80-62-6	50 - 70
14808-60-7	30 - 50
128-37-0	5 - 10
34562-31-7	5 - 10
107-21-1	5 - 10
150-76-5	1 - 5
	80-62-6 14808-60-7 128-37-0 34562-31-7

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

WELD MOUNT® AT-1050 PART B				
Version 1.0	Revision Date 07/11/2023			
General advice	: Show this material safety data sheet to the doctor in attendance.			
If inhaled	: Move to fresh air. Keep patient warm and at rest. Consult a physician after significant exposure.			
In case of skin contact	: Wash off immediately with soap and plenty of water. Call a physician if irritation develops or persists.			
In case of eye contact	: Rinse immediately with plenty of water, also under the eyelids. Seek medical advice.			
If swallowed	 If swallowed, call a poison control center or doctor immediately. Do not induce vomiting without medical advice. 			

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Carbon dioxide (CO2) Sand Foam
Unsuitable extinguishing media	: Water
Hazardous combustion products Specific extinguishing methods	: No hazardous combustion products are known
Further information	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for fire-fighters	: Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Refer to protective measures listed in sections 7 and 8. Ensure adequate ventilation.
Environmental precautions	:	Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.
Methods and materials for containment and cleaning up	:	Ventilate the area. Soak up with inert absorbent material. Do not flush with water. Shovel or sweep up.

WELD MOUNT® AT-1050 PART B

Version	1.0

Revision Date 07/11/2023

SECTION 7. HANDLING AND STORAGE

Local/Total ventilation	: Use only with adequate ventilation.
Advice on safe handling	: Wear personal protective equipment. Do not get on skin or clothing. Keep away from heat and flame.
Conditions for safe storage	: Keep containers tightly closed in a dry, cool and well- ventilated place. Store in original container.
Materials to avoid	: Do not store together with oxidizing and self-igniting products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methyl methacrylate	80-62-6	TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
		TWA	100 ppm 410 mg/m3	OSHA Z-1
		TWA	100 ppm 410 mg/m3	OSHA P0
		PEL	50 ppm 205 mg/m3	CAL PEL
		STEL	100 ppm 410 mg/m3	CAL PEL
Quartz (SiO2)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWÁ (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		PEL	0.05 mg/m3	CAL PEL

WELD MOUNT® AT-1050 PART B

Version 1.0

Revision Date 07/11/2023

		(Respirable dust)		
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
2,6-di-tert-butyl-p-cresol	128-37-0	TWA (Inhalable fraction and vapor)	2 mg/m3	ACGIH
		TWA	10 mg/m3	OSHA P0
		PEL	10 mg/m3	CAL PEL
ethylene glycol	107-21-1	С	50 ppm 125 mg/m3	OSHA P0
		С	100 mg/m3	ACGIH
		C (Vapor)	40 ppm 100 mg/m3	CAL PEL
		TWA (Vapor)	25 ppm	ACGIH
		STEL (Vapor)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH
mequinol	150-76-5	TWA	5 mg/m3	ACGIH
•		TWA	5 mg/m3	OSHA P0
		PEL	5 mg/m3	CAL PEL

Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate risk management measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Filter type	:	Combined particulates and organic vapor type
Hand protection		
Material	:	Impervious gloves
Eye protection	:	Tightly fitting safety goggles Ensure that eyewash stations and safety showers are close to the workstation location.
Skin and body protection	:	Long sleeved clothing Preventive skin protection
Protective measures	:	Avoid contact with skin.
Hygiene measures	:	Avoid contact with skin, eyes and clothing.

WELD MOUNT® AT-1050 PART B

Version 1.0

Revision Date 07/11/2023

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Color Odor Odor Threshold	 paste light brown characteristic no data available 	
рН	: is not determined	
Melting point/freezing point	: is not determined	
Boiling point/boiling range	:	
	101 °C	
Flash point Evaporation rate	: 10 °C : is not determined	_
Flammability (solid, gas)	: Not classified as a flammability hazard	l
Upper explosion limit	: Upper flammability limit is not determined	
Lower explosion limit	: Lower flammability limit is not determined	
Vapor pressure	: is not determined	
Density	: 1.4 g/cm ³ (20 °C)	
Solubility(ies) Water solubility	: is not determined	
Partition coefficient: n- octanol/water	: no data available	
Autoignition temperature	: is not determined	
Viscosity Viscosity, kinematic	: is not determined	

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	:	The product is chemically stable.
Hazardous decomposition products	:	Nitrogen oxides (NOx) Sulfur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Version 1.0	Revision Date 07/11/2023
Acute oral toxicity	: Acute toxicity estimate : 3,876 mg/kg Method: Calculation method
Components:	
methyl methacrylate: Acute inhalation toxicity	: LC50 Rat: 4632 ppm Exposure time: 4 h Test atmosphere: vapor
2,6-di-tert-butyl-p-cresol: Acute oral toxicity	: LD50 Oral Rat: 6,000 mg/kg
ethylene glycol: Acute oral toxicity	: LD50 Oral Rat: 4,000 mg/kg
Skin corrosion/irritation	
No data available	
Serious eye damage/eye irritatior	1
No data available	
Respiratory or skin sensitization	
No data available	
Germ cell mutagenicity	
No data available	
Carcinogenicity No data available	
Reproductive toxicity	
No data available	
STOT-single exposure	
No data available	
STOT-repeated exposure	
No data available	
Aspiration toxicity	
No data available	

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

WELD MOUNT® AT-1050 PART B

Version 1.0	Revision Date 07/11/2023
methyl methacrylate :	
Toxicity to fish	 LC50 (Oncorhynchus mykiss (rainbow trout)): > 79 mg/l Exposure time: 96 h Test Method: flow-through test
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 69 mg/l Exposure time: 48 h Test Method: static test
2,6-di-tert-butyl-p-cresol :	
Toxicity to fish	: LC50 (Oryzias latipes (Japanese medaka)): 5 mg/l Exposure time: 48 h Test Method: static test
Toxicity to algae	 EC50 (Desmodesmus subspicatus (green algae)): > 0.42 mg/l Exposure time: 72 h Test Type: flow-through test
Persistence and degradability	
No data available Bioaccumulative potential	
Mobility in soil	
No data available	
Other adverse effects	
No data available	

Disposal methods

Waste from residues	Do not dispose of together with household waste. Do not dispose of waste into sewer. To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at
	an approved facility is recommended, as industry best practice. Consult state, local or provincial authorities for more restrictive requirements.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR	
UN/ID No.	: UN 1133
Proper shipping name	: Adhesives

WELD MOUNT® AT-1050 PART B

Version 1.0

Revision Date 07/11/2023

Class Packing group Labels Packing instruction (cargo aircraft)	:	3 II Flammable Liquids 364
Packing instruction (passenger aircraft)	:	353
IMDG-Code		
UN number	:	UN 1133
Proper shipping name	:	ADHESIVES
Class		3
Packing group	:	5 II
	:	
Labels	•	3
EmS Code	:	F-E, S-D
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR UN/ID/NA number Proper shipping name		UN 1133 Adhesives
Class Packing group Labels ERG Code Marine pollutant	:	3 II FLAMMABLE LIQUID 128 no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.


SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards	: Flammable (gases, aerosols, liquids, or solids) Respiratory or skin sensitization Specific target organ toxicity (single or repeated exposu Skin corrosion or irritation	re)
SARA 302	: This material does not contain any components with a section EHS TPQ.	n 302

WELD MOUNT® AT-1050 PART B				
ersion 1.0	Revision Date 07/11/2023			
SARA 313	: The following components are subject by SARA Title III, Section 313:	: The following components are subject to reporting levels established by SARA Title III, Section 313:		
	methyl methacrylate ethylene glycol	80-62-6 107-21-1		
Clean Air Act				
The following chemical(s) a 61):	are listed as HAP under the U.S. Clean A	ir Act, Section 112 (40 CFR		
methyl methacry ethylene glycol	late	80-62-6 107-21-1		
US State Regulations				
California Prop 65	Please contact Supplier for more	information.		
The ingredients of this p TCSI	roduct are reported in the following inv On the inventory, or in compliance			
TSCA	All substances listed as active on the	All substances listed as active on the TSCA inventory		
AIIC	On the inventory, or in compliance	On the inventory, or in compliance with the inventory		
DSL	All components of this product are	All components of this product are on the Canadian DSL		
ISHL	On the inventory, or in compliance	On the inventory, or in compliance with the inventory		
KECI	On the inventory, or in compliance	On the inventory, or in compliance with the inventory		
PICCS	On the inventory, or in compliance	On the inventory, or in compliance with the inventory		
IECSC	On the inventory, or in compliance	with the inventory		
NZIoC	On the inventory, or in compliance	On the inventory, or in compliance with the inventory		
	On the inventory, or in compliance (USA), DSL (Canada), REACH(Europe), (ECI (Korea), PICCS (Philippines), IECS	, AIIC (Australia), NZIoC (New		

SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Office - phone: 1-651-236-5842 - email: msds.request@hbfuller.com



The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.

11/11