

SAFETY DATA SHEET

SECTION 1 / Identification

PRODUCT CODE: SCR - S, M, B

Product Use: Compound Buffing

Manufacturer/Distributor: Dico Products Corporation

Address: 200 Seward Ave

Utica, NY 13502

 Telephone No:
 315-797-9088

 Emergency Telephone No:
 315-797-9088

 Date:
 3/11/2015

SECTION 2: Hazard(s) Identifications

Buffing compounds as shipped do not present a hazard.

Buffering operations may cause lint and abrasives to become airborne. Proper ventilation and respirator recommended.

Signal Word:

Warning



SECTION 3: Composition/information on ingredients

| Substance: | CAS No. | % |
|-------------------------|-----------|----------------|
| Hydrogenated Fatty Acid | 54-11-4 | less than 21 % |
| Aluminum Oxide | 1344-28-1 | less than 79 % |
| Carbon Black | 1333-86-4 | less than 5 % |

SECTION 4: First Aid Measures

Ingestion: If swallowed - seek medical attention **Inhalation:** Move to a fresh air environment

Eye Contac Flush thoroughly with water and call physician **Skin Conta** Remove dust from skin with warm water and soap

SECTION 5: Firefighting measures

Flash Point (method used): 350° F (CoC)

LEL: N/A

Extinguishing Media: CO₂ Dry Chemical

Special Fire Fighting Instructions: Use Air Pack - Treat as Grease Fire

Unusual Fire and Explosion Hazar Dense smoke

Flammable Limits: No Data

UEL: N/A

SECTION 6: Accidental release measures

If material is spilled or released - sweep up with broom and dispose. Follow normal clean up procedures per State and Local law.- Care taken to prevent dust from becoming airborne.

SECTION 7: Handling and Storage

Do not store near direct heat sources - Store in a cool dry area No other precautions apply

SECTION 8: Exposure controls/personal protection

Hazardous Guidelines:

| Hazardous Component | OSHA PEL | ACGIH / TLV |
|-------------------------|-------------|-------------|
| Hydrogenated Fatty Acid | 15 mg ./m³ | 5 mg ./m³ |
| Aluminum Oxide | 15 mg ./m³ | 5 mg ./m³ |
| Carbon Black | 3.5 mg ./m³ | 3.5mg ./m³ |

Special: None

Mechanical (General): To maintain employee below permissible limits. **Respiratory Protection**: OSHA/MOHA approved dust mask / respirator

Gloves: Yes

Eye Protection: Safety Glasses

Other: Long sleeve protective clothing

Page 3 SDS

SECTION 9: Physical and chemical properties

Boiling Point: > 450°FSpecific Gravity: 1.9 to 2.6Vapor Pressure (mm H N/AMelting Point: 140°FVapor Density: N/AEvaporation Rate: N/ASolubility in Water: Insoluble(Butyl Acetate=1)

Appearance & Odor: Gray Bar Form

SECTION 10: Stability and Reactivity

Stability: Yes Incompatibility: N/A

Hazardous Decomposition of By-Products: N/A

Hazardous Polymerization: Will not occur

Conditions to Avoid: N/A

SECTION 11: Toxological Information

Route(s) of Entry: Inhalation: Yes Skin: No Ingestion: Yes

Health Hazards (Acute and Chron Coughing and sneezing. Buffing operations may cause lint and abrasives to become airborne. Respirator and ventilation is recommended.

Effects of overexposur N/A

Carcinogenicity: N/A NTP: N/A

IARC Monographs: No OSHA Regulated: No

SECTION 12: Ecological information (Non-Mandatory)

SECTION 13: Disposal considerations (Non-Mandatory)

SECTION 14: Transport Information (Non-Mandatory)

SECTION 15: Regulatory Information (Non-Mandatory)

SECTION 16: Other Information (Non-Mandatory)

Revision Date: 03/11/2015

Revision Summary:
Update all sections
Revised By: A.Battle