



FS88560-E

V-Line 6' Energy Absorbing Lanyard: Snap Hook

FEATURES :

- 1" polyester webbing
- 1 stamped steel snap hooks
- Single leg construction
- Ballistic shock pack with label cover
- Minimum Breaking Strength: 5,000 lbs.
- All components are ANSI Z359.12 Compliant

ATTACHMENT POINT(S) :

- 2 Snap Hook

ITEM LENGTH :

- 6' (1.8 m)

ITEM WEIGHT :

- 2.5 lbs. (2.4 kg)



USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-140.6 kg)
OSHA	N/A

STANDARD COMPLIANT WITH

ANSI	Z359.13-2013
OSHA	1926.502, 1910.140, 1910.66

SIZE(S)

N/A	

COMPONENT

MATERIAL SPECIFICATION

Webbing	Polyester/POY
Snap Hook	Stamped zinc plated steel
Shock Cover	Polyester



FS88560-E

Acollador absorbente de energía 6' V-Line: Gancho autocierre

CARACTERÍSTICAS:

- Tejido de poliéster 1"
- 2 ganchos autocierre de acero estampado
- Diseño para una sola pierna
- Cabo de vida balístico con funda con etiqueta
- Resistencia mínima a la rotura: 5,000 lb
- Todos los componentes cumplen con las pautas de ANSI Z359.12.

PUNTOS DE ENGANCHE:

- 2 ganchos autocierre

LONGITUD DEL ARTÍCULO:

- 6' (1.8 m)

PESO DEL ARTÍCULO:

- 2.5 lb (2.4 kg)



CAPACIDAD DE PESO DEL USUARIO

ANSI	De 130 a 310 lb (de 59 a 140.6 kg)
OSHA	N/C

NORMAS CUMPLIDAS

ANSI	Z359.13-2013
OSHA	1926.502, 1910.140, 1910.66

TALLES

N/C	

COMPONENTE

ESPECIFICACIÓN DEL MATERIAL

Tejido	Poliéster parcialmente orientado
Gancho autocierre	Acero cincado estampado
Cobertura	Poliéster