alpha

Safety Data Sheet

Section 1. Identification	
Product name	: ALPHA® AC-94 Flux Solder Wire Cored 40Sn/60Pb Alloy
Product code	: M040AC94
Product type	: Solid.
Date of issue/Date of revision	: September 20 2023.

Manufacturer - Supplier	Telephone no.:	Emergency phone:
Alpha Assembly Solutions Inc. Global Headquarters 140 Centennial Avenue Piscataway, NJ 08854	Toll Free: (800) 367-5460 Main Phone: (908) 791-3000	DOMESTIC NORTH AMERICA 202-464-2554
ALPHA METALS MEXICO SA DE CV Ave Nafta 800, Parque Industrial STIVA Apodaca NL 66600 Mexico	Tel: +52 81 1156-6602	Tel: 01 800 022 1400 Tel: +52 55 5559-1588
Alpha Assembly Solutions Brasil Soldas Ltda Rio Jaguarão, 1540 - Vila Buriti Manaus Amazonas 69072-055 Brasil	Tel: 55 92 3614-7400	Tel: 55 92 3614-7423

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	: Suspected of causing cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. (nervous system, reproductive organs) Very toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe dust. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

ALPHA® AC-94 Flux Solder Wire Cored 40Sn/60Pb Alloy M040AC94

Section 2. Hazards identification

Response	: Collect spillage. IF exposed or concerned: Get medical advice or attention.
Storage	: Store locked up.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Ingredient name	%	CAS number	
lead	50-60	7439-92-1	
tin	30-40	7440-31-5	
Additive	1-10	-	
Ammonium salt.	0.1-1.0	-	

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 30 minutes, keeping eyelids open. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 15 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects			
Eye contact	: No known significant effects or critical hazards.		
Inhalation	: No known significant effects or critical hazards.		
Skin contact	: No known significant effects or critical hazards.		
Ingestion	: No known significant effects or critical hazards.		

Continued on next page

Section 4. First aid measures

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that mists are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Extinguishing media : Use an extinguishing agent suitable for the surrounding fire. Suitable extinguishing media Unsuitable extinguishing : None known. media Specific hazards arising : This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged from the chemical to any waterway, sewer or drain. : Decomposition products may include the following materials: Hazardous thermal decomposition products carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides : Promptly isolate the scene by removing all persons from the vicinity of the incident if **Special protective actions** for fire-fighters there is a fire. No action shall be taken involving any personal risk or without suitable training. : Fire-fighters should wear appropriate protective equipment and self-contained breathing **Special protective** apparatus (SCBA) with a full face-piece operated in positive pressure mode. equipment for fire-fighters

Section 5. Fire-fighting measures

Section 6. Accidental release measures

Personal precautions, protec	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Methods and materials for co	ont	ainment and cleaning up
Small spill	:	Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters	
Occupational exposure li	<u>mits</u>
lead	 OSHA PEL (United States, 5/2005). TWA: 0.05 mg/m³ 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 50 μg/m³, (as Pb) 8 hours. ACGIH TLV (United States, 3/2017). Notes: as Pb TWA: 0.05 mg/m³, (as Pb) 8 hours. OSHA PEL (United States, 6/2016). Notes: as Pb TWA: 50 μg/m³, (as Pb) 8 hours. NIOSH REL (United States, 10/2016). Notes: See Appendix C - Supplemental Exposure Limits Note: The REL and PEL also apply
	to other lead compounds (as Pb).
tin	TWA: 0.05 mg/m ³ 8 hours. ACGIH TLV (United States, 3/2017). TWA: 2 mg/m ³ , (as Sn) 8 hours. NIOSH REL (United States, 10/2016). TWA: 2 mg/m ³ , (as Sn) 10 hours.
	OSHA PEL (United States, 6/2016).
	TWA: 2 mg/m ³ , (as Sn) 8 hours.
Additive	OARS WEEL (United States, 10/2011).
Additive Ammonium salt. Appropriate engineering controls Environmental exposure controls	 STEL: 20 mg/m³ 8 hours. STEL: 20 mg/m³ 15 minutes. TWA: 10 mg/m³ 8 hours. STEL: 20 mg/m³ 15 minutes. TWA: 10 mg/m³ 8 hours. ACGIH TLV (United States, 3/2017). STEL: 20 mg/m³ 15 minutes. Form: Fume TWA: 10 mg/m³ 8 hours. Form: Fume NIOSH REL (United States, 10/2016). STEL: 20 mg/m³ 15 minutes. Form: Fume TWA: 10 mg/m³ 10 hours. Form: Fume If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection meas	ures
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	

Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	olid.	
Color	ray.	
Odor	one.	
Odor threshold	ot available.	
рН	ot available.	
Melting point/freezing point	ot available.	
Boiling point, initial boiling point, and boiling range	ot available.	
Flash point	ot applicable.	
Evaporation rate	ot available.	
Flammability	ot available.	
Lower and upper explosion limit/flammability limit	ot applicable.	
Vapor pressure	ot available.	
Relative vapor density	ot applicable.	
Relative density	ot available.	
Solubility	soluble in the	following materials: cold water and hot water.
VOC	5.5 g/l	
Partition coefficient: n- octanol/water	ot applicable.	
Auto-ignition temperature	ot applicable.	
Decomposition temperature	ot available.	
Viscosity	ot applicable.	
Flow time (ISO 2431)	ot available.	
Particle characteristics		
Median particle size	ot available.	

Section 10. Stability and reactivity

Reactivity	specific test data related to reactivity available for this product o	r its ingredients.
Chemical stability	product is stable.	
Possibility of hazardous reactions	ler normal conditions of storage and use, hazardous reactions v	vill not occur.
Incompatibility with various substances	active or incompatible with the following materials: oxidizing mat erials, metals, acids, alkalis and moisture. prine, peroxides	erials, reducing
Hazardous decomposition products	ler normal conditions of storage and use, hazardous decompos be produced.	ition products should
Other Hazardous decomposition products	al oxides, toxic. fumes	
Hazardous polymerization	ler normal conditions of storage and use, hazardous polymeriza	tion will not occur.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
lead	LD50 Oral	Rat	>5000 mg/kg	-
tin	LD50 Oral	Rat	>2000 mg/kg	-
Additive	LD50 Oral	Mouse	11 g/kg	-
	LD50 Oral	Rat	8471 mg/kg	-
	LDLo Oral	Rabbit	10 g/kg	-
Ammonium salt.	LD50 Oral	Rat	1650 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Additive	Skin - Mild irritant	Human	-	72 hours 22 milligrams Intermittent	-
	Skin - Moderate irritant	Human	-	24 hours 20 Percent	-
Ammonium salt.	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Severe irritant	Rabbit	-	100 milligrams	-

Sensitization

Not available.

Mutagenicity

Product/ingredient name	Test	Experiment	Result
lead Additive	-	Subject: Mammalian-Animal Experiment: In vitro Subject: Mammalian-Human Cell: Germ	Equivocal Positive

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
lead	-	2B	Reasonably anticipated to be a human carcinogen.

Reproductive toxicity

Page: 8/13 September 20 2023.

Section 11. Toxicological information

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
lead	-	-	Equivocal	Rat - Female	Oral: 520 mg/kg	-
	-	-	Equivocal	Rat - Female	Inhalation: 3 mg/m ³	24 hours per day
	Equivocal	-	-	Mouse - Female	Oral: 300 mg/kg	-
	-	Equivocal	-	Mouse	Oral: 4099.2 mg/kg	-

Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
lead	Equivocal - Oral Equivocal - Inhalation	Mammal - species unspecified Rat	2118 mg/kg 10 mg/m³	- 24 hours per day

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name		Route of exposure	Target organs
lead	Category 1		nervous system, reproductive organs

Aspiration hazard

Not available.

Information on the likely routes of exposure	: Dermal contact. Eye contact. Inhalation. Ingestion.	
Potential acute health effects		
Eye contact	: No known significant effects or critical hazards.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: No known significant effects or critical hazards.	
Ingestion	: No known significant effects or critical hazards.	
Symptoms related to the physical sectors and the sectors are set of the sectors and the sectors are set of the sectors	sical, chemical and toxicological characteristics	
Eye contact	: No specific data.	
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations	
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations	
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations	

<u>Delayed and immediate effects and also chronic effects from short and long term exposure</u> <u>Short term exposure</u>

Continued on next page

Section 11. Toxicological information

Potential immediate effects	1	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	1	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effe	ect	<u>s</u>
Not available.		
General	:	Causes damage to organs through prolonged or repeated exposure.
Carcinogenicity	1	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	1	May damage fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

_				
Т	οχί	ici	itv	

Product/ingredient name	Result	Species	Exposure
lead	Acute EC50 105 ppb Marine water	Algae - Chaetoceros sp Exponential growth phase	72 hours
	Acute EC50 0.489 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 8000 μg/l Fresh water	Aquatic plants - Lemna minor	4 days
	Acute LC50 530 µg/l Fresh water	Crustaceans - Ceriodaphnia reticulata	48 hours
	Acute LC50 4400 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.44 ppm Fresh water	Fish - Cyprinus carpio - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 0.25 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.03 µg/l Fresh water	Fish - Cyprinus carpio	4 weeks
Additive	Acute EC50 6573.1 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute EC50 3910000 μg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 22.5 ppt Fresh water	Fish - Oreochromis mossambicus - Young	96 hours
	Chronic NOEC 2 g/L Fresh water	Fish - Heteropneustes fossilis	30 days
Ammonium salt.	Acute EC50 0.07 mg/l Marine water	Algae - Hormosira banksii - Gamete	72 hours
	Acute LC50 20 μg/l Fresh water	Crustaceans - Macrobrachium rosenbergii - Post-larvae	48 hours
	Acute LC50 390 µg/l Fresh water	Daphnia - Daphnia magna - Young	48 hours
	Acute LC50 80 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic EC10 0.03 mg/l Fresh water	Daphnia - Daphnia obtusa	21 days
	Chronic NOEC 0.6 mg/l Marine water	Algae - Entomoneis punctulata - Exponential growth phase	72 hours
	Chronic NOEC 330 µg/l Fresh water	Crustaceans - Crangonyx sp Juvenile (Fledgling, Hatchling,	21 days

ALPHA® AC-94 Flux Solder Wire Cored 40Sn/60Pb Alloy M040AC94		Sept	<i>Page: 10/13</i> ember 20 2023.
Section 12. Ecolo	gical information		
	Chronic NOEC 0.006 mg/l Fresh water	Weanling) Fish - Ictalurus punctatus - Fry	30 days

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Additive	<-1.73	-	low
Ammonium salt.	-3.2		low

Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

UN IMDG DOT TDG Mexico ΙΑΤΑ Classification Classification Classification **UN number** UN3077 UN3077 UN3077 UN3077 Not regulated. UN3077 ENVIRONMENTALLY ENVIRONMENTALLY ENVIRONMENTALLY ENVIRONMENTALLY ENVIRONMENTALLY **UN proper** shipping name HAZARDOUS HAZARDOUS HAZARDOUS HAZARDOUS HAZARDOUS SUBSTANCE, SUBSTANCE. SUBSTANCE. SUBSTANCE. SUBSTANCE, SOLID, N.O.S. SOLID, N.O.S. SOLID, N.O.S. SOLID, N.O.S. SOLID, N.O.S. (lead) (lead) (lead) (lead) (lead) 9 Transport 9 9 9 9 hazard class(es) ш Ш Ш Ш ш **Packing group** Continued on next page

Section 14. Transport information

ALPHA® AC-94 Flux Solder Wire Cored 40Sn/60Pb Alloy	Page: 11/13
M040AC94	September 20 2023.

Section 14. Transport information

Environmental	No.	Yes.	Yes.	Yes.	Yes.	Yes.	
hazards							

Additional information - TDG Classification	This product is not regulated as a dangerous good when transported in sizes of ≤ 5 L or ≤ 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
Additional information - Mexico Classification	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Additional information - UN Classification	This product is not regulated as a dangerous good when transported in sizes of ≤ 5 L or ≤ 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
Additional information - IMDG Classification	This product is not regulated as a dangerous good when transported in sizes of ≤ 5 L or ≤ 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
Additional information - IATA Classification	This product is not regulated as a dangerous good when transported in sizes of ≤ 5 L or ≤ 5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

U.S. Federal regulations	: TSCA 5(a)2 proposed significant new use rule (SNUR): No products were found.
	TSCA 5(a)2 final significant new use rules: Aliphatic alcohol.
	TSCA 12(b) one-time export notification: No products were found.
	TSCA 12(b) annual export notification: lead
United States inventory (TSCA 8b)	: All components are listed or exempted.
<u>SARA 302/304</u>	
Composition/information	on ingredients
No products were found.	
<u>SARA 311/312</u>	
Classification	: CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	lead	7439-92-1	50-60
Supplier notification	lead	7439-92-1	50-60

ALPHA® AC-94 Flux Solder Wire Cored 40Sn/60Pb Alloy M040AC94

Section 15. Regulatory information

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

California Prop. 65

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

		5
<u>Canada</u> Canada inventory	: All components are listed or exemp	oted.
International regulations		
Inventory list		
Australia	: All components are listed or exemp	oted.
China	: All components are listed or exemp	oted.
Japan	: All components are listed or exemp	oted.
New Zealand	: All components are listed or exemp	oted.
Philippines	: All components are listed or exemp	oted.
Republic of Korea	: All components are listed or exemp	oted.
Taiwan	: All components are listed or exemp	oted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	2
Flammability	1
Physical hazards	0

Procedure used to derive the classification

Classification	Justification
CARCINOGENICITY - Category 2	Calculation method
TOXIC TO REPRODUCTION - Category 1A	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1	Calculation method
AQUATIC HAZARD (ACUTE) - Category 1	Calculation method
AQUATIC HAZARD (LONG-TERM) - Category 1	Calculation method

Date of issue/Date of revision	: 9/20/2023
Date of previous issue	: 3/11/2023
Version	: 2.05
	Regulatory Affairs Department enthone.msds@macdermidenthone.com
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Section 16. Other information

References

: Not available.

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

4.12.3.4 b7396

Alpha SDS GHS Americas