

[All Categories](#) > [Ball Valves](#) > [Leaded Ball Valves](#) > [58 - Ball Full Port, Threaded](#) > Item # 58 - 014

Item # 58 - 014, Ball Valve - Brass - 58

600WOG / 150WSP**

2-pc, Full Port

CSA, UL, FM (≤ 2)

Threaded Ends

ASTM B283, C37700

Cr. Plated / Vented Ball

PTFE Seats

O-Ring Stem Seals

MSS SP-110

1/4" - 4"

** 2 1/2" - 4" - 400 WOG / 150 WSP

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.



[Specifications](#) | [Material](#) | [Dimensions](#) | [Industry Standards/Certifications](#)

Specifications

| | |
|---------------------------------|--|
| Type | Ball Valve - Brass |
| Size | 1/4 |
| Connection Type | FNPT |
| Carton Qty | 120 |
| Operating Pressure [Max] | 600 psi |
| Operating Pressure | 150 PSI - SATURATED STEAM TO 366°F 600 PSI - NON-SHOCK COLD WATER, OIL OR GAS |
| Cv Coefficient | 4.7 |
| End Type | FNPT |
| End Size | 1/4 |
| Second End Type | FNPT |
| Second End Size | 1/4 |
| Valve Operator | Lever Handle |
| Weight | 0.11 kg 0.24 lb |

Material

| | |
|--------------------------------|---|
| Body Material | Forged Brass (B283, C37700) |
| Ball Material | Forged Brass (B283, C37700) Straight or Hollow Ball |
| Seat Material | PTFE |
| Stem Material | Brass Rod (B16) |
| Valve Operator Material | Carbon Steel |

Dimensions

| | |
|---------------|---------|
| Length | 1.65 in |
|---------------|---------|

| | |
|--------|---------|
| Height | 1.46 in |
| D1 | 2.76 in |
| d | 0.39 in |

Industry Standards/Certifications

- End to end - KITZ
- End connection ANSI B1.20.1
- Wall Thickness - KITZ
- Conform to MSS-SP 110 - Replaces US. FED.
- Spec. WWW-V-35B, Type II, Class A, Style 3