

[All Categories](#) > [Ball Valves](#) > [Leaded Ball Valves](#) > [58 - Ball Full Port, Threaded](#) > Item # 58 - 038

Item # 58 - 038, Ball Valve - Brass - 58

600WOG / 150WSP**

2-pc, Full Port

CSA, UL, FM (≤ 2)

Threaded Ends

ASTM B283, C37700

Cr. Plated / Vented Ball

PTFE Seats

O-Ring Stem Seals

MSS SP-110

1/4" - 4"

** 2 1/2" - 4" - 400 WOG / 150 WSP

 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.



[Specifications](#) | [Material](#) | [Dimensions](#) | [Industry Standards/Certifications](#)

Specifications	
Type	Ball Valve - Brass
Size	3/8
Connection Type	FNPT
Carton Qty	120
Operating Pressure [Max]	600 psi
Operating Pressure	150 PSI - SATURATED STEAM TO 366°F 600 PSI - NON-SHOCK COLD WATER, OIL OR GAS
Cv Coefficient	8.5
End Type	FNPT
End Size	3/8
Second End Type	FNPT
Second End Size	3/8
Valve Operator	Lever Handle
Weight	0.11 kg 0.24 lb
Material	
Body Material	Forged Brass (B283, C37700)
Ball Material	Forged Brass (B283, C37700) Straight or Hollow Ball
Seat Material	PTFE
Stem Material	Brass Rod (B16)
Valve Operator Material	Carbon Steel
Dimensions	
Length	1.65 in

Height	1.46 in
D1	2.76 in
d	0.39 in

Industry Standards/Certifications

- End to end - KITZ
- End connection ANSI B1.20.1
- Wall Thickness - KITZ
- Conform to MSS-SP 110 - Replaces US. FED.
- Spec. WWW-V-35B, Type II, Class A, Style 3