

[All Categories](#) > [Ball Valves](#) > [Leaded Ball Valves](#) > [58 - Ball Full Port, Threaded](#) > Item # 58 - 114

## Item # 58 - 114, Ball Valve - Brass - 58

600WOG / 150WSP\*\*

2-pc, Full Port

CSA, UL, FM ( $\leq 2$ )

Threaded Ends

ASTM B283, C37700

Cr. Plated / Vented Ball

PTFE Seats

O-Ring Stem Seals

MSS SP-110

1/4" - 4"

\*\* 2 1/2" - 4" - 400 WOG / 150 WSP

**⚠ WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



[Specifications](#) | [Material](#) | [Dimensions](#) | [Industry Standards/Certifications](#)

### Specifications

<b>Type</b>	Ball Valve - Brass
<b>Size</b>	1 1/4
<b>Connection Type</b>	FNPT
<b>Carton Qty</b>	24
<b>Operating Pressure [Max]</b>	600 psi
<b>Operating Pressure</b>	150 PSI - SATURATED STEAM TO 366°F 600 PSI - NON-SHOCK COLD WATER, OIL OR GAS
<b>Cv Coefficient</b>	140
<b>End Type</b>	FNPT
<b>End Size</b>	1 1/4
<b>Second End Type</b>	FNPT
<b>Second End Size</b>	1 1/4
<b>Valve Operator</b>	Lever Handle
<b>Weight</b>	1.3 kg 2.83 lb

### Material

<b>Body Material</b>	Forged Brass (B283, C37700)
<b>Ball Material</b>	Forged Brass (B283, C37700) Straight or Hollow Ball
<b>Seat Material</b>	PTFE
<b>Stem Material</b>	Brass Rod (B16)
<b>Valve Operator Material</b>	Carbon Steel

### Dimensions

<b>Length</b>	3.31 in
---------------	---------

Height	2.16 in
D1	4.33 in
d	1.26 in

Industry Standards/Certifications

- End to end - KITZ
- End connection ANSI B1.20.1
- Wall Thickness - KITZ
- Conform to MSS-SP 110 - Replaces US. FED.
- Spec. WWW-V-35B, Type II, Class A, Style 3