

# **SAFETY DATA SHEET**

E6000 MV BLACK

### **Section 1. Identification**

Product	name
Product	code

: E6000 MV BLACK : 1000352

#### Relevant identified uses of the substance or mixture and uses advised against

<b>Identified uses</b>
------------------------

Adhesive.

Supplier's details	:	Eclectic Products LLC 990 Owen Loop North Eugene, OR 97402 541-484-9621
Responsible name	:	Regulatory Affairs
Emergency telephone number (with hours of operation)	:	INFOTRAC 1-800-535-5053 001-352-323-3500 24 hours per day, 7 days per week.

## Section 2. Hazards identification

OSHA/HCS status	<ul> <li>This material is considered hazardous by the OSHA Hazard Com (29 CFR 1910.1200).</li> </ul>	munication Standa	ard
Classification of the substance or mixture	: SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2B CARCINOGENICITY - Category 2		
GHS label elements			
Hazard pictograms			
Signal word	: Warning		
Hazard statements	: ₩315 + H320 - Causes skin and eye irritation. H351 - Suspected of causing cancer.		
Precautionary statements	<u>)</u>		
Prevention	<ul> <li>₱201 - Obtain special instructions before use.</li> <li>P202 - Do not handle until all safety precautions have been read a P280 - Wear protective gloves, protective clothing and eye or face P264 - Wash thoroughly after handling.</li> </ul>		
Response	<ul> <li>P308 + P313 - IF exposed or concerned: Get medical advice or a P362 + P364 - Take off contaminated clothing and wash it before P302 + P352 - IF ON SKIN: Wash with plenty of water.</li> <li>P332 + P313 - If skin irritation occurs: Get medical advice or atter P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for Remove contact lenses, if present and easy to do. Continue rinsin P337 + P313 - If eye irritation persists: Get medical advice or atter</li> </ul>	reuse. ntion. or several minutes. ng.	
Storage	: P405 - Store locked up.		
Date of issue/Date of revision	: 10/18/2021	ersion : 1	1/1

## Section 2. Hazards identification

Disposal

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

## Hazards not otherwise classified

### Section 3. Composition/information on ingredients

: None known.

Substance/mixture

: Mixture

Ingredient name	%	CAS number
	≥50 - ≤72 ≥10 - ≤25	127-18-4 9003-55-8

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove person to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Wush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove person to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed		
: Causes eye irritation.		
: No known significant effects or critical hazards.		
: 🖉auses skin irritation.		
: No known significant effects or critical hazards.		
Over-exposure signs/symptoms		

## Section 4. First aid measures

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

	-
Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds carbonyl halides
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

Personal precautions, protection	ve equipment and emergency procedures
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

## Section 6. Accidental release measures

Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains
	and sewers. Inform the relevant authorities if the product has caused environmental
	pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to
	the environment if released in large quantities.

#### Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

Precautions for safe handling	
Protective measures	: Fut on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

**Occupational exposure limits** 

## Section 8. Exposure controls/personal protection

Ingredient name		Exposure limits
ketrachloroethylene		ACGIH TLV (United States, 3/2020). Notes: Substance identified by other sources as a suspected or confirmed human carcinogen. Substances for which there is a Biological Exposure Index or Indices Substances for which the TLV is higher than the OSHA Permissible Exposure Limit (PEL) and/or the NIOSH Recommended Exposure Limit (REL). See CFR 58(124) : 36338-33351, June 30, 1993, for revised OSHA PEL. Refers to Appendix A Carcinogens. STEL: 685 mg/m <sup>3</sup> 15 minutes. STEL: 100 ppm 15 minutes. TWA: 170 mg/m <sup>3</sup> 8 hours. TWA: 25 ppm 8 hours. OSHA PEL Z2 (United States, 2/2013). AMP: 300 ppm 5 minutes. TWA: 100 ppm 8 hours. CEIL: 200 ppm OSHA PEL 1989 (United States, 3/1989). TWA: 25 ppm 8 hours. TWA: 25 ppm 8 hours. TWA: 170 mg/m <sup>3</sup> 8 hours.
Benzene, ethenyl-, polymer 1,3-butadiene	with	None.
Appropriate engineering controls Environmental exposure controls	loc air : En the cas	user operations generate dust, fumes, gas, vapor or mist, use process enclosures, cal exhaust ventilation or other engineering controls to keep worker exposure to borne contaminants below any recommended or statutory limits. Inissions from ventilation or work process equipment should be checked to ensure ey comply with the requirements of environmental protection legislation. In some ses, fume scrubbers, filters or engineering modifications to the process equipment I be necessary to reduce emissions to acceptable levels.
Individual protection measu Hygiene measures	: Wa	ash hands, forearms and face thoroughly after handling chemical products, before ting, smoking and using the lavatory and at the end of the working period.
	Ŵa	propriate techniques should be used to remove potentially contaminated clothing. ash contaminated clothing before reusing. Ensure that eyewash stations and safety owers are close to the workstation location.
Eye/face protection	as: ga:	fety eyewear complying with an approved standard should be used when a risk sessment indicates this is necessary to avoid exposure to liquid splashes, mists, ses or dusts. If contact is possible, the following protection should be worn, unless assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection		
Hand protection	wo ne du no glo	emical-resistant, impervious gloves complying with an approved standard should be rn at all times when handling chemical products if a risk assessment indicates this is cessary. Considering the parameters specified by the glove manufacturer, check ring use that the gloves are still retaining their protective properties. It should be ted that the time to breakthrough for any glove material may be different for different ove manufacturers. In the case of mixtures, consisting of several substances, the otection time of the gloves cannot be accurately estimated.
Body protection	ре	rsonal protective equipment for the body should be selected based on the task being rformed and the risks involved and should be approved by a specialist before ndling this product.
Other skin protection	: Ap ba	propriate footwear and any additional skin protection measures should be selected sed on the task being performed and the risks involved and should be approved by a ecialist before handling this product.
	. 40/40/	

### Section 8. Exposure controls/personal protection

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid. [Paste.]
Color	: Black.
Odor	: Not available.
Odor threshold	: Not available.
рН	: 4.3
Melting point	: Not available.
Boiling point	: 97.2 to 110°C (207 to 230°F)
Flash point	: Closed cup: >97.2°C (>207°F) [Pensky-Martens.]
Evaporation rate	: <1 (Water = 1)
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: 1.7 kPa (13 mm Hg) [room temperature]
Vapor density	: Not available.
Relative density	: 1.36 to 1.37
Partition coefficient: n- octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): 320 to 411 cm²/s (32000 to 41100 cSt)

## Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

6/13

## Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
tetrachloroethylene	LC50 Inhalation Vapor LD50 Dermal LD50 Oral	Rabbit	20 mg/l 5000 mg/kg 2629 mg/kg	4 hours - -

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
tetrachloroethylene	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Eyes - Mild irritant	Rabbit	-	162 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500	-
	Skin - Severe irritant	Rabbit	-	mg 24 hours 810 mg	-
Benzene, ethenyl-, polymer with 1,3-butadiene	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### Conclusion/Summary

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Etrachloroethylene Benzene, ethenyl-, polymer with 1,3-butadiene	-	2A 3	Reasonably anticipated to be a human carcinogen. -

#### **Reproductive toxicity**

Not available.

#### Teratogenicity

Not available.

#### Specific target organ toxicity (single exposure)

2

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

#### Information on the likely : Routes of entry anticipated: Dermal, Inhalation.

routes of exposure

#### Potential acute health effects

## Section 11. Toxicological information

Eye contact	: Causes eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: 🗭 auses skin irritation.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics					
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness				
Inhalation	: No specific data.				
Skin contact	<ul> <li>Adverse symptoms may include the following: irritation redness</li> </ul>				
Ingestion	: No specific data.				

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	

General	: No known significant effects or critical hazards.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
<b>Developmental effects</b>	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

#### Numerical measures of toxicity

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)		Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
E6000 MV BLACK	2657.6	5054.5	N/A	20.2	N/A
tetrachloroethylene	2629	5000	N/A	20	N/A

## Section 12. Ecological information

#### <u>Toxicity</u>

Product/ingredient name	Result	Species	Exposure
tetrachloroethylene	Acute EC50 200 µg/l Marine water	Algae - Skeletonema costatum	72 hours
-	Acute EC50 504 ppm Marine water	Algae - Skeletonema costatum	96 hours
	Acute LC50 3.5 mg/l Marine water	Crustaceans - Elminius modestus	48 hours
	Acute LC50 3.40071 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 4000 μg/l Fresh water	Fish - Jordanella floridae - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 0.01 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
	Chronic NOEC 0.4 mg/l Fresh water Chronic NOEC 500 µg/l Fresh water	Daphnia - Daphnia magna Fish - Pimephales promelas - Larvae	21 days 32 days

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
tetrachloroethylene	2.53	49	low

#### **Mobility in soil**

Soil/water partition	: Not available.
coefficient (Koc)	

#### Other adverse effects

: No known significant effects or critical hazards.

### Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

# Section 14. Transport information

	•				
	DOT Classification	TDG Classification	Mexico Classification	IMDG	ΙΑΤΑ
UN number	₩N1897	<mark>₩</mark> N1897	<mark>₩</mark> N1897	<mark>₩</mark> N1897	<mark>₩</mark> N1897
UN proper shipping name	Tetrachloroethylene mixture	Tetrachloroethylene mixture	Tetrachloroethylene mixture	Tetrachloroethylene mixture	Tetrachloroethylene mixture
Transport hazard class(es)	6.1	6.1	6.1	6.1	6.1
Packing group	Ш		111	111	111
Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.

Additional information		
DOT Classification	:	This product is not regulated as a marine pollutant when transported on inland waterways in sizes of ≤5 L or ≤5 kg or by road, rail, or inland air in non-bulk sizes, provided the packagings meet the general provisions of §§ 173.24 and 173.24a. Reportable quantity 139.81 lbs / 63.475 kg [12.285 gal / 46.502 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements. Limited quantity Yes. Packaging instruction Exceptions: 153. Non-bulk: 203. Bulk: 241. Quantity limitation Passenger aircraft/rail: 60 L. Cargo aircraft: 220 L.
TDG Classification	:	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.26-2.36 (Class 6), 2.7 (Marine pollutant mark). The marine pollutant mark is not required when transported by road or rail. <b>Explosive Limit and Limited Quantity Index</b> 5 <b>Passenger Carrying Vessel Index</b> 60
IMDG	1	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. <b>Emergency schedules</b> F-A, S-A
ΙΑΤΑ	:	The environmentally hazardous substance mark may appear if required by other transportation regulations. Quantity limitation Passenger and Cargo Aircraft: 30 kg. Remarks ID8000, Consumer Commodity may continue to be used according to 173.167
Special precautions for user	:	<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Transport in bulk according to IMO instruments	:	Not available.

## Section 15. Regulatory information

U.S. Federal regulations	:
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed
CADA 202/204	

<u>SARA 302/304</u>

No products were found.

SARA 304 RQ : Not a	applicable.
---------------------	-------------

SARA 311/312

Classification

: SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2B CARCINOGENICITY - Category 2

#### **Composition/information on ingredients**

Name	%	Classification
<b>te</b> trachloroethylene		ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 CARCINOGENICITY - Category 1B
Benzene, ethenyl-, polymer with 1,3-butadiene	≥10 - ≤25	EYE IRRITATION - Category 2B

#### <u>SARA 313</u>

	Product name	CAS number	%
Form R - Reporting requirements	tetrachloroethylene	127-18-4	≥50 - ≤72
Supplier notification	tetrachloroethylene	127-18-4	≥50 - ≤72

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

**State regulations** 

Massachusetts	: The following components are listed: TETRACHLOROETHYLENE
New York	: The following components are listed: Tetrachloroethylene; Ethylene, tetrachloro-
New Jersey	<ul> <li>The following components are listed: TETRACHLOROETHYLENE; ETHENE, TETRACHLORO-</li> </ul>
Pennsylvania	: The following components are listed: ETHENE, TETRACHLORO-

#### California Prop. 65

ARNING: This product can expose you to tetrachloroethylene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Tetrachloroethylene Carbon black	Yes. -	-

International regulations

Date of issue/Date of revision	: 10/18/202
--------------------------------	-------------

## Section 15. Regulatory information

Coolien for Rog	
Chemical Weapon Conv	ention List Schedules I, II & III Chemicals
Not listed.	
Montreal Protocol	
Not listed.	
Stockholm Convention	on Persistent Organic Pollutants
Not listed.	-
Rotterdam Convention	on Prior Informed Consent (PIC)
Not listed.	
UNECE Aarhus Protoco	l on POPs and Heavy Metals
Not listed.	
Inventory list	
Australia	: All components are listed or exempted.
Canada	: All components are listed or exempted.
China	: All components are listed or exempted.
Europe	: Not determined.
Japan	: Japan inventory (ENCS): Not determined. Japan inventory (ISHL): Not determined.
New Zealand	: All components are listed or exempted.
Philippines	: All components are listed or exempted.
Republic of Korea	: All components are listed or exempted.
Taiwan	: All components are listed or exempted.
Thailand	: Not determined.
Turkey	: Not determined.
United States	: MI components are active or exempted.
Viet Nam	: Not determined.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

#### National Fire Protection Association (U.S.A.)



12/13

## Section 16. Other information

#### Procedure used to derive the classification

	Classification	Justification
KIN IRRITATION - Catego EYE IRRITATION - Catego CARCINOGENICITY - Cate	ry 2B	Calculation method Calculation method Regulatory data
History		· · ·
Date of issue/Date of revision	: 10/18/2021	
Version	: 1	
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations</li> </ul>	
References	: Not available.	

**V** Indicates information that has changed from previously issued version.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.