

# SAFETY DATA SHEET



Date of issue/Date of revision 25 July 2022

Version 6

## Section 1. Identification

**Product name** : QUIKALUMINUM - 24 CT7  
**Product code** : FG600457050-24  
**Other means of identification** : Not available.  
**Product type** : Solid.

### Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Industrial applications.  
**Use of the substance/mixture** : Coating. Paints. Painting-related materials.  
**Uses advised against** : Not applicable.

**Manufacturer** : PPG Industries, Inc.  
One PPG Place  
Pittsburgh, PA 15272  
**Emergency telephone number** : (412) 434-4515 (U.S.)  
(514) 645-1320 (Canada)  
SETIQ Interior de la República: 800-00-214-00 (México)  
SETIQ Ciudad de México: (55) 5559-1588 (México)

**Technical Phone Number** : (414) 764-6000 (OAK CREEK, WI) 8:00 a.m. - 5:00 p.m. Central

## Section 2. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture** : SKIN IRRITATION - Category 2  
EYE IRRITATION - Category 2A  
SKIN SENSITIZATION - Category 1  
CARCINOGENICITY - Category 1A  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  
 Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 15.4% (oral), 79.8% (dermal), 92.7% (inhalation)

### GHS label elements

**Hazard pictograms** :



## Section 2. Hazards identification

|   |  |
|---|--|
| <b>Signal word</b>                      | : Danger   |
| <b>Hazard statements</b>                | : Causes skin irritation.<br>May cause an allergic skin reaction.<br>Causes serious eye irritation.<br>May cause respiratory irritation.<br>May cause cancer.  |
| <b><u>Precautionary statements</u></b>  |  |
| <b>Prevention</b>                       | : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Use only outdoors or in a well-ventilated area. Avoid breathing dust. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.   |
| <b>Response</b>                         | : IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. |
| <b>Storage</b>                          | : Store locked up. Store in a well-ventilated place. Keep container tightly closed.  |
| <b>Disposal</b>                         | : Dispose of contents and container in accordance with all local, regional, national and international regulations.  |
| <b>Supplemental label elements</b>      | : Sanding and grinding dusts may be harmful if inhaled. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Emits toxic fumes when heated.  |
| <b>Hazards not otherwise classified</b> | : None known.  |

## Section 3. Composition/information on ingredients

|                          |                         |
|--------------------------|-------------------------|
| <b>Substance/mixture</b> | : Mixture               |
| <b>Product name</b>      | : QUIKALUMINUM - 24 CT7 |

| Ingredient name   | %           | CAS number |
|---|-------------|------------|
| Talc, not containing asbestiform fibres   | ≥50 - ≤75   | 14807-96-6 |
| Poly[oxy(methyl-1,2-ethanediyl)], α-hydro-ω-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether | ≥10 - ≤20   | 72244-98-5 |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane   | ≥5.0 - ≤10  | 1675-54-3  |
| Epoxy resin (MW ≤ 700)  | ≥5.0 - ≤10  | 25068-38-6 |
| glass, oxide, chemicals   | ≥1.0 - ≤5.0 | 65997-17-3 |
| Aluminium powder (stabilized)   | ≥1.0 - ≤5.0 | 7429-90-5  |
| 2,4,6-tris(dimethylaminomethyl)phenol   | ≥1.0 - <3.0 | 90-72-2    |
| crystalline silica, respirable powder (<10 microns)   | <1.0        | 14808-60-7 |

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

### Section 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

#### Description of necessary first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

##### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : May cause respiratory irritation.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

##### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

## Section 4. First aid measures

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

**Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing media** : None known.

**Specific hazards arising from the chemical** : No specific fire or explosion hazard.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon oxides  
nitrogen oxides  
sulfur oxides  
halogenated compounds  
metal oxide/oxides

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

**Small spill** : Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

## Section 6. Accidental release measures

- Large spill** : Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Special precautions** : If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

| Ingredient name   | Exposure limits  |
|---|--|
| alc , not containing asbestiform fibres   | <b>ACGIH TLV (United States, 1/2021).</b><br>TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable<br><b>OSHA PEL Z3 (United States).</b><br>TWA: 2 mg/m <sup>3</sup> |
| Poly[oxy(methyl-1,2-ethanediyl)], α-hydro-ω-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether | None.  |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane   | None.  |
| Epoxy resin (MW ≤ 700)  | None.  |
| glass, oxide, chemicals   | <b>OSHA PEL (United States).</b>   |

## Section 8. Exposure controls/personal protection

aluminium powder (stabilised)

2,4,6-tris(dimethylaminomethyl)phenol  
crystalline silica, respirable powder (<10 microns)

TWA: 15 mg/m<sup>3</sup>

TWA: 5 mg/m<sup>3</sup> Form: Respirable

TWA: 15 mg/m<sup>3</sup> Form: Total dust

**ACGIH TLV (United States).**

TWA: 1 f/cc Form: Continuous filament glass fibers

TWA: 5 mg/m<sup>3</sup>, (Inhalable) Form: Continuous filament glass fibers

TWA: 3 mg/m<sup>3</sup> Form: Respirable

TWA: 10 mg/m<sup>3</sup> Form: Total dust

**ACGIH TLV (United States, 1/2021).**

**[Continuous filament glass fibers]**

TWA: 5 mg/m<sup>3</sup> 8 hours. Form: Inhalable fraction

TWA: 1 f/cc 8 hours. Form: Respirable fibers: length greater than 5 µm; aspect ratio equal to or greater than 3:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective) phase contrast illumination.

**ACGIH TLV (United States, 1/2021).**

**[Aluminum, metal and insoluble compounds]**

TWA: 1 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction

**OSHA PEL (United States, 5/2018).**

TWA: 5 mg/m<sup>3</sup>, (as Al) 8 hours. Form: Respirable fraction

TWA: 15 mg/m<sup>3</sup>, (as Al) 8 hours. Form: Total dust

None.

**ACGIH TLV (United States, 1/2021). [Silica, crystalline]**

TWA: 0.025 mg/m<sup>3</sup> 8 hours. Form: Respirable

**OSHA PEL Z3 (United States, 6/2016).**

TWA: 10 mg/m<sup>3</sup> / (%SiO<sub>2</sub>+2) 8 hours. Form: Respirable

TWA: 250 mppcf / (%SiO<sub>2</sub>+5) 8 hours. Form: Respirable

**OSHA PEL (United States, 5/2018). [Silica, crystalline]**

TWA: 50 µg/m<sup>3</sup> 8 hours. Form: Respirable dust

### Key to abbreviations

|       |  |
|-------|--|
| A     | = Acceptable Maximum Peak  |
| ACGIH | = American Conference of Governmental Industrial Hygienists.       |
| C     | = Ceiling Limit  |
| F     | = Fume   |
| IPEL  | = Internal Permissible Exposure Limit                              |
| OSHA  | = Occupational Safety and Health Administration.                   |
| R     | = Respirable   |
| Z     | = OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances |

|      |                                    |
|------|------------------------------------|
| S    | = Potential skin absorption        |
| SR   | = Respiratory sensitization        |
| SS   | = Skin sensitization               |
| STEL | = Short term Exposure limit values |
| TD   | = Total dust                       |
| TLV  | = Threshold Limit Value            |
| TWA  | = Time Weighted Average            |

## Section 8. Exposure controls/personal protection

Consult local authorities for acceptable exposure limits.

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Appropriate engineering controls** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Chemical splash goggles.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Gloves** : butyl rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. The respiratory protection shall be in accordance to 29 CFR 1910.134.

## Section 9. Physical and chemical properties

### Appearance

|  |   |
|--|---|
| Physical state                               | : Solid.  |
| Color  | : Not available.                                    |
| Odor   | : Not available.                                    |
| Odor threshold                               | : Not available.                                    |
| pH   | : Not applicable.                                   |
| Melting point                                | : Not available.                                    |
| Boiling point                                | : Not available.                                    |
| Flash point                                  | : Closed cup: Not applicable.                       |
| Auto-ignition temperature                    | : Not applicable.                                   |
| Decomposition temperature                    | : Not available.                                    |
| Flammability (solid, gas)                    | : Not available.                                    |
| Lower and upper explosive (flammable) limits | : Not applicable.                                   |
| Evaporation rate                             | : Not available.                                    |
| Vapor pressure                               | : Not available.                                    |
| Vapor density                                | : Not applicable.                                   |
| Relative density                             | : 1.93  |
| Density ( lbs / gal )                        | : 16.11   |
| Solubility                                   | : Insoluble in the following materials: cold water. |
| Partition coefficient: n-octanol/water       | : Not applicable.                                   |
| Viscosity                                    | : Kinematic (40°C (104°F)): Not applicable.         |
| Volatility                                   | : 0% (v/v), 0% (w/w)                                |
| % Solid. (w/w)                               | : 100   |

## Section 10. Stability and reactivity

|                                    |  |
|------------------------------------|--|
| Reactivity                         | : No specific test data related to reactivity available for this product or its ingredients.   |
| Chemical stability                 | : The product is stable.   |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.  |
| Conditions to avoid                | : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8. |
| Incompatible materials             | : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.           |



## Section 10. Stability and reactivity

**Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials:  
carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

| Product/ingredient name                 | Result                          | Species | Dose         | Exposure |
|---|---------------------------------|---------|--------------|----------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | LD50 Dermal                     | Rabbit  | 23000 mg/kg  | -        |
|   | LD50 Oral                       | Rat     | 15000 mg/kg  | -        |
| Epoxy resin (MW ≤ 700)                  | LD50 Dermal                     | Rabbit  | >2 g/kg      | -        |
|   | LD50 Oral                       | Rat     | >2 g/kg      | -        |
| aluminium powder (stabilised)           | LC50 Inhalation Dusts and mists | Rat     | >5 mg/l      | 4 hours  |
|   | LD50 Oral                       | Rat     | >15900 mg/kg | -        |
| 2,4,6-tris(dimethylaminomethyl)phenol   | LD50 Dermal                     | Rabbit  | 1.28 g/kg    | -        |
|   | LD50 Dermal                     | Rat     | 1280 mg/kg   | -        |
|   | LD50 Oral                       | Rat     | 1200 mg/kg   | -        |

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Irritation/Corrosion

| Product/ingredient name                 | Result                             | Species | Score | Exposure | Observation |
|---|------------------------------------|---------|-------|----------|-------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Eyes - Mild irritant               | Rabbit  | -     | 24 hours | -           |
|   | Eyes - Redness of the conjunctivae | Rabbit  | 0.4   | 24 hours | -           |
|   | Skin - Edema                       | Rabbit  | 0.5   | 4 hours  | -           |
|   | Skin - Erythema/Eschar             | Rabbit  | 0.8   | 4 hours  | -           |
| Epoxy resin (MW ≤ 700)                  | Skin - Mild irritant               | Rabbit  | -     | 4 hours  | -           |
|   | Eyes - Mild irritant               | Rabbit  | -     | -        | -           |
| 2,4,6-tris(dimethylaminomethyl)phenol   | Skin - Mild irritant               | Rabbit  | -     | -        | -           |
|   | Skin - Visible necrosis            | Rabbit  | -     | 4 hours  | 7 days      |

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

#### Sensitization

| Product/ingredient name                 | Route of exposure | Species | Result      |
|---|-------------------|---------|-------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | skin              | Mouse   | Sensitizing |
| Epoxy resin (MW ≤ 700)                  | skin              | Mouse   | Sensitizing |

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

## Section 11. Toxicological information

**Respiratory** : There are no data available on the mixture itself.

### Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Classification

| Product/ingredient name                             | OSHA | IARC | NTP                             |
|---|------|------|---------------------------------|
| Diis-[4-(2,3-epoxypropoxy)phenyl]propane            | -    | 3    | -                               |
| glass, oxide, chemicals                             | -    | 3    | -                               |
| crystalline silica, respirable powder (<10 microns) | -    | 1    | Known to be a human carcinogen. |

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

| Name                                    | Category   | Route of exposure | Target organs                |
|---|------------|-------------------|------------------------------|
| Alc , not containing asbestiform fibres | Category 3 | -                 | Respiratory tract irritation |

### Specific target organ toxicity (repeated exposure)

| Name  | Category   | Route of exposure | Target organs |
|---|------------|-------------------|---------------|
| crystalline silica, respirable powder (<10 microns) | Category 1 | inhalation        | -             |

**Target organs** : Contains material which causes damage to the following organs: eye, lens or cornea.  
Contains material which may cause damage to the following organs: lungs, the nervous system, cardiovascular system, upper respiratory tract, skin.

### Aspiration hazard

Not available.

### Information on the likely routes of exposure

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.  
**Inhalation** : May cause respiratory irritation.  
**Skin contact** : Causes skin irritation. May cause an allergic skin reaction.  
**Ingestion** : No known significant effects or critical hazards.

## Section 11. Toxicological information

### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

- Conclusion/Summary** : There are no data available on the mixture itself. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Short term exposure

- Potential immediate effects** : There are no data available on the mixture itself.
- Potential delayed effects** : There are no data available on the mixture itself.

### Long term exposure

- Potential immediate effects** : There are no data available on the mixture itself.
- Potential delayed effects** : There are no data available on the mixture itself.

### Potential chronic health effects

- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

## Section 11. Toxicological information

| Product/ingredient name                 | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|---|--------------|----------------|--------------------------|----------------------------|-------------------------------------|
| QUIKALUMINUM - 24 CT7                   | 19493.9      | 4765.9         | N/A                      | N/A                        | N/A                                 |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | 15000        | 23000          | N/A                      | N/A                        | N/A                                 |
| Epoxy resin (MW ≤ 700)                  | 2500         | 2500           | N/A                      | N/A                        | N/A                                 |
| 2,4,6-tris(dimethylaminomethyl)phenol   | 1200         | 1280           | N/A                      | N/A                        | N/A                                 |

## Section 12. Ecological information

### Toxicity

| Product/ingredient name                 | Result                                       | Species                 | Exposure            |
|---|--|-------------------------|---------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Acute LC50 1.8 mg/l Fresh water              | Daphnia - daphnia magna | 48 hours            |
| Epoxy resin (MW ≤ 700)                  | Chronic NOEC 0.3 mg/l<br>Acute LC50 1.8 mg/l | Daphnia<br>Daphnia      | 21 days<br>48 hours |
| 2,4,6-tris(dimethylaminomethyl)phenol   | Chronic NOEC 0.3 mg/l<br>Acute LC50 175 mg/l | Daphnia<br>Fish         | 21 days<br>96 hours |

### Persistence and degradability

| Product/ingredient name | Test      | Result        | Dose | Inoculum |
|-------------------------|-----------|---------------|------|----------|
| Epoxy resin (MW ≤ 700)  | OECD 301F | 5 % - 28 days | -    | -        |

  

| Product/ingredient name                 | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|------------|------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | -                 | -          | Not readily      |
| Epoxy resin (MW ≤ 700)                  | -                 | -          | Not readily      |

### Bioaccumulative potential

| Product/ingredient name               | LogP <sub>ow</sub> | BCF | Potential |
|---------------------------------------|--------------------|-----|-----------|
| Epoxy resin (MW ≤ 700)                | 3                  | 31  | low       |
| 2,4,6-tris(dimethylaminomethyl)phenol | 0.219              | -   | low       |

### Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

## 14. Transport information

|                                    | DOT             | IMDG            | IATA            |
|------------------------------------|-----------------|-----------------|-----------------|
| <b>UN number</b>                   | Not regulated.  | Not regulated.  | Not regulated.  |
| <b>UN proper shipping name</b>     | -               | -               | -               |
| <b>Transport hazard class (es)</b> | -               | -               | -               |
| <b>Packing group</b>               | -               | -               | -               |
| <b>Environmental hazards</b>       | No.             | No.             | No.             |
| <b>Marine pollutant substances</b> | Not applicable. | Not applicable. | Not applicable. |

### Additional information

**DOT** : None identified.

**IMDG** : None identified.

**IATA** : None identified.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not applicable.

## Section 15. Regulatory information

### United States

United States inventory (TSCA 8b) : All components are active or exempted.

United States - TSCA 5(a)2 - Final significant new use rules:

Mercury

Listed

### SARA 302/304

SARA 304 RQ : Not applicable.

### Composition/information on ingredients

No products were found.

### SARA 311/312

Classification : SKIN IRRITATION - Category 2  
 EYE IRRITATION - Category 2A  
 SKIN SENSITIZATION - Category 1  
 CARCINOGENICITY - Category 1A  
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

### Composition/information on ingredients

| Name  | %           | Classification  |
|---|-------------|---|
| alc , not containing asbestiform fibres   | ≥50 - ≤75   | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  |
| Poly[oxy(methyl-1,2-ethanediyl)], α-hydro-ω-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether | ≥10 - ≤20   | SKIN SENSITIZATION - Category 1B  |
| bis-[4-(2,3-epoxipropoxy)phenyl] propane  | ≥5.0 - ≤10  | SKIN IRRITATION - Category 2<br>EYE IRRITATION - Category 2A<br>SKIN SENSITIZATION - Category 1B                                    |
| Epoxy resin (MW ≤ 700)  | ≥5.0 - ≤10  | SKIN IRRITATION - Category 2<br>EYE IRRITATION - Category 2A<br>SKIN SENSITIZATION - Category 1B                                    |
| 2,4,6-tris(dimethylaminomethyl) phenol  | ≥1.0 - <3.0 | ACUTE TOXICITY (oral) - Category 4<br>ACUTE TOXICITY (dermal) - Category 4<br>SKIN CORROSION - Category 1C                          |
| crystalline silica, respirable powder (<10 microns)   | <1.0        | SERIOUS EYE DAMAGE - Category 1<br>CARCINOGENICITY - Category 1A<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 |

### SARA 313

| Supplier notification | Chemical name                   | CAS number | Concentration |
|-----------------------|---------------------------------|------------|---------------|
|                       | : Aluminium powder (stabilized) | 7429-90-5  | 1 - 5         |

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

## Section 15. Regulatory information

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

### California Prop. 65

 **WARNING:** Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)

Health : 3 \* Flammability : 0 Physical hazards : 0

(\* ) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

### National Fire Protection Association (U.S.A.)

Health : 3 Flammability : 0 Instability : 0

Date of previous issue : 6/2/2021

Organization that prepared the SDS : EHS

### Key to abbreviations

: ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
N/A = Not available  
SGG = Segregation Group  
UN = United Nations

 Indicates information that has changed from previously issued version.

### Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.