

1. Identification

Product identifier Dykem® Cross Check™ Torque Seal® - Blue

Other means of identification

Part Number 83318

Recommended use Inspection Paint

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Pro Brands

Address 805 E. Old 56 Highway
Olathe, KS 66061

Country (U.S.A.)

Tel: +1 800-443-9536

In Case of Emergency 1-800-535-5053 (Infotrac)

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Serious eye damage/eye irritation	Category 1
	Sensitization, skin	Category 1
	Carcinogenicity	Category 2
	Specific target organ toxicity, repeated exposure	Category 1 (central nervous system)
	Aspiration hazard	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing cancer. Causes damage to organs (central nervous system) through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist/vapors. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Light Mineral Spirits		64742-88-7	30 - 40
Diacetone Alcohol		123-42-2	1 - 5
Methyl Ethyl Ketoxime		96-29-7	1 - 5
Ethylbenzene		100-41-4	0.1 - 1

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. Narcosis. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapors. Do not get this material in contact with eyes. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Diacetone Alcohol (CAS 123-42-2)	PEL	240 mg/m3 50 ppm
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m3 100 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Diacetone Alcohol (CAS 123-42-2)	TWA	50 ppm
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Diacetone Alcohol (CAS 123-42-2)	TWA	240 mg/m3 50 ppm
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3 125 ppm
	TWA	435 mg/m3 100 ppm

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Methyl Ethyl Ketoxime (CAS 96-29-7)	TWA	36 mg/m ³ 10 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear appropriate chemical resistant gloves.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Liquid.

Color

Blue.

Odor

Mild.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

Not available.

Initial boiling point and boiling range

276.98 - 485.06 °F (136.1 - 251.7 °C)

Flash point

105.1 °F (40.6 °C)

Evaporation rate

Not available.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)

1.1 %

Flammability limit - upper (%)

7 %

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure	Not available.
Vapor density	> 1 (air = 1)
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC	37.62%, 364 g/L

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the decomposition temperature. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction.
Eye contact	Causes serious eye damage.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. Narcosis. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause an allergic skin reaction. Dermatitis. Rash.
--	--

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways.
----------------	---

Components	Species	Test Results
Diacetone Alcohol (CAS 123-42-2)		
Acute		
Dermal		
LD50	Rat	> 1900 mg/kg, 24 Hours
Oral		
LD50	Rat	3000 mg/kg
Ethylbenzene (CAS 100-41-4)		
Acute		
Oral		
LD50	Rat	3500 mg/kg

Components	Species	Test Results
Light Mineral Spirits (CAS 64742-88-7)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 4.5 mg/l, 4 Hours > 0.1 mg/l, 8 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Methyl Ethyl Ketoxime (CAS 96-29-7)		
Acute		
Dermal		
LD50	Rabbit	> 1000 mg/kg, 24 Hours
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 4.8 mg/l, 4 Hours
Oral		
LD50	Rat	> 900 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Causes serious eye damage.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer.	
ACGIH Carcinogens		
Ethylbenzene (CAS 100-41-4)	A3 Confirmed animal carcinogen with unknown relevance to humans.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)		
Not listed.		
US. National Toxicology Program (NTP) Report on Carcinogens		
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Causes damage to organs (central nervous system) through prolonged or repeated exposure.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Chronic effects	Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.	
12. Ecological information		
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.	

Components	Species	Test Results
Diacetone Alcohol (CAS 123-42-2)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>) 420 mg/l, 96 hours
Ethylbenzene (CAS 100-41-4)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Atlantic silverside (<i>Menidia menidia</i>) 4.4 - 5.7 mg/l, 96 hours
Methyl Ethyl Ketoxime (CAS 96-29-7)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 777 - 914 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Diacetone Alcohol	-0.098
Ethylbenzene	3.15

Mobility in soil Not established.

Other adverse effects None known.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

D001: Waste Flammable material with a flash point <140 F
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1263
UN proper shipping name	Paint
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	B1, B52, IB3, T2, TP1, TP29
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242

IATA

UN number	UN1263
UN proper shipping name	Paint
Transport hazard class(es)	
Class	3
Subsidiary risk	-

Packing group III
Environmental hazards No.
ERG Code 3L
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed with restrictions.
Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1263
UN proper shipping name PAINT
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group III
Environmental hazards
Marine pollutant No.
EmS F-E, S-E
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethylbenzene (CAS 100-41-4) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
Serious eye damage or eye irritation
Respiratory or skin sensitization
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
ETHYLBENZENE	100-41-4	0.1 - 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylbenzene (CAS 100-41-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

Diacetone Alcohol (CAS 123-42-2)

Ethylbenzene (CAS 100-41-4)

California Proposition 65



WARNING: This product can expose you to chemicals including Ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethylbenzene (CAS 100-41-4)

Listed: June 11, 2004

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Ethylbenzene (CAS 100-41-4)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 12-30-2020

Revision date 06-14-2021

Version # 04

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

Revision information Transport Information: Proper Shipping Name/Packing Group