

Revision Number: 011.0

# PRODUCT AND COMPANY IDENTIFICATION

Product name:

Medium 3 Product type/use: Adhesive Restriction of Use: None ider Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

Loctite(R) 242(R) Threadlocker Medium Strength Adhesive None identified

1.


IDH number:	230718
Item number:	24205 United States
Region: Contact information:	United States
Telephone: +1 (860) 571	-5100
	Phone: Poison Control Center
1-877-671-4608 (toll free	) or 1-303-592-1711
TRANSPORT EMERGE	NCY Phone: CHEMTREC
1-800-424-9300 (toll free	

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW		
WARNING:	CAUSES SKIN AND EYE IRRITATION.	
	MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR	
	REPEATED EXPOSURE.	

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2B
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2



**Precautionary Statements** 

Prevention:	Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Wear protective gloves.
Response:	IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if you feel unwell. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
Storage:	Not prescribed
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS			
Hazardous Component(s)	CAS Number	Percentage*	
Oleic acid 5.5EO	9004-96-0	10 - 30	
Saccharin	81-07-2	1 - 5	
Silica, amorphous, fumed, crystfree	112945-52-5	1 - 5	
Cumene hydroperoxide	80-15-9	1 - 5	
Propane-1,2-diol	57-55-6	1 - 5	
Titanium dioxide	13463-67-7	0.1 - 1	

IDH number: 230718

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FI	RST AID MEASURES
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Get medical attention.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.
5. FIRE	FIGHTING MEASURES
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.
Unusual fire or explosion hazards:	Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers.
Hazardous combustion products:	Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapours.
6. ACCIDEN	ITAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Clean-up methods:

Do not allow product to enter sewer or waterways.

Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during cleanup. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

### 7. HANDLING AND STORAGE

Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8.

For safe storage, store between -20 °C (-4°F) and 50 °C (122°F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

Handling:

Storage:

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Oleic acid 5.5EO	None	None	None	None
Saccharin	None	None	None	None
Silica, amorphous, fumed, crystfree	3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	20 MPPCF TWA 0.8 mg/m3 TWA 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
Propane-1,2-diol	None	None	10 mg/m3 TWA Aerosol.	None
Titanium dioxide	0.2 mg/m3 TWA Respirable nanoscale particles 2.5 mg/m3 TWA Respirable finescale particles	15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None

**Engineering controls:** 

**Respiratory protection:** 

Eye/face protection:

Skin protection:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Neoprene gloves. Butyl rubber gloves. Natural rubber gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Liquid Blue Physical state: Color: Mild Odor: Odor threshold: Not available. Not applicable, Product is non-polar/aprotic. pH: < 6.67 mbar (27 °C (80.6 °F)) < 5 mm hg (27 °C (80.6 °F)) < 0.13 mbar (20 °C . Vapor pressure: (68°F)) **Boiling point/range:** > 150 °C (> 302°F)None Not applicable, Product is a liquid Melting point/ range: Specific gravity: 1.1 at 23.9 °C (75.02 °F) Vapor density: > 1 20 °C > 100 °C (> 212°F) Tagliabue closed cup Flash point: Flame projection: Not applicable Flammable/Explosive limits - lower: 2.6 % (propylene glycol) Flammable/Explosive limits - upper: 12.5 % (propylene glycol) Autoignition temperature: Not determined Flammability: The product is not flammable. **Evaporation rate:** Not available. Solubility in water: Slight Solubility in water: Not available. Solubility in water: Not available. Partition coefficient (n-octanol/water): Not available IDH number: 230718 Product name: Loctite(R) 242(R) Threadlocker Medium Strength

Page 3 of 6

VOC content: Viscosity: Decomposition temperature:	0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated) Not available. Not available.
	10. STABILITY AND REACTIVITY
Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing. Polymerization may occur at elevated temperature or in the presence of incompatible materials.
Hazardous decomposition products:	Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapours.
Incompatible materials:	Strong oxidizing agents. Free radical initiators. Strong reducing agents. Alkalis. Oxygen scavengers. Other polymerization initiators. Copper. Iron. Zinc. Aluminum. Rust.
Reactivity:	Not available.
Conditions to avoid:	Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.

**11. TOXICOLOGICAL INFORMATION** 

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation:	Inhalation of vapors or mists of the product may be irritating to the respiratory system.
Skin contact:	Causes skin irritation.
Eye contact:	Causes eye irritation.
Ingestion:	May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Oleic acid 5.5EO	None	Irritant
Saccharin	Oral LD50 (Mouse) = 17 g/kg	No Target Organs
Silica, amorphous, fumed, crystfree	None	No Data
Cumene hydroperoxide	None	Allergen, Central nervous system, Corrosive, Irritant, Mutagen
Propane-1,2-diol	Oral LD50 (Rabbit) = 18 g/kg Oral LD50 (Mouse) = 23.9 g/kg Oral LD50 (Rat) = 30 g/kg	Irritant
Titanium dioxide	Inhalation LC50 (Rat, 4 h) = > $6.82$ mg/l Inhalation LC50 (Rat, 4 h) = > $2.28$ mg/l Inhalation LC50 (Rat, 4 h) = > $3.56$ mg/l	Irritant, Respiratory, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Oleic acid 5.5EO	No	No	No
Saccharin	No	No	No
Silica, amorphous, fumed, crystfree	No	No	No
Cumene hydroperoxide	No	No	No
Propane-1,2-diol	No	No	No
Titanium dioxide	No	Group 2B	No

# 12. ECOLOGICAL INFORMATION

**Ecological information:** 

Not available.

## **13. DISPOSAL CONSIDERATIONS**

#### Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

### **14. TRANSPORT INFORMATION**

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (4 Proper shipping name: Hazard class or division: Identification number: Packing group: DOT Hazardous Substance(s):	<b>49 CFR)</b> RQ, Environmentally hazardous substance, liquid, n.o.s. 9 UN 3082 III alpha,alpha-Dimethylbenzylhydroperoxide
International Air Transportation (ICAO/IATA) Proper shipping name: Hazard class or division: Identification number: Packing group:	RQ, Environmentally hazardous substance, liquid, n.o.s. 9 UN 3082 III
Water Transportation (IMO/IMDG) Proper shipping name: Hazard class or division: Identification number: Packing group:	RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. 9 UN 3082 III

## **15. REGULATORY INFORMATION**

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed as active or are exempt from listing on the Toxic Substances
TSCA 12 (b) Export Notification:	Control Act (TSCA) inventory. None above reporting de minimisNone above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health, Delayed Health This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Saccharin (CAS# 81-07-2). Cumene hydroperoxide (CAS# 80-15-9).
CERCLA Reportable quantity:	Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg)
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

### Canada Regulatory Information

CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3,8,9,11,13,15

Prepared by:	Product Safety and Regulatory Affairs
--------------	---------------------------------------

Issue date: 05/03/2023

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.