

# Product Data Sheet

No. **35062** - 05/23

## ANTI-VANDAL SPRAY

CARB VOC <50% (GRAFFITI REMOVER)

PRODUCT NUMBERS: 5062 - 13 OZ. NET. WT. AEROSOL

### I. GENERAL DESCRIPTION

**Description:** This industrial strength Anti-Vandal Spray removes the most stubborn graffiti, such as spray paint, ink, crayon, lipstick and pencil from all hard surfaces.

**Benefits:** The use of this product eliminates the need to sandblast or grind marks off concrete and brick surfaces. Leaves no residue.

**Applications:** Use on road signs, washroom walls, trucks, sidewalks, public buildings, buses, bowling equipment, railroad bridges and underpasses. This product is harmless to all hard surfaces, tile, brick, aluminum, steel, brass, glass, chrome, vinyls, enamels, porcelain, marble, ceramics, Formica and more. Test for compatibility on synthetic surfaces, susceptible to solvent damage, such as rubber, asphalt tile, rubber base paints and plastics.

**Directions:** Spray on surface and wipe with clean cloth. If soil is stubborn repeat the application. In extreme cases, use bristle brush or nylon scrubbing pad and work into foreign material. Spray on and wipe again with clean cloth.

**Limitations:** Please refer to the Safety Data Sheet for specific information on material hazards, etc.

**Packaging:**

Aerosol:	Cans (16 oz.)	13 oz. net wt. (369 grams)	15.8 fl. oz. (467 ml)
	12 cans/case	14 lbs. (6.4 kg)	0.47 CF (0.013 CM)



**AerVOE Industries, Inc.**  
P.O. Box 485, Gardnerville, NV 89410



(775) 783-3100 Phone • (775) 782-5687 Fax • (800) 227-0196 Customer Service  
[www.aerVOE.com](http://www.aerVOE.com) • [mailbox@aerVOE.com](mailto:mailbox@aerVOE.com)

---

## II. CHARACTERISTICS & PROPERTIES

---

**Specifications:**

None

**Appearance:**

Non-foaming liquid

**Color:**

Colorless, transparent

**Odor:**

Ketone

**Dry Schedule:**

Not applicable

**Performance and Chemical Properties:**

Weight per gallon .....	6.9 lbs.
Specific gravity .....	0.82
Viscosity in centipoise .....	Not applicable
Flammability: Label marking .....	Extremely Flammable
Flash point.....	<1.4°F (-17°C)
Active ingredient by weight .....	96%
CARB VOC (graffiti remover) .....	<50%
Operating temperature range .....	40° to 110° F (4° to 43° C)
Boiling point @ 760mm Hg .....	N/A
Dielectric strength .....	TBD
Surface tension .....	TBD
Food contact rating .....	N/A

**Base Materials**

Solvents (top two) .....	Methyl Ethyl Ketone, Aliphatic Hydrocarbon
Propellant system.....	Carbon Dioxide

---

## III. SHIPPING, STORAGE AND HEALTH

---

UN number .....	UN1950
Proper Shipping Description .....	Aerosols
Hazard Class .....	2.1
Packing Group .....	N/A
Limited Quantity .....	Yes
Warehouse storage level number .....	NFPA 30B Level 3
Storage temperature .....	32° to 120°F (0° to 49°C)
Shelf life .....	1 to 3 years
HMIS ratings	
Health .....	2
Fire .....	3
Reactivity .....	1

---

## IV. MISCELLANEOUS

---

Contains no Ozone Depleting Substances (O.D.S.)

---

## V. WARRANTY

---

1-year performance warranty on all products from date of purchase. Report to home office or local Aerovee representative for examination. Because Seller cannot control Buyer's handling or use of product, Seller makes no warranty expressed or implied when not used or stored in accordance with directions. Seller shall not be liable for cost of labor, incidental or consequential damages, and this warranty is limited to replacement of product or credit of purchase.