

SAFETY DATA SHEET

Goof Off Professional Strength

Page: 1 of 8

Revision: 02/18/2020

Supersedes Revision: 11/04/2019

This SDS complies with the Canadian Hazardous Products Regulations of 2015.

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Goof Off Professional Strength

Company Name: W. M. Barr
2105 Channel Avenue
Memphis, TN 38113

Phone Number: (901)775-0100

Web site address: www.wmbarr.com

Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346
Information: W.M. Barr Customer Service (800)398-3892

Product Category: General Purpose Adhesive Remover

Intended Use: Multi-Purpose Remover for rar, ink, paint, adhesive, etc.

Product Code: FG612, FG631, FG653, FG654, FG654LWS, FG655AM, FG655B, FG655BUL, FG655B36HDWS, FG657, FG661, FG690, FG6616, FG661CAN

2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 2
Acute Toxicity: Inhalation, Category 4
Carcinogenicity, Category 2
Skin Corrosion/Irritation, Category 2
Serious Eye Damage/Eye Irritation, Category 2
Specific Target Organ Toxicity (single exposure), Category 1
Specific Target Organ Toxicity (repeated exposure), Category 2



GHS Signal Word: **Danger**

GHS Hazard Phrases: Highly flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
Harmful if inhaled.
Suspected of causing cancer .
Causes damage to organs
May cause damage to - Auditory system. through prolonged or repeated exposure.

GHS Precautionary Phrases: Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/.../ equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe fumegas/mist/vapors/spray.
Wash hands thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases: IF ON SKIN: Wash with plenty of soap and water.
IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

SAFETY DATA SHEET

Goof Off Professional Strength

Revision: 02/18/2020
Supersedes Revision: 11/04/2019

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Call a POISON CENTER/Doctor/...

Get medical advice/attention.

Call a POISON CENTER or doctor/physician if you feel unwell.

Get medical attention/advice if you feel unwell.

Specific treatment see label.

If skin irritation occurs, get medical advice/attention.

If eye irritation persists, get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

In case of fire, use dry chemical powder to extinguish.

GHS Storage and Disposal Phrases:

Store in cool/well-ventilated place.

Store locked up.

Dispose of contents/container according to local, state and federal regulations.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic):

**See above.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
67-64-1	Acetone {2-Propanone}	60.0 -80.0 %
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	7.0 -13.0 %
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	1.0 -5.0 %
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	1.0 -5.0 %
110-91-8	Morpholine {Diethylene imidoxide}	0.1 -1.0 %

Additional Chemical Information

Specific percentage of composition is being withheld as a trade secret.

4. FIRST AID MEASURES

Emergency and First Aid Procedures:

Skin:
IF ON CLOTHING: Rinse immediately contaminated clothing and skin with plenty of water before removing clothes.

Eyes:
In case of contact with eyes, flush with copious amounts of water for at least 15 minutes.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Get medical attention immediately.

Ingestion: If swallowed, do not induce vomiting unless directed to do so by medical personnel. Get medical attention immediately. Never give anything by mouth to an unconscious person.

Note to Physician:

Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

	NFPA Class IB
Flash Pt:	-17.2 C (1.00 F) Method Used: Setaflash Closed Cup (Rapid Setaflash)
Explosive Limits:	LEL: N.D. UEL: N.D.
Autoignition Pt:	N.D.
Suitable Extinguishing Media:	Use water spray, dry chemical, carbon dioxide, or appropriate foam.
Unsuitable Extinguishing Media:	**None known.
Fire Fighting Instructions:	Wear self contained breathing apparatus for fire fighting if necessary.
Flammable Properties and Hazards:	Vapor may travel considerable distance to source of ignition and flash back.
Hazardous Combustion Products:	Carbon monoxide, Carbon dioxide.

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled:	Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Stay upwind. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Use non-sparking tools. Take up with sand or other non-combustible absorbent material and place into containers for later disposal. Dike far ahead of spill for later disposal. Avoid runoff into storm sewers and ditches which lead to waterways.
---	--

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:	Do not reuse this container. Read carefully and follow all instructions. Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc. Do not spread this product over large surface areas because fire and health safety risks will increase dramatically.
Precautions To Be Taken in Storing:	Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.
Other Precautions:	Keep away from heat, sparks, and open flame.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

SAFETY DATA SHEET

Goof Off Professional Strength

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
67-64-1	Acetone {2-Propanone}	ACGIH TLV	TLV: 500 ppm STEL: 750 ppm	
		OSHA PELs	PEL: 1000 ppm	
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	ACGIH TLV	TLV: 100 ppm STEL: 150 ppm	
		OSHA PELs	PEL: 100 ppm	
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	ACGIH TLV	TLV: 100 ppm STEL: 125 ppm	
		OSHA PELs	PEL: 100 ppm	
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	ACGIH TLV	TLV: 200 ppm STEL: 250 ppm	
		OSHA PELs	PEL: 200 ppm	
110-91-8	Morpholine {Diethylene imidoxide}	ACGIH TLV	TLV: 20 ppm	
		OSHA PELs	PEL: 20 ppm	
Respiratory Equipment (Specify Type):	Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).			
Eye Protection:	Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).			
Protective Gloves:	Wear appropriate gloves to prevent skin exposure.			
Other Protective Clothing:	Wear appropriate protective clothing to prevent skin exposure.			
Engineering Controls (Ventilation etc.):	Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air.			
Work/Hygienic/Maintenance Practices:	Wash thoroughly after handling.			

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States:	[] Gas [X] Liquid [] Solid
Appearance and Odor:	solvent odor. Odor threshold not determined.
pH:	N.D.
Melting Point:	N.D.
Boiling Point:	37.7 C (99.90 F)
Flash Pt:	-17.2 C (1.00 F) Method Used: Setaflash Closed Cup (Rapid Setaflash)
Evaporation Rate:	> 1
Flammability (solid, gas):	No data available.
Explosive Limits:	LEL: N.D. UEL: N.D.
Vapor Pressure (vs. Air or mm Hg):	N.D.
Vapor Density (vs. Air = 1):	N.D.

SAFETY DATA SHEET

Goof Off Professional Strength

Specific Gravity (Water = 1):	0.8200 - 0.8248
Density:	6.84 - 6.88 LB/GL
Solubility in Water:	No data.
Solubility Notes:	Partial or Limited Solubility.
Saturated Vapor Concentration:	N.D.
Octanol/Water Partition Coefficient:	N.D.
Percent Volatile:	100.0 % by weight.
VOC / Volume:	20.0000 % WT
Autoignition Pt:	N.D.
Decomposition Temperature:	N.D.
Viscosity:	< 5 cps
Additional Physical Information	VOC (g/L): 162.32 g/L max.
	ND = Not Determined.

10. STABILITY AND REACTIVITY

Stability:	Unstable [] Stable [X]
Conditions To Avoid - Instability:	No data available.
Incompatibility - Materials To Avoid:	Strong oxidizing agents.
Hazardous Decomposition or Byproducts:	Carbon monoxide, Carbon dioxide.
Possibility of Hazardous Reactions:	Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions:	**None known.

11. TOXICOLOGICAL INFORMATION

Toxicological Information: This product has not been tested as a whole. Refer to section 2 for health effects.

CAS# 67-64-1:

Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe.

Result:

Behavioral: Change in motor activity (specific assay).

Behavioral: Alteration of classical conditioning.

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS# 1330-20-7:

Acute toxicity, LC50, Inhalation, Rat, 5000. PPM, 4 H.

Result:

Behavioral: Muscle contraction or spasticity.

Lungs, Thorax, or Respiration: Other changes.

- Raw Material Data Handbook, Vol.1: Organic Solvents, 1974., National Assoc. of Printing Ink Research Institute, Francis McDonald Sinclair Memorial Labor, Lehigh Univ.,

SAFETY DATA SHEET

Goof Off Professional Strength

Bethlehem, PA 18015, Vol/p/yr: 1,123, 1974

Standard Draize Test, Eyes, Species: Rabbit, 5.000 MG, 24 H, Severe.

Result:

Behavioral: General anesthetic.

Behavioral: Somnolence (general depressed activity).

Behavioral: Irritability.

- "Sbornik Vysledku Toxikologickeho Vysetreni Latek A Pripravku," , Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho, Prumyclu Praha Czechoslovakia, Vol/p/yr: -,24, 1972

CAS# 100-41-4:

Tumorigenic Effects:, TCLo, Inhalation, Rat, 750.0 ppm.

Result:

Tumorigenic: Carcinogenic by RTECS criteria.

Kidney, Ureter, Bladder: Tumors.

Standard Draize Test, Eyes, Species: Rabbit, 500.0 MG, Severe.

Result:

Effects on Fertility: Post-implantation mortality (e.g., dead and/or resorbed implants per total number of implants).

Effects on Fertility: Litter size (e.g.; # fetuses per litter; measured before birth).

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

Carcinogenicity/Other Information:

ACGIH A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans.

ACGIH A4 - Not Classifiable as a Human Carcinogen.

IARC 2B - Possibly Carcinogenic to Humans.

IARC 3: Not Classifiable as to Carcinogenicity in Humans.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
67-64-1	Acetone {2-Propanone}	n.a.	n.a.	A4	n.a.
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	n.a.	3	A4	n.a.
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	n.a.	2B	A3	n.a.
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	n.a.	n.a.	n.a.	n.a.
110-91-8	Morpholine {Diethylene imidoxide}	n.a.	3	A4	n.a.

12. ECOLOGICAL INFORMATION

General Ecological Information:

This product has not been tested as a whole.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with applicable local, state, and federal regulations.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Paint related material.
DOT Hazard Class: 3 FLAMMABLE LIQUID
UN/NA Number: UN1263 **Packing Group:** II



LAND TRANSPORT (Canadian TDG):

TDG Shipping Name: Paint related material.
UN Number: 1263 **Packing Group:** II
Hazard Class: 3 - FLAMMABLE LIQUID **TDG Classification:**

Additional Transport Information: The shipper / supplier may be able to apply one of the following exceptions if allowed under 49 CFR Regulations: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49 CFR Hazmat Regulations. Please consult 49 CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
67-64-1	Acetone {2-Propanone}	No	Yes 5000 LB	No
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	No	Yes 100 LB	Yes
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	No	Yes 1000 LB	Yes
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	No	Yes 5000 LB	Yes
110-91-8	Morpholine {Diethylene imidoxide}	No	No	No

CAS #	Hazardous Components (Chemical Name)	Canadian NPRI	Canadian Toxic	Canadian DSL
67-64-1	Acetone {2-Propanone}	No	No	Yes
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	Yes: Part 5		Yes
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	Yes: Part 1A	No	Yes
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	Yes: Part 5		Yes
110-91-8	Morpholine {Diethylene imidoxide}	No	No	Yes

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
67-64-1	Acetone {2-Propanone}	TSCA: Inventory
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	CAA HAP,ODC: HAP: VHAP CWA NPDES TSCA: Inventory
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	CAA HAP,ODC: HAP: VHAP CWA NPDES TSCA: Inventory
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	CA PROP.65: Yes: Canc. CAA HAP,ODC: HAP: VHAP TSCA: Inventory CA PROP.65: Yes: RDTox.

SAFETY DATA SHEET

Goof Off Professional Strength

Revision: 02/18/2020
Supersedes Revision: 11/04/2019

110-91-8 Morpholine {Diethylene imidoxide}

TSCA: Inventory

Additional Regulatory Information

This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

16. OTHER INFORMATION

Revision Date: 02/18/2020**Preparer Name:** W.M. Barr EHS Dept (901)775-0100**Additional Information About This Product:** No data available.**Company Policy or Disclaimer:**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.