Version 6.1

Revision Date 10/01/2023

Print Date 10/02/2023

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	ZEP BRAKE WASH (LOCK & KEY)	
Material number	:	00000000000689385	
Manufacturer or supplier's details			
Company	:	Zep Inc.	
Address	:	350 Joe Frank Harris Parkway, SE Emerson, GA 30137	
Telephone	:	Compliance Services - 877-428-9937	

Emergency telephone numbers		
For SDS Information	:	Compliance Services - 877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation Emergency	:	CHEMTREC: 800-424-9300 - All Calls Recorded. In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	clear
Odour	alcohol-like

GHS Classification

Flammable liquids Skin irritation Specific target organ toxicity - single exposure Aspiration hazard	 Category 2 Category 2 Category 3 (Central nervous system) Category 1
GHS label elements	
Hazard pictograms	: Flame Health hazard Exclamation mark
Signal word	: Danger
Hazard statements	 H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness.
Precautionary statements	: Prevention:

Version 6.1	Revision Date 10/01/2023	Print Date 10/02/2023
Version 6.1	Revision Date 10/01/2023P210 Keep away from heat, hot a and other ignition sources. No sr P233 Keep container tightly close P240 Ground/bond container and P241 Use explosion-proof electri equipment.P242 Use only non-sparking tool P243 Take precautionary measu P261 Avoid breathing dust/ fume P264 Wash skin thoroughly after P271 Use only outdoors or in a v P280 Wear protective gloves/ ey Response: P301 + P310 IF SWALLOWED: CENTER/doctor.P303 + P361 + P353 IF ON SKIN immediately all contaminated clo P304 + P340 + P312 IF INHALEI and keep comfortable for breathin CENTER/doctor if you feel unwel P331 Do NOT induce vomiting. P332 + P313 If skin irritation occ attention.P362 Take off contaminated clot P370 + P378 In case of fire: Use alcohol-resistant foam to extingui Storage: P403 + P233 Store in a well-vent tightly closed. P235 Keep cool.Disposal:	surfaces, sparks, open flames noking. ed. d receiving equipment. cal/ ventilating/ lighting s. res against static discharge. / gas/ mist/ vapours/ spray. handling. vell-ventilated area. e protection/ face protection. Immediately call a POISON N (or hair): Take off thing. Rinse skin with water. D: Remove person to fresh air ng. Call a POISON I. urs: Get medical advice/ hing and wash before reuse. dry sand, dry chemical or ish.
	P501 Dispose of contents/contain regulation.	ner in accordance with local

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Concentration [%]
64742-49-0	>= 90 - < 100
67-63-0	>= 3 - < 5
142-82-5	>= 3 - < 5
	64742-49-0 67-63-0

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice

: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

sion 6.1	Revision Date 10/01/2023	Print Date 10/02/202
	Do not leave the victim unattend	ed.
lf inhaled	 Consult a physician after signific If unconscious, place in recovery advice. Move to fresh air. Oxygen or artificial respiration if 	position and seek medical
In case of skin contact	 Wash off with soap and water. Take off all contaminated clothin Wash off immediately with plenty minutes. Wash contaminated clothing before If symptoms persist, call a physic 	y of water for at least 15 ore re-use.
In case of eye contact	: Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsin If eye irritation persists, consult a If in eyes, rinse with water for 15	a specialist.
If swallowed	: Keep respiratory tract clear. Never give anything by mouth to If symptoms persist, call a physic DO NOT induce vomiting unless physician or poison control center Take victim immediately to hosp	cian. directed to do so by a er.
Most important symptoms and effects, both acute and delayed	: Effects are immediate and delay Symptoms of overexposure may dizziness; and confusion. May p paralysis, and convulsions.	include disorientation;
	Symptoms may include irritation, Aspiration may cause pulmonary Effects are dependent on expose contact time). May be fatal if swallowed and en Causes skin irritation. May cause drowsiness or dizzing Review section 2 of SDS to see	v oedema and pneumonitis. ure (dose, concentration, nters airways. ess.
Notes to physician	: Treat symptomatically. Symptor	ms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.

Version 6.1	Revision Date 10/01/2023	Print Date 10/02/2023
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke	
Specific extinguishing methods	: Use extinguishing measures that are circumstances and the surrounding	
Further information	: Collect contaminated fire extinguishi must not be discharged into drains. Fire residues and contaminated fire be disposed of in accordance with lo For safety reasons in case of fire, ca separately in closed containments. Use a water spray to cool fully close	extinguishing water must ocal regulations. ans should be stored
Special protective equipment for firefighters	: Wear self-contained breathing apparent necessary.	atus for firefighting if

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Do not breathe vapours or spray mist. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	: No smoking. Keep container tightly closed in a dry and well-ventilated place.

Version 6.1	Revision Date 10/01/2023	Print Date 10/02/2023
	Containers which are opened must kept upright to prevent leakage. Observe label precautions. Electrical installations / working ma the technological safety standards.	aterials must comply with
Materials to avoid	: Strong oxidizing agents	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of	Control parameters /	Basis
		exposure)	Permissible concentration	
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0
		PEL	400 ppm 980 mg/m3	CAL PEL
		STEL	500 ppm 1,225 mg/m3	CAL PEL
heptane	142-82-5	TWA	85 ppm 350 mg/m3	NIOSH REL
		С	440 ppm 1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		STEL	500 ppm 2,000 mg/m3	OSHA P0
		PEL	400 ppm 1,600 mg/m3	CAL PEL
		STEL	500 ppm 2,000 mg/m3	CAL PEL
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH

Components with workplace control parameters

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at	40 mg/l	ACGIH BEI

ersion 6.1	Revision Date 10/01/2023	Print Date 10/02/2023
		end of workwee k
Engineering measures	: Effective exhaust ventilation sys	
Personal protective equ	ipment	
Respiratory protection	: Use respiratory protection unles ventilation is provided or exposithat exposures are within recom	ure assessment demonstrates
Hand protection Material Remarks	Protective glovesThe suitability for a specific wor with the producers of the protect	
Eye protection	: Safety glasses Ensure that eyewash stations a the workstation location.	and safety showers are close to
Skin and body protection	: Impervious clothing Choose body protection accord concentration of the dangerous	
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	clear
Odour	:	alcohol-like
Odour Threshold	:	No data available
рН	:	Not applicable
Melting point/freezing point	:	Not applicable
Boiling point	:	63 - 98.9 °C
Flash point	:	-3.89 °C Method: TCC
Evaporation rate	:	< 1
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available

/ersion 6.1	Revision Date 10/01/2023	Print Date 10/02/2023
Density	: 0.675 g/cm3	
Solubility(ies)		
Water solubility	: No data available	
Solubility in other solvents	: not determined	
Partition coefficient: n- octanol/water	: No data available	
Auto-ignition temperature	: not determined	
Thermal decomposition	: No data available	
Viscosity		
Viscosity, kinematic	: No data available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	:	None known.
Symptoms of Overexposure	:	Effects are immediate and delayed. Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness, paralysis, and convulsions.
		Symptoms may include irritation, redness, pain, and rash. Aspiration may cause pulmonary oedema and pneumonitis. Effects are dependent on exposure (dose, concentration, contact time). May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Review section 2 of SDS to see all potential hazards.

Version 6.1	Revision Date 10/01/2023	Print Date 10/02/2023
	Treat symptomatically. Symptom	ns may be delayed.
Carcinogenicity:		
IARC	No component of this product prese equal to 0.1% is identified as probab	
ACGIH	human carcinogen by IARC. No component of this product prese equal to 0.1% is identified as a carc carcinogen by ACGIH.	
OSHA	No component of this product prese	
NTP	equal to 0.1% is on OSHA's list of re No component of this product prese equal to 0.1% is identified as a know by NTP.	nt at levels greater than or
Acute toxicity		
Product:		
Acute oral toxicity	: Acute toxicity estimate : > 5,000 Method: Calculation method	mg/kg
Components:		
propan-2-ol: Acute oral toxicity	: LD50 Oral Rat: 4,396 mg/kg Method: Calculation method	
heptane: Acute inhalation toxicity	: LC50 Rat: 103 mg/l Exposure time: 4 h	
Skin corrosion/irritation		
Product:		
Remarks: Irritating to skin.		
Serious eye damage/eye irritatio	n	
Product:		
Remarks: Irritating to eyes.		
Respiratory or skin sensitisation		
No data available		
Germ cell mutagenicity		
No data available		
Carcinogenicity		
No data available		
Reproductive toxicity		
No data available		

Version 6.1

Revision Date 10/01/2023

Print Date 10/02/2023

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available Bioaccumulative potential

Product:

Partition coefficient: n- : octanol/water <u>Components:</u> propan-2-ol :	Remarks: No data available
	log Pow: 0.05
•	log Pow: 5
Mobility in soil	
No data available	
Other adverse effects	
No data available Product:	
Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

Version 6.1	Revision Date 10/01/2023	Print Date 10/02/2023
	+ B).	
Additional ecological information	: An environmental hazard cannot event of unprofessional handlin aquatic life with long lasting effo	g or disposal., Toxic to

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): UN1993, Flammable liquids, n.o.s., (HEPTANE, ISOPROPANOL), 3, II

Transportation Regulation: IMDG (Vessel): UN1993, FLAMMABLE LIQUID, N.O.S., (HEPTANE, ISOPROPANOL), 3, II

Transportation Regulation: IATA (Cargo Air): UN1993, Flammable liquid, n.o.s., (HEPTANE, ISOPROPANOL), 3, II

Transportation Regulation: IATA (Passenger Air): UN1993, Flammable liquid, n.o.s., (HEPTANE, ISOPROPANOL), 3, II

Transportation Regulation: TDG (Canada): UN1993, FLAMMABLE LIQUID, N.O.S., (HEPTANE, ISOPROPANOL), 3, II

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list

: No substances are subject to a Significant New Use Rule.

Version 6.1

Revision Date 10/01/2023

Print Date 10/02/2023

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
benzene	71-43-2	10	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	: Flammable (gases, aerosols, liquids, or solids) Skin corrosion or irritation Specific target organ toxicity (single or repeated exposure) Aspiration hazard
SARA 302	: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 313	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop. 65	
Ŵ	WARNING: This product can expose you to chemicals including benzene, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to

www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL	All components of this product are on the Canadian DSL
TSCA	On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Version 6.1

Revision Date 10/01/2023

Print Date 10/02/2023

Further information

NFPA:



0 = not significant, 1 = Slight,

2 = Moderate, 3 = High


4 = Extreme

HMIS III:

HEALTH	3
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,

- 2 = Moderate, 3 = High
- 4 = Extreme, * = Chronic



Version 6.1

Revision Date 10/01/2023

occurs: Get medical advice/ attention. Take off contaminated clothing and w ash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foamto extinguish.

Storage : Store in a w ell-ventilated place. Keep container tightly closed. Keep cool. **Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	6.1
Revision Date:	10/01/2023
Print Date:	10/02/2023

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.