



K&W Tech Grade Knock'er Loose Lubricant Penetrant

ATTRIBUTES –

Item Number

1006081

Legacy Number

401724

Product Description

A super-fast penetrant that attacks corrosion to free rusted & corroded fasteners & components. Powerful, concentrated formula penetrates & leaves behind a long-lasting lubricant that will prevent future corrosion.

Applications

Rusted and frozen metals, such as bolts, hinges, nuts, hinges, exhaust clamps.

Unit Package Description

24 Ounce Aerosol

Brand

K&W

Net Fill

18 Wt Oz

UPC Code

78372017247

Unit Dimensions

9.19H x 3W x 3D in

Units Per Case

12

Case Dimensions

9.75H x 9.25W x 12.25D in

Cases per pallet USA

80

Appearance

Light Amber Liquid

Base Type

Petroleum Distillate

Flash point (F)

141°F

Flash point (C)

60.6°C

Flammability Class - CPSC

Flammable

Spec Gravity Concentrate

0.82

KB Value

28

Plastic Safe

Safe on Most Plastics (test small area)

Film Type

Thin, Non-Drying

Evaporation Rate

Slow

Dielectric Strength

60,000 Volts

Timken Ok Load (lbs)

N/A

Propellant

Carbon Dioxide

Aerosol Flammability Level

III

DOT Proper Shipping Name

Aerosols, Flammable, Limited Quantity

4 Ball EP

Not Determined

4 Ball Wear

Not Determined

Drop Point

N/A

pH

N/A

SAE Grade

N/A

Water Washout

N/A

Working Temp (F)

Max 300°F

Working Temp (C)

Max 148.9°C

VOC % (Consumer Product def)

24.1

VOC g/L (Consumer Product def)

197.6

VOC lbs/gal (Consumer Prod def)

1.65

VOC Category

Penetrant

Removal (How To)

Remove with mineral spirits or degreasers etc.