

# Safety Data Sheet



Revision Number: 010.0

Issue date: 02/22/2024

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product name:** LOCTITE LB 8008 C5-A known as  
LOCTITE C5-A CO A/S 1LB EN

**Product type/use:** Antiseize

**Restriction of Use:** None identified

**Company address:**  
Henkel Corporation  
One Henkel Way  
Rocky Hill, Connecticut 06067

**IDH number:** 160796

**Item number:** 51007

**Region:** United States

**Contact information:**  
Telephone: +1 (860) 571-5100  
MEDICAL EMERGENCY Phone: Poison Control Center  
1-877-671-4608 (toll free) or 1-303-592-1711  
TRANSPORT EMERGENCY Phone: CHEMTREC  
1-800-424-9300 (toll free) or 1-703-527-3887  
Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**DANGER:** CAUSES SKIN IRRITATION.  
CAUSES SERIOUS EYE DAMAGE.  
CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

| HAZARD CLASS                                       | HAZARD CATEGORY |
|--|-----------------|
| SKIN IRRITATION                                    | 2               |
| SERIOUS EYE DAMAGE                                 | 1               |
| SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE | 1               |

### PICTOGRAM(S)



### Precautionary Statements

**Prevention:** Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves, eye protection, and face protection.

**Response:** IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if you feel unwell. If skin irritation occurs: Get medical attention. Take off contaminated clothing.

**Storage:** Not prescribed

**Disposal:** Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s)                                 | CAS Number | Percentage* |
|--|------------|-------------|
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 | 10 - 30     |
| Calcium dihydroxide                                    | 1305-62-0  | 10 - 30     |

IDH number: 160796

Product name: LOCTITE LB 8008 C5-A known as LOCTITE C5-A CO A/S 1LB EN  
Page 1 of 6

|  |            |         |
|--|------------|---------|
| Copper   | 7440-50-8  | 10 - 30 |
| Graphite   | 7782-42-5  | 5 - 10  |
| Quartz (SiO <sub>2</sub> ) "respirable particulates (reaches the alveoli)" (RCS) <0.1% | 14808-60-7 | 1 - 5   |
| Quartz (SiO <sub>2</sub> ) respirable particulates (RCS) >=10%                         | 14808-60-7 | 0.1 - 1 |

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

|                      |   |
|----------------------|---|
| <b>Inhalation:</b>   | Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention. |
| <b>Skin contact:</b> | Wash with soap and water. If symptoms develop and persist, get medical attention.   |
| <b>Eye contact:</b>  | Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.   |
| <b>Ingestion:</b>    | Do not induce vomiting. Get medical attention.  |
| <b>Symptoms:</b>     | See Section 11.   |

#### 5. FIRE FIGHTING MEASURES

|   |  |
|---|--|
| <b>Extinguishing media:</b>               | Water spray (fog), foam, dry chemical or carbon dioxide. |
| <b>Special firefighting procedures:</b>   | None   |
| <b>Unusual fire or explosion hazards:</b> | None   |
| <b>Hazardous combustion products:</b>     | Oxides of carbon.  |

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

|                                   |  |
|-----------------------------------|--|
| <b>Environmental precautions:</b> | Do not allow material to contaminate ground water system.                  |
| <b>Clean-up methods:</b>          | Scrape up as much material as possible. Clean residue with soap and water. |

#### 7. HANDLING AND STORAGE

|                  |  |
|------------------|--|
| <b>Handling:</b> | Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Keep container closed. Wash thoroughly after handling. |
| <b>Storage:</b>  | Keep in a cool, well ventilated area.  |

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)   | ACGIH TLV   | OSHA PEL   | AIHA WEEL | OTHER |
|--|---|--|-----------|-------|
| Distillates (petroleum), hydrotreated heavy naphthenic                                 | 5 mg/m3 TWA<br>Inhalable fraction.                                | 5 mg/m3 PEL Mist.<br>500 ppm (2,000 mg/m3) PEL   | None      | None  |
| Calcium dihydroxide  | 5 mg/m3 TWA   | 5 mg/m3 PEL<br>Respirable fraction.<br>15 mg/m3 PEL Total dust.<br>50 MPPCF TWA Total dust.<br>5 mg/m3 TWA Respirable fraction.<br>15 MPPCF TWA Respirable fraction.<br>15 mg/m3 TWA Total dust. | None      | None  |
| Copper   | 0.2 mg/m3 TWA (as Cu) Fume.<br>1 mg/m3 TWA (as Cu) Dust and mist. | 1 mg/m3 PEL (as Cu) Dust and mist.<br>0.1 mg/m3 PEL (as Cu) Fume.  | None      | None  |
| Graphite   | 2 mg/m3 TWA<br>Respirable fraction.                               | 5 mg/m3 PEL<br>Respirable fraction.<br>15 mg/m3 PEL Total dust.<br>5 mg/m3 PEL<br>Respirable fraction.<br>15 mg/m3 PEL Total dust.   | None      | None  |
| Quartz (SiO <sub>2</sub> ) "respirable particulates (reaches the alveoli)" (RCS) <0.1% | 0.025 mg/m3 TWA<br>Respirable fraction.                           | 0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.)<br>0.025 mg/m3 OSHA_ACT (Respirable dust.)<br>0.05 mg/m3 PEL Respirable dust.<br>2.4 MPPCF TWA Respirable.<br>0.1 mg/m3 TWA Respirable.     | None      | None  |
| Quartz (SiO <sub>2</sub> ) respirable particulates (RCS) >=10%                         | 0.025 mg/m3 TWA<br>Respirable fraction.                           | 0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.)<br>0.025 mg/m3 OSHA_ACT (Respirable dust.)<br>0.05 mg/m3 PEL Respirable dust.<br>2.4 MPPCF TWA Respirable.<br>0.1 mg/m3 TWA Respirable.     | None      | None  |

**Engineering controls:**

Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

**Respiratory protection:**

Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Observe OSHA regulations for respirator use (29 CFR 1910.134).

**Eye/face protection:**

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

**Skin protection:**

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|   |  |
|---|--|
| <b>Physical state:</b>                          | Paste  |
| <b>Color:</b>                                   | Copper   |
| <b>Odor:</b>                                    | Mild   |
| <b>Odor threshold:</b>                          | Not available.                                     |
| <b>pH:</b>                                      | Not applicable, Product is non-soluble (in water). |
| <b>Vapor pressure:</b>                          | < 1 hPa (20 °C (68°F))                             |
| <b>Boiling point/range:</b>                     | > 100 °C (> 212°F)                                 |
| <b>Melting point/ range:</b>                    | Not applicable, Product is a liquid                |
| <b>Specific gravity:</b>                        | 1.30   |
| <b>Vapor density:</b>                           | > 1 20 °C Heavier than air.                        |
| <b>Flash point:</b>                             | > 93 °C (> 199.4 °F)                               |
| <b>Flammable/Explosive limits - lower:</b>      | Not available.                                     |
| <b>Flammable/Explosive limits - upper:</b>      | Not available.                                     |
| <b>Autoignition temperature:</b>                | Not determined                                     |
| <b>Flammability:</b>                            | The product is not flammable.                      |
| <b>Evaporation rate:</b>                        | Slower than ether.                                 |
| <b>Solubility in water:</b>                     | Not miscible or difficult to mix                   |
| <b>Partition coefficient (n-octanol/water):</b> | Not available.                                     |
| <b>VOC content:</b>                             | < 3 % Estimated                                    |
| <b>Viscosity:</b>                               | Not available.                                     |
| <b>Decomposition temperature:</b>               | Not available.                                     |

## 10. STABILITY AND REACTIVITY

|  |  |
|--|--|
| <b>Stability:</b>                        | Stable at normal conditions.                     |
| <b>Hazardous reactions:</b>              | Will not occur.                                  |
| <b>Hazardous decomposition products:</b> | Hydrocarbons. Oxides of carbon.                  |
| <b>Incompatible materials:</b>           | Strong acids and strong bases. Oxidizing agents. |
| <b>Reactivity:</b>                       | Not available.                                   |
| <b>Conditions to avoid:</b>              | Prolonged exposure to heat.                      |

## 11. TOXICOLOGICAL INFORMATION

|                                     |                                   |
|-------------------------------------|-----------------------------------|
| <b>Relevant routes of exposure:</b> | Skin, Inhalation, Eyes, Ingestion |
|-------------------------------------|-----------------------------------|

### Potential Health Effects/Symptoms

**Inhalation:** Inhalation of copper fumes may result in metal fume fever. Symptoms include metallic taste, discoloration of skin or hair. May cause respiratory tract irritation. Contains crystalline silica (quartz), which is classified as a possible carcinogen. However, the crystalline silica present in this product is encapsulated in the liquid and will only be liberated if the product is sanded or abraded, and even then what is liberated will not be pure crystalline silica. Appropriate precautions, however, should be taken if the product is sanded or abraded to prevent personnel from breathing the dust.

**Skin contact:** Causes skin irritation.

**Eye contact:** Causes serious eye damage.

**Ingestion:** May cause gastrointestinal tract irritation if swallowed.

| Hazardous Component(s)  | LD50s and LC50s   | Immediate and Delayed Health Effects   |
|---|---|--|
| Distillates (petroleum), hydrotreated heavy naphthenic                    | Inhalation LC50 (Rat, 4 h) = > 4.026 mg/l<br>Inhalation LC50 (Rat, 4 h) = 2.18 mg/l<br>Inhalation LC50 (Rat, 4 h) = 10.5 mg/l<br>Inhalation LC50 (Rat, 4 h) = > 5.2 mg/l<br>Inhalation LC50 (Rat, 4 h) = < 5.7 mg/l | Irritant   |
| Calcium dihydroxide   | Oral LD50 (Rat) = 7,340 mg/kg   | Irritant, Corrosive  |
| Copper  | Inhalation LC50 (Rat, 4 h) = > 5.11 mg/l  | Allergen, Blood, Central nervous system, Developmental, Gastrointestinal, Immune system, Irritant, Kidney, Liver, Mutagen, Sensory, Skin |
| Graphite  | Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m3  | Lung   |
| Quartz (SiO2) "respirable particulates (reaches the alveoli)" (RCS) <0.1% | None  | No Data  |
| Quartz (SiO2) respirable particulates (RCS) >=10%                         | None  | No Data  |

| Hazardous Component(s)  | NTP Carcinogen                | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|---|-------------------------------|-----------------|--|
| Distillates (petroleum), hydrotreated heavy naphthenic                    | No                            | No              | No                                       |
| Calcium dihydroxide   | No                            | No              | No                                       |
| Copper  | No                            | No              | No                                       |
| Graphite  | No                            | No              | No                                       |
| Quartz (SiO2) "respirable particulates (reaches the alveoli)" (RCS) <0.1% | Known To Be Human Carcinogen. | Group 1         | Yes                                      |
| Quartz (SiO2) respirable particulates (RCS) >=10%                         | Known To Be Human Carcinogen. | Group 1         | Yes                                      |

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Environmentally hazardous substance, liquid, n.o.s. (Copper)  
**Hazard class or division:** 9  
**Identification number:** UN 3082  
**Packing group:** III  
**Marine pollutant:** Copper  
**DOT Hazardous Substance(s):** Copper

**International Air Transportation (ICAO/IATA)**

**Proper shipping name:** Environmentally hazardous substance, liquid, n.o.s. (Copper)  
**Hazard class or division:** 9  
**Identification number:** UN 3082  
**Packing group:** III

**Water Transportation (IMO/IMDG)**

**Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Copper)  
**Hazard class or division:** 9  
**Identification number:** UN 3082  
**Packing group:** III  
**Marine pollutant:** Copper

**15. REGULATORY INFORMATION****United States Regulatory Information**

**TSCA 8 (b) Inventory Status:** All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.  
**TSCA 12 (b) Export Notification:** None above reporting de minimis.  
**CERCLA/SARA Section 302 EHS:** None above reporting de minimis.  
**CERCLA/SARA Section 311/312:** Immediate Health, Delayed Health  
**CERCLA/SARA Section 313:** This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Copper (CAS# 7440-50-8). copper flakes (coated with aliphatic acid) (CAS# 7440-50-8).  
**CERCLA Reportable quantity:** Copper (CAS# 7440-50-8) 5,000 lbs. (2,270 kg)  
**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

**Canada Regulatory Information**

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

**16. OTHER INFORMATION**

This safety data sheet contains changes from the previous version in sections: 3,8,9,11,14,15

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 02/22/2024

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.