



Clear Penetrating Grease



FEATURES

- High tack
- Quick penetrating action
- Resists water washout
- Protects against corrosion
- Clear lubricating gel

APPLICATIONS

- Bottling Equipment
- Bushings
- Cables
- Chains
- Door Hinges
- Food Machinery
- Fork Lifts
- Pistons
- Rails
- Rings
- Seals
- Slides
- Valves
- Wire Rope

PROPERTIES

Appearance / Physical State	Gas.
Color	Beige.
Odor	Acetone.
Boiling Point / Range	132.8 °F (56 °C)
Flash Point	132.8 °F (56.0 °C) Tag Closed Cup
Flammability	Flammable gas.
Vapor density	2 (air = 1)
Water Solubility	Partially miscible.
Auto-Ignition Temperature	Not available.
Viscosity	260 cP @ 75°F (concentrate)
Density	6.80
Heat of Combustion	> 30 kJ/g
Percent Volatile	41.5%
Specific Gravity	0.82
VOC Content	24.5 % per U.S. State and Federal Consumer Product Regulations
Temperature Range	0°F (-18°C) to 400°F (204°C)
4-Ball Weld Load	126 kg
Thickener Type	Aluminum Complex

DIRECTIONS

Shake well before using to insure proper mixing. Apply liberally. A thicken grease will form within seconds after application.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. (See Section 7 of the SDS)

STORAGE

Level 3 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. (See Section 7 of the SDS)

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations. (See Section 13 of the SDS)

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
06716	C06716	11 wt oz	aerosol	12	12 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved