



CRC Dry Moly Lube

ATTRIBUTES –

Item Number

1003351

Case Number

1003350

Legacy Number

03084

Product Description

Lowers friction, prevents galling and helps to reduce torque and energy consumption. High anti-friction and anti-seizure properties. Fast drying film resists dirt and dust build-up.

Applications

Gaskets, transfer belts, conveyor belts, motors, plant machinery and handling equipment, rubber moldings, high temperature, low load, or high rpm slides, rollers, wheels, gears, chains & hoists

Unit Package Description

16 Ounce Aerosol

Brand

CRC

Net Fill

11 Wt Oz

UPC Code

78254030845

Unit Dimensions

7.75H x 2.63W x 2.63D in

Units Per Case

12

Case Dimensions

8.6H x 8.4W x 11.3D in

Cases per pallet USA

133

Appearance

Dark Gray Viscous Liquid

Flash point (F)

-4°F

Flash point (C)

-20°C

Flammability Class - CPSC

Extremely Flammable

Spec Gravity Concentrate

0.81

KB Value

N/A

Plastic Safe

No

Film Type

Dry

Evaporation Rate

Fast

Timken Ok Load (lbs)

N/A

Propellant

Hydrocarbon

Aerosol Flammability Level

III

DOT Proper Shipping Name

Aerosols, Flammable, LIMITED QUANTITY

4 Ball EP

Not Determined

4 Ball Wear

Not Determined

Drop Point

N/A

pH

N/A

SAE Grade

N/A

Water Washout

N/A

Working Temp (F)

400°F (Continuous) / 850°F (Intermittent)

Working Temp (C)

204°C (Continuous) / 454°C (Intermittent)

VOC % (Consumer Product def)

46.9

VOC g/L (Consumer Product def)

375.2

VOC lbs/gal (Consumer Prod def)

3.13

VOC Category

Dry Film Lubricant

Removal (How To)

Remove with a heavy duty degreaser.