# -Lube<sup>®</sup> Stick Lube Hand-Applied Lubricant

# **FEATURES**

- Solid lubricant stick for rotating or stationary cutting tools
- Convenient push-up container to keep hands clean while applying to cutting tool
- Reduces friction for cleaner cutting and better finish
- Vegetable-based, biodegradable lubricant
- Worker friendly and environmentally safe formula
- For ferrous & nonferrous metals, aluminum and titanium
- Clean with soap and water

# APPLICATIONS

- Short-run machining
- Belt, disc and wheel grinding • General machining, sawing, • Ferrous & nonferrous metals, aluminum and titanium
- and cutting operations
- Rotating or stationary cutting field and kept in a toolbox for tools
- Drilling, tapping, milling, etc. Portable can be used in the use at remote locations

## DIRECTIONS

Apply sparingly, directly on the tool.

## HANDLING

Observe good industrial hygiene practices. Avoid contact with skin, eyes, clothing. Wash thoroughly after handling.

#### **STORAGE**

Keep container tightly closed in a dry and well-ventilated place.

#### DISPOSAL

Dispose of in accordance with local regulations.



# PHYSICAL PROPERTIES

Appearance / Physical State	Solid. Paste.		
Color	White		
Odor	Mild		
Melting / Freezing Point	109.4 - 120.2°F (43 - 49°C)		
Boiling Point / Range	>399.2°F (>204°C)		
Flash Point	>199.4°F (>93.0°C) Pensky-		
	Martens Closed Cup		
Vapor Pressure	< 1 mm Hg		
Vapor density	>1		
Specific Gravity	0.86		
VOC Content	None		
Prop 65 Warning	Yes		

## **AVAILABLE PRODUCTS**

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
79042	2.2 oz	push-up stick	24	6 lbs
79045	13 wt oz	Stick	24	23 lbs



#### **CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved