Date Prepared/Revised: 2/23/24 Version no.: 05 Supersedes: (10/2/19)

1.) Identification of the Mixture and of the Company

Product identifier: Crown Brite Galvanize Coating 65% Zinc Rich - Aerosol

Product name:

7008 Crown Brite Galvanize Coating 65% Zinc Rich

Relevant identified uses of the substance: Use on damaged galvanized surfaces, structural steel, automobiles, chain link fences, guard rails, hand rails, bridges, TV and radio towers, heat ducts, welded joints, storage tanks, signs and sign posts, equipment (farming, mining and construction, power plant, railroad, offshore, etc.), gutters, pipelines, transformers, corrugated metal buildings and anywhere the bright look of hot-dipped surfaces is desired. Ideal for industrial type application, (e.g., aviation, marine, manufacturing, petroleum).

Uses advised against: Do not apply at temperatures below 40°F (4°C), or if rain is imminent within 6 hours of application

CAS No:	Not Applicable (mixture)
EC No:	Not Applicable (mixture)
Index No:	Not Applicable (mixture)
Manufacturer/Supplier:	Aervoe Industries Incorporated
Street address/P.O. Box:	1100 Mark Circle
Country ID/Postcode/Place	Gardnerville, Nevada 89410
Telephone number:	1-775-782-0100
e-mail:	mailbox@aervoe.com
National contact:	Aervoe Industries Incorporated
For Product Information:	1-800-227-0196
Emergency telephone number:	1-800-424-9300 (CHEMTREC – 24 hrs)

#### 2. Hazards identification

#### Classifications

Physical Hazards:	Aerosol - Category 1 Flam. Liq. 2 Flam. Liq. 3 Liquified Gas
	Flam. Gas 1
Health Hazards:	
	Asp. Tox. 1
	Skin Irr. 2
	Eye Irrit. 2
	STOT SE 3
Environmental Hazards:	
	Aquatic Acute 1
	Aquatic Chronic 1
	Aquatic Tox. 2
Environmental Hazards:	Skin Irr. 2 Eye Irrit. 2 STOT SE 3 Aquatic Acute 1 Aquatic Chronic 1

Date Prepared/Revised: 2/23/24 Version no.: 05 Supersedes: (10/2/19)

# Labeling

LERVOE

Signal Word:	Danger
Hazard Statements:	<ul> <li>H220 – Extremely flammable gas.</li> <li>H222 – Extremely Flammable Aerosol</li> <li>H224 – Extremely flammable liquid and vapor.</li> <li>H225 – Highly flammable liquid and vapor.</li> <li>H229 – Pressurized container: may burst if heated</li> <li>H304 – May be fatal if swallowed and enters airways</li> <li>H315 – Causes skin irritation.</li> <li>H319 – Causes serious eye irritation.</li> <li>H336 – May cause drowsiness or dizziness.</li> <li>H400 – Very toxic to aquatic life.</li> <li>H410 – Very toxic to aquatic life with long lasting effects.</li> <li>H411 – Toxic to aquatic life with long lasting effects.</li> </ul>
Precautionary Statements:	<ul> <li>P101 - If medical advice is needed, have product container or label at hand</li> <li>P102 - Keep out of reach of children</li> <li>P103 - Read label before use</li> <li>P210 - Keep away from heat/sparks/open flames/hot surfaces - no smoking</li> <li>P211 - Do not spray on an open flame or other ignition source</li> <li>P251 - Pressurized container: Do not pierce or burn, even after use</li> <li>P261 - Avoid breathing dust/fume/gas/mist/vapours/spray</li> <li>P262 - Do not get in eyes, on skin, or on clothing</li> <li>P264 - Wash thoroughly after handling</li> <li>P280 - Wear protective gloves/eye protection/face protection</li> <li>P303+P361+P353 - If on skin or hair, remove/takeoff immediately all contaminated clothing. Rinse skin with water/shower.</li> <li>P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F</li> <li>P501 - Dispose of contents/container in accordance with local/regional/national/international regulation</li> </ul>



Symbols/Pictograms:

# 3. Composition / Information on Ingredients

# Composition

Chemical Synonyms	CAS	EINECS	Weight	Hazard Category	H-Code
-------------------	-----	--------	--------	-----------------	--------



Date Prepared/Revised: 2/23/24 Version no.: 05 Supersedes: (10/2/19)

		Number	Number	Percent		
Acetone	Propanone	67-64-1	200-662-2	15-40%	Flam. Liq. 2	H225
					Eye Irrit. 2	H319
					STOT SE 3	H336
Hydrocarbon	LPG	68476-86-8	270-705-8	10-30%	Liquified Gas	H220
Propellant					Flam. Gas 1	H229
Zinc Powder	Zinc Dust	7440-66-6	231-175-3	10-30%	Aquatic Acute 1	H400
					Aquatic Chronic 1	H410
n-Butyl	n-Butyl Ester	123-86-4	204-658-1	10-30%	Flam. Liq. 3	H226
Acetate					STOT SE 3	H336
Aliphatic	Solvent	64742-89-8	265-192-2	1-5%	Flam Liq. 2	H224
Petroleum	Naphtha				Skin Irr. 2	H304
Distillates					Asp. Tox. 1	H315
					STOT SE 3	H336
					Aquatic Tox. 2	H411

# **Other Product Information**

Chemical Identity: Mixture

4.)	) First Aid	Measures
-----	-------------	----------

General Advice:	If symptoms persist, always call a doctor.
Inhalation First Aid:	Remove victim to fresh air and provide oxygen if breathing is
	difficult. If not breathing, give artificial respiration, preferably
	mouth to mouth. Get medical attention immediately.
Skin Contact First Aid:	Wash with soap and water. Remove contaminated clothing and
	shoes. Get medical attention immediately. Wash clothing before reuse.
Eye Contact First Aid:	If contact with eyes, immediately flush eyes with plenty of water
-	for at least 15 minutes, while holding eyelids open. Get medical
	attention immediately.
Ingestion First Aid:	If swallowed, wash out mouth with water provided the person is
-	conscious. Do not induce vomiting. Never give anything by mouth
	to an unconscious person. Get medical attention immediately.
Most Important	-
Symptoms/Effects:	Exposure may cause slight irritation to the skin, eyes, and respiratory tract.
	Excessive exposure may cause central nervous system effects.

# **5. Fire Fighting Measures**

Flammable Properties:
Auto Ignition Temperature:
Suitable extinguishing media:
Unsuitable extinguishing media:
Special hazards arising from the

Aerosol Not Available Carbon dioxide, dry chemical, water spray. None known



Date Prepared/Revised: 2/23/24 Version no.: 05 Supersedes: (10/2/19)

substance or mixture:	None known
Hazardous combustion products:	Carbon dioxide, Carbon monoxide
Fire & Explosion Hazards:	Closed Containers may rupture due to the buildup of pressure
	from extreme temperatures.
pressu NIOS	rater spray to cool containers exposed to heat or fire to prevent are build up. In the event of a fire, wear full protective clothing and H- approved self-contained breathing apparatus with full face piece and in the pressure demand or other positive pressure mode.

#### 6. Accidental Release Measures

## PERSONAL PRECAUTIONARY MEASURES:

- 1) Follow personal protective equipment recommendations found in section 8.
- 2) Maintain adequate ventilation.

## **SPILL CLEAN-UP PROCEDURES:**

- 1.) Evacuate unprotected personnel from the area.
- 2.) Remove sources of ignition if safe to do so.
- 3.) Pickup spilled materials using non-sparking tools and place in an appropriate container for disposal.
- 4.) Contain spill to prevent material from entering sewage or ground water systems.
- 5.) Always dispose of waste materials in accordance with all EU, National and Local Regulations.

7.	Hand	ling	and	Storage
----	------	------	-----	---------

#### Handling:

Flammable Aerosol, use in a well ventilated area.

Do not use near sources of ignition.

Do not to eat, drink and smoke while working with this material.

Wash hands after use.

# Conditions for safe storage, including any incompatibilities:

Store out of direct sunlight.

Storage Temperature: 32° to 120°F (0° to 49°C). No known incompatibilities.

# 8. Exposure Controls / Personal Protection

## Appropriate engineering controls:

Ensure adequate ventilation. A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits.

Keep away from sources of ignition.

Take precautionary measures against static discharge.

## **Personal Protection:**

Eye & face protection devices such as safety glasses, safety goggles or face shield are recommended.



Date Prepared/Revised: 2/23/24 Version no.: 05 Supersedes: (10/2/19)

#### **Skin protection**

Wear the appropriate protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

#### **Respiratory protection:**

Use only in an adequately ventilated area. For unknown vapor concentrations use a positive-pressure, pressure-demand, self-contained breathing apparatus (SCBA).

Hazardous Ingredient	CAS	ACGIH TLV	ACGIH TLV	OSHA PEL	OSHA PEL
	Number	(TWA)	(STEL)	(TWA)	(STEL)
Acetone	67-64-1	250PPM	500PPM	1000PPM	N/A
Hydrocarbon Propellant	68476-86-8	N/A	N/A	N/A	N/A
Zinc Powder	7440-66-6	N/A	N/A	N/A	N/A
n-Butyl Acetate	123-86-4	50PPM	150PPM	N/A	N/A
Aliphatic Petroleum Distillates	64742-89-8	N/A	N/A	N/A	N/A

#### \*Values are based on the 2019 Guide to Occupational Exposure Values by ACGIH

# 9. Information on Basic Physical and Chemical Properties

Appearance: Metallic gray	Odor: Ketone Odor
Odor Threshold: N/AV	pH: Not Applicable (solvent Base)
Melting Point: N/AV	Freezing Point: N/AV
Initial Boiling Point: N/AV	Boiling Point Range: N/AV
Flash Point: <0° F (-18° C)	Evaporation Rate: Faster than n-Butyl
	Acetate
Flammability Solid/Gas: Flammable gas	LEL: 0.9% UEL: 12.8%
Vapor Pressure: N/AV	Vapor Density: Heavier Than Air
Relative Density: N/AV	Solubility: Negligible
Partition Coefficient:	Auto-ignition Temperature: N/AV
n-octanol/ water: N/AV	
Decomposition Temperature: N/AV	Viscosity: N/AV
Explosive Properties: N/AV	Oxidizing Properties: N/AV

#### **10. Stability & Reactivity**

Possibility of hazardous reactions: Hazardous polymerization will not occur under normal conditions Chemical stability: Stable under normal conditions Conditions to avoid: Heat and ignition sources Incompatible materials: Strong Oxidizing Agents Hazardous decomposition products: Will not occur

#### **11. Toxicological Information**

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart and blood



Date Prepared/Revised: 2/23/24 Version no.: 05 Supersedes: (10/2/19)

Routes of exposure: Eyes, skin, ingestion, and/or inhalation

Acute toxicological data:	(Acetone) 5800 mg/kg (Rat-Oral) (Acetone) 21000 ppm/8 hr (Rat-Inha)
Eye irritation data:	Eye Irrit 2
Skin irritation/sensitization/absorption data:	Skin Irrit 2
Reproductive toxicity data:	N/AV
Mutagenicity data:	N/AV
Symptoms associated with physical contact:	N/AV
Acute/chronic effects from short/long term exposure:	Irritating to skin. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis. Not expected to be a skin sensitizer.
Known reportable carcinogens via the following agencies:	
NTP:	N/AV
IARC:	N/AV
OSHA:	TLV-A4
12. Ecological Information	

Ecotoxicity: **No Data Available** Persistence and degradability: **No Data Available** Bioaccumulative potential: **No Data Available** Mobility in soil: **No Data Available** Results of PBT and vPvB assessment: **No Data Available** Other adverse effects: **No Data Available** 

## 13. Disposal Considerations

**Waste Disposal:** Dispose of material in accordance with EU, national and local requirements. For proper disposal of used material, an assessment must be completed to determine the proper and permissible waste management options permitted under applicable rules, regulations and/or laws governing your location.

**Product / Packaging disposal:** Dispose of packaging in accordance with federal, state and local requirements, regulations and/or laws governing your location.



Date Prepared/Revised: 2/23/24 Version no.: 05 Supersedes: (10/2/19)

#### **US DOT**

00201					
UN	Proper Shipping Name	Hazard	Packing	Marine	Special
Number		Class	Group	Pollutant	Provisions
UN1950	Aerosols	2.1	Not	Not	Reference 49
			Applicable	Applicable	CFR 172.101

#### IMDG

UN	Proper Shipping Name	Hazard	Packing	Marine	Special
Number		Class	Group	Pollutant	Provisions
UN1950	Aerosols	2.1	Not	Not	Reference
			Applicable	Applicable	IMDG code
					part 3

#### IATA:

UN	Proper Shipping Name	Hazard	Packing	Marine	Special
Number		Class	Group	Pollutant	Provisions
UN1950	Aerosols, Flammable	2.1	Not	Not	Reference
			Applicable	Applicable	IATA
					Dangerous
					Goods
					Regulation

## **15. Regulatory Information**

## Workplace classification:

This product is considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). The Occupational Safety and Health Administration's interpretation of the product's hazard to workers.

# SARA Title 3:

Section 311/312 Categorizations (40 CFR 372): This product is a hazardous chemical under 29 CFR 1910.1200, and is categorized as an immediate and delayed health, and flammability physical hazard. Superfund Amendment and Reauthorization Act (SARA) category. SARA requires reporting any spill of any hazardous substance.

**TSCA status:** All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

**WHMIS:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the (M)SDS contains all of the information required by the CPR.

# **16. Other Information**

This SDS has been completed in accordance with GHS Rev04 (2011): U.S OSHA, CMA, ANSI, Canadian WHMIS standards, and European Directives.

Date of Preparation/Revision: 2/23/24 Supersedes: 10/2/19



Date Prepared/Revised: 2/23/24 Version no.: 05 Supersedes: (10/2/19)

To the best of our knowledge, the information contained herein is believed to be accurate. However, the above data does not imply any guarantee or warranty of any kind, expressed or implied. The final determination of the suitability of any material is the sole responsibility of the user. All materials made present un-known hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee these are the only hazards existing.