Safety Data Sheet

Date of issue: 03/05/2025 Revised On 03/05/2025

1 Identification of the substance and manufacturer

Trade name: SANDVICK ORANGE

Other means of identification

TS00663121 Product code:

Article category

Paint and coatings application. Recommended use:

Uses advised against: Any that differs from the recommended use.

Distributed By: Manufacturer/Supplier:

Tacoma Screw Products, Inc.

2001 Center Street Tacoma, WA 98409 800-562-8192

Emergency telephone number: 1-800-255-3924

2 Hazard(s) identification

Classification of the substance or mixture

Aerosols 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

Eye irritation 2A Causes serious eye irritation. H319 H336

Specific target organ toxicity (single exposure) 3 May cause drowsiness or dizziness. Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms**

GHS02 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol. Pressurized container: may burst if heated.

Causes serious eye irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. **Precautionary statements**

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. If inhaled: Remove person to fresh air and keep comfortable for breathing

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.
Call a poison center/doctor if you feel unwell.
If eye irritation persists: Get medical advice/attention.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).

Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

HMIS-ratings (0 - 4): Health= Fire=

Physical Hazard= 3

PPE----B

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
	Acetone	15-25%
	propane	15-25%
	barium sulfate	5-10%
106-97-8		5-10%
	Isobutyl Acetate	5-10%
	Glycol Ether EP	≥5-<10%
	butyl acetate	1-5%
	PM acetate	1-5%
107-87-9	Methyl Propyl Ketone	1-5%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After eye contact:

Rinse out mouth and then drink plenty of water. After swallowing: Rinse mouth with water. Do not induce vomiting

(Contd. on page 2)

(Contd. of page 1)

Date of issue: 03/05/2025 Revised On 03/05/2025

Trade name: SANDVICK ORANGE

Most important symptoms and

effects:

Dizziness

Indication of any immediate medical attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: Special hazards:

Protective equipment for

firefighters:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

7 Handling and storage

Precautions for safe handling

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection

Components	Components with limit values that require monitoring at the workplace:		
67-64-1 Acet	one		
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm		
REL (USA)	Long-term value: 590 mg/m³, 250 ppm		
TLV (USA)	Short-term value: 500 ppm		
	Long-term value: 250 ppm A4, BEI		
74-98-6 prop			
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm		
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm		
TLV (USA)	see Appendix F Minimal oxygen content (D, EX)		
7727-43-7 barium sulfate			
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction		
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction		
TLV (USA)	Long-term value: 5* mg/m³ *inhalable fraction; E		
106-97-8 n-butane			
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm		
TLV (USA)	Short-term value: 1000 ppm (EX)		
	butyl Acetate		
PEL (USA)	Long-term value: 700 mg/m³, 150 ppm		
REL (USA)	Long-term value: 700 mg/m³, 150 ppm		
TLV (USA)	Short-term value: 150 ppm		
, ,	Long-term value: 50 ppm		
123-86-4 but			
PEL (USA)	Long-term value: 710 mg/m³, 150 ppm		
REL (USA)	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm		
TLV (USA)	Short-term value: 150 ppm Long-term value: 50 ppm		
108-65-6 PM			
	Long-term value: 50 ppm		
107-87-9 Methyl Propyl Ketone			
PEL (USA)	Long-term value: 700 mg/m³, 200 ppm		
REL (USA)	Long-term value: 530 mg/m³, 150 ppm		
TLV (USA)	Short-term value: 150 ppm		

(Contd. on page 3)

(Contd. of page 2)

Date of issue: 03/05/2025 Revised On 03/05/2025

Trade name: SANDVICK ORANGE

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 25 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In

cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Physical state
Odor:
Odor threshold:
Melting point/Melting range
Boiling point:
Flammability:
Aerosol
Aromatic
Not determined.
Undetermined.
-44 °C (-47.2 °F)
Extremely flammable.

Lower Explosion Limit: 1.7 Vol % Upper Explosion Limit: 10.9 Vol % -19 °C (-2.2 °F) Flash point: Flammability (solid, gas): Extremely flammable. Decomposition temperature: Not determined. pH-value: Viscosity: Not determined. Not determined. Solubility: Not determined. Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density Not determined.
Particle characteristics Not applicable.
Appearance: Aerosol.

Ignition temperature: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Water: 0.0 %

Evaporation rate Not applicable. Partition coefficient: n-octonal/water: Not determined.

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

4,763 mg/kg (rbt)

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD50

LD/LC50 values that are relevant for classification:
110-19-0 Isobutyl Acetate

123-86-4 butyl acetate

Oral

Oral LD50 14,000 mg/kg (rat) Inhalative LC50/4 h >21 mg/l (rat)

108-65-6 PM acetate

Oral LD50 8,500 mg/kg (rat) Inhalative LC50/4 h 35.7 mg/l (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

Safety Data Sheet

Date of issue: 03/05/2025 Revised On 03/05/2025

Trade name: SANDVICK ORANGE

(Contd. of page 3)

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl

substances (PFA's), or chlorinated solvents.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950 DOT UN1950 DOT DOT

Aerosols, flammable

1950 Aerosols **ADR**

Transport hazard class(es):

Class 2.1 Gases Nο

Marine pollutant: Special marking (IATA):

Packaging Group:

Warning: Gases Special precautions for user: F-D.S-Ŭ

EMS Number:

UN1950, Aerosols, 2.1 **UN "Model Regulation":**

15 Regulatory information

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulfate

Toxic Substances Control Act

(TSCA): All ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

(DSL): All ingredients are listed or exempted.

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

108-10-1 methyl isobutyl ketone

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-10-1 methyl isobutyl ketone

EPA:

67-64-1 Acetone

7727-43-7 barium sulfate D, CBD(inh), NL(oral)

110-19-0 Isobutyl Acetate

16 Other information

Contact: Regulatory Affairs