Printing date 01/10/2020 Revised On 01/02/2020

### 1 Identification of the substance and manufacturer

Trade name: MRO GLOSS WHITE (BULK)

Product code: 0000011413

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com

3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

Seymour of Sycamore

www.seymourpaint.com

**Emergency telephone number:** 

1-800-255-3924

### 2 Hazard(s) identification

#### Classification of the substance or mixture

Flam. Liq. 3 H226 Flammable liquid and vapor. Eye Irrit. 2A H319 Causes serious eye irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms







GHS02 GHS07 GHS08

Signal word Warning

Flammable liquid and vapor. **Hazard statements** 

Causes serious eve irritation.

May cause damage to organs through prolonged or repeated exposure. **Precautionary statements** Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.
Do not breathe dust/fume/gas/mist/vapors/spray.

Wash hands thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Dispose of contents/container in accordance with local/regional/national/international regulations.

# 3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

| Dangerous components: |                  |          |
|-----------------------|------------------|----------|
| 64742-47-8            | Mineral Spirits  | 15-25%   |
| 13463-67-7            | titanium dioxide | ≥15-<20% |
| 7727-43-7             | barium sulfate   | 10-15%   |
| 1330-20-7             | xylene (mix)     | 1-5%     |

#### 4 First-aid measures

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Rinse opened eye for several minutes under running water. Rinse mouth with water. Do not induce vomiting.

After swallowing:

Most important symptoms and

effects: Indication of any immediate medical

No further relevant information available.

attention needed: No further relevant information available.

## 5 Fire-fighting measures

Special hazards: No further relevant information available.

Protective equipment for firefighters: No special measures required.

# 6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Methods and material for

containment and cleaning up:

Not required.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Safety Data Sheet

Printing date 01/10/2020 Revised On 01/02/2020

Trade name: MRO GLOSS WHITE (BULK)

(Contd. of page 1)

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Storage requirements:

Store locked up.

# 8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

7727-43-7 barium sulfate

PEL (USA) Long-term value: 15\* 5\*\* mg/m³

total dust \*\*respirable fraction

REL (USA) Long-term value: 10\* 5\*\* mg/m³ \*total dust \*\*respirable fraction

TLV (USA) Long-term value: 5\* mg/m³ \*inhalable fraction; E

1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m³, 100 ppm

REL (USA) Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm

Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm TLV (USA)

Ingredients with biological limit values:

1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Methylhippuric acids

Hygienic protection: Wash hands after use.

Do not eat or drink while working.

**Breathing equipment:** Not required.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles Eye protection:

# 9 Physical and chemical properties

Appearance: Liquid.

Odor threshold: Not determined. Not determined. pH-value: Melting point/Melting range Undetermined. 157 °C (314.6 °F) **Boiling point:** 43 °C (109.4 °F) Flash point:

Flammability (solid, gas): Flammable. **Decomposition temperature:** Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

0.5 Vol % 6.5 Vol % **Lower Explosion Limit: Upper Explosion Limit:** Vapor pressure: Not determined. Vapor density Not determined. Evaporation rate Not determined. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Viscosity: Not determined.

VOC content (less exempt solvents): 23.8 %

### 10 Stability and reactivity

No decomposition if used according to specifications. Conditions to avoid:

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. No dangerous decomposition products known. Hazardous decomposition:

Safety Data Sheet

Printing date 01/10/2020 Revised On 01/02/2020

Trade name: MRO GLOSS WHITE (BULK)

(Contd. of page 2)

# 11 Toxicological information

LD/LC50 values that are relevant for classification:

13463-67-7 titanium dioxide

LD50 >20,000 mg/kg (rat) Oral Dermal LD50 >10,000 mg/kg (rbt) Inhalative LC50/4 h >6.82 mg/l (rat)

1330-20-7 xylene (mix)

LD50 8,700 mg/kg (rat) Oral Dermal LD50 2,000 mg/kg (rbt) Inhalative LC50/4 h 6,350 mg/l (rat)

Information on toxicological effects: No data available. No irritant effect. Skin effects: Eye effects: No irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated Other information:

solvents.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

# 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Completely empty cans should be recycled. Recommendation:

# 14 Transport information

**UN-Number** 

DOT UN1263 DOT Paint **1263 PAINT ADR** 

Transport hazard class(es):

Class 3 Flammable liquids

Warning: Flammable liquids Special precautions for user:

F-E,S-È EMS Number: **Stowage Category** 

Packaging Group: Ш

UN "Model Regulation": UN 1263 PAINT, 3, III

### 15 Regulatory information

# SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed

### SARA Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulfate

1330-20-7 xylene (mix)

All hazardous ingredients are found on the inventory list of substances. (TSCA):

Canadian Domestic Substances List

All ingredients are listed or exempted. (DSL):

Consumer Product Safety

**Toxic Substances Control Act** 

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

# California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

### Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

EPA:

7727-43-7 barium sulfate D, CBD(inh), NL(oral)

(Contd. on page 4)

Page 4/4

# Safety Data Sheet

Printing date 01/10/2020 Revised On 01/02/2020

Trade name: MRO GLOSS WHITE (BULK)

(Contd. of page 3)

1330-20-7 | xylene (mix)

16 Other information
Contact: Regulatory Affairs