Printing date 01/04/2021 Revised On 01/04/2021

1 Identification of the substance and manufacturer

Trade name: FLAT BLACK (MRO) GALLONS

0000011433 Product code:

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101

www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:**

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Liq. 2 H225 Highly flammable liquid and vapor. STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information:

GHS Hazard pictograms

Precautionary statements







Signal word Danger

Hazard statements Highly flammable liquid and vapor.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALÈD: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

This product is a mixture of the substances listed below with nonhazardous additions. **Chemical Description:**

Dangerous components:			
1317-65-3	Calcium Carbonate	25-50%	
64742-47-8	Mineral Spirits	15-25%	
	Silicon Dioxide	5-10%	
	zinc stearate	1-5%	
108-65-6	PM acetate	1-5%	

4 First-aid measures

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

Rinse out mouth and then drink plenty of water. After swallowing: Rinse mouth with water. Do not induce vomiting

Most important symptoms and

effects: No further relevant information available.

Indication of any immediate medical

No further relevant information available. attention needed:

5 Fire-fighting measures

Special hazards: No further relevant information available.

Protective equipment for firefighters: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency

Wear protective equipment. Keep unprotected persons away. procedures:

(Contd. on page 2)

Safety Data Sheet

Printing date 01/04/2021 Revised On 01/04/2021

Trade name: FLAT BLACK (MRO) GALLONS

Methods and material for

Ensure adequate ventilation.

(Contd. of page 1)

containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

7 Handling and storage

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

Components with limit values that r	require monitoring	at the workplace:
-------------------------------------	--------------------	-------------------

112926-00-8 Silicon Dioxide

20mppcf or 80mg/m3 /%SiO2 PEL (USA)

Long-term value: 6 mg/m³ REL (USA)

See Pocket Guide App. C

TLV (USA) TLV withdrawn

557-05-1 zinc stearate

Long-term value: 15* 5** mg/m³ PEL (USA)

*total dust **respirable fraction Long-term value: 10* 5** mg/m3 *totăl dust **respirable fraction

TLV (USA) Long-term value: 10 mg/m³

108-65-6 PM acetate

REL (USA)

WEEL (USA) Long-term value: 50 ppm

Keep away from foodstuffs and animal feed. Wash hands after use. Hygienic protection:

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Do not eat or drink while working.

Breathing equipment: Not required.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles Eye protection:

9 Physical and chemical properties

Appearance: Liquid. Odor threshold: Not determined.

Not determined. pH-value: Melting point/Melting range Undetermined. 175 °C (347 °F) **Boiling point:** -19 °C (-2.2 °F) Flash point: Flammability (solid, gas): Highly flammable.

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

In use, may form flammable/explosive vapour-air mixture. Danger of explosion:

Lower Explosion Limit: 0.5 Vol % Upper Explosion Limit: 6.5 Vol % Vapor pressure: Not determined. Vapor density Not determined. Evaporation rate Not determined. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Not determined. Viscosity:

10 Stability and reactivity Conditions to avoid:

Water:

No decomposition if used according to specifications.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

0.0 %

Printing date 01/04/2021 Revised On 01/04/2021

Trade name: FLAT BLACK (MRO) GALLONS

(Contd. of page 2)

11 Toxicological information

LD/LC50 values that are relevant for classification:

108-65-6 PM acetate

LD50 8,500 mg/kg (rat) Oral Inhalative LC50/4 h 35.7 mg/l (rat)

Information on toxicological effects: No data available. No irritant effect. Skin effects:

Eye effects: No irritating effect. Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated Other information:

solvents.

Bioaccumulative potential: No further relevant information available. No further relevant information available. Mobility in soil: Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Completely empty cans should be recycled. Recommendation:

14 Transport information

UN-Number

ADR 1263 Paint

Transport hazard class(es):

Class

3 Flammable liquids Nο

Marine pollutant:

Warning: Flammable liquids Special precautions for user: EMS Number:

F-E,S-Ĕ

Stowage Category В Packaging Group:

UN "Model Regulation": UN 1263 PAINT, 3, II

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

557-05-1 zinc stearate

Toxic Substances Control Act

All hazardous ingredients are found on the inventory list of substances. (TSCA):

Canadian Domestic Substances List

(DSL): Consumer Product Safety All ingredients are listed or exempted.

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead. Comission (CPSC):

California Proposition 65 chemicals known to cause cancer:

1333-86-4 Carbon black

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

EPA:

557-05-1 zinc stearate D, I, II

16 Other information

Contact: Regulatory Affairs