

Schedule 80 CPVC Industrial Products & Accessories True Union 2000 Industrial Ball Valves



Socket Style



SR Threaded Style



6" Lever Handle Style

All Valves Assembled with Silicone-Free, Water Soluble Lubricant
Contact Spears® for Pricing on Custom Elastomer Seals

See Ball Valve Accessories & Repair Kits Section for Additional Options and Features

Pressure Rating @ 73°F (23°C), Water

1/2" - 4" 235 psi
6" - 8" 150 psi
All Flanged 150 psi

Maximum Service Temperature

CPVC = 200°F (93°C)
Temperature/Pressure De-ratings Apply
Rated for Vacuum Service

Note: Standard 6" Valve uses lockout type Lever-Style Handle for proper leverage.

Non-locking T-Handle is more compact, but will increase difficulty of operation.

True Union 2000 Industrial Ball Valves have Built-in Handle Lockouts (except 6" T-Handle Option)

CPVC Industrial

Size	EPDM	FKM	Std Pk	Mstr Pk	Disc Code
------	------	-----	--------	---------	-----------

Threaded & Socket Ends

1/2	1829-005C 65.63	1839-005C 72.93	1	18	602
3/4	1829-007C 82.65	1839-007C 91.86	1	18	602
1	1829-010C 98.40	1839-010C 109.33	1	12	602
1-1/4	1829-012C 156.43	1839-012C 173.86	1	8	602
1-1/2	1829-015C 165.21	1839-015C 183.57	1	8	602
2	1829-020C 220.95	1839-020C 254.00	1	4	602

Socket Ends

2-1/2	1822-025C 495.39	1832-025C 550.40	1	0	603
3	1822-030C 579.22	1832-030C 643.63	1	0	603
4	1822-040C 1049.59	1832-040C 1166.19	1	0	603
6	1822-060C 2234.41	1832-060C 2482.51	1	0	613
8	1822-080C 2971.79	1832-080C 3301.76	1	0	613

8" Venturied valves are 6" ball valves fitted with 6x8 end connector adapters.

Threaded Ends

2-1/2	1821-025C 495.39	1831-025C 550.40	1	0	603
3	1821-030C 579.22	1831-030C 643.63	1	0	603
4	1821-040C 1049.59	1831-040C 1166.19	1	0	603
6	1821-060C 2234.41	1831-060C 2482.51	1	0	613

SR Threaded Ends

1/2	1821-005CSR 66.68	1831-005CSR 73.99	1	18	602
3/4	1821-007CSR 85.23	1831-007CSR 94.43	1	18	602
1	1821-010CSR 100.98	1831-010CSR 111.88	1	12	602
1-1/4	1821-012CSR 164.17	1831-012CSR 181.60	1	8	602
1-1/2	1821-015CSR 173.53	1831-015CSR 191.85	1	8	602
2	1821-020CSR 229.95	1831-020CSR 263.00	1	4	602
2-1/2	1821-025CSR 519.58	1831-025CSR 574.58	1	0	603
3	1821-030CSR 603.40	1831-030CSR 667.80	1	0	603
4	1821-040CSR 1077.80	1831-040CSR 1194.44	1	0	603
6	1821-060CSR 2295.64	1831-060CSR 2543.73	1	0	613

CPVC Industrial

Size	EPDM	FKM	Std Pk	Mstr Pk	Disc Code
------	------	-----	--------	---------	-----------

Spigot Ends

1/2	1827-005C 65.63	1837-005C 72.93	1	18	602
3/4	1827-007C 82.65	1837-007C 91.86	1	18	602
1	1827-010C 98.40	1837-010C 109.33	1	12	602
1-1/4	1827-012C 156.43	1837-012C 173.86	1	8	602
1-1/2	1827-015C 165.21	1837-015C 183.57	1	8	602
2	1827-020C 220.95	1837-020C 254.00	1	4	602
2-1/2	1827-025C 495.39	1837-025C 550.40	1	0	603
3	1827-030C 579.22	1837-030C 643.63	1	0	603
4	1827-040C 1049.59	1837-040C 1166.19	1	0	603
6	1827-060C 2234.41	1837-060C 2482.51	1	0	613

Flanged Ends

1/2	1823-005C 111.36	1833-005C 113.76	1	8	602
3/4	1823-007C 136.51	1833-007C 142.17	1	8	602
1	1823-010C 156.26	1833-010C 165.88	1	8	602
1-1/4	1823-012C 233.48	1833-012C 241.68	1	8	602
1-1/2	1823-015C 256.82	1833-015C 265.38	1	4	602
2	1823-020C 357.38	1833-020C 425.63	1	0	602
2-1/2	1823-025C 667.02	1833-025C 800.64	1	0	603
3	1823-030C 975.47	1833-030C 997.72	1	0	603
4	1823-040C 1710.82	1833-040C 1779.24	1	0	603
6	1823-060C 3644.03	1833-060C 3789.02	1	0	613
8	1823-080C 4846.55	1833-080C 5039.38	1	0	613

8" Venturied valves are 6" ball valves fitted with 6x8 end connector adapters.

CPVC 6" Industrial T-Handle Valve Option (Non-Locking) NOTICE: T-Handle is more compact, but will greatly increase difficulty of operation.

Size	EPDM	FKM	Std Pk	Mstr Pk	Disc Code
------	------	-----	--------	---------	-----------

Socket Ends

6	18226-060C 2234.41	18326-060C 2482.51	1	0	613
----------	------------------------------	------------------------------	---	---	-----