


Don't wait. Modernize your office.

The ECOSYS PA4000wx is your dependable workmate, with a fast warm-up time of 15 seconds or less, compatibility with diverse mobile printing software, and sustainable long-life parts.





ECOSYS PA4000wx

BASIC SPECIFICATIONS

Configuration: B&W Printer - Print

Pages per Minute: Letter: 42 ppm; Legal: 34 ppm; A4: 40 ppm Duplex Print Speed: Letter 21 ppm; Legal 17 ppm; A4 20 ppm Display: 5 line LCD with Hard Key Control Panel Warm Up Time: 15 Seconds or Less (Power On) First Page Out Time: Print: 6.4 Seconds or Less Resolution: 300dpi, 600dpi, up to Fine1200 Memory: 512MB

Duplex: Standard Stackless Duplex Supports Statement to Legal (5.5" x 8.5" - 8.5" x 14"), 16 lb. Bond - 90 lb. Index (60 - 163gsm)

Dimensions / Weight: 15.2" W x 15.5" D x 10.7" H / 32 lbs Monthly Print Volume: 80,000 Pages per Month

POWER CONSUMPTION

Electrical Requirements: 120V, 60Hz, 8.2A; 220-240V, 50/60Hz, 4.1A

Typical Electricity Consumption (TEC): 120V: 0.34 kWh/week; 220-240V 0.34 kWh/week Maximum (including Options): 120V: 1114 W; 220-240V: 1,085 W Printing: 120V: 559.6 W; 220-240V: 555.9 W Ready Mode: 120V: 0.4W; 220-240V: 6.0W Sleep Mode: 120V: 0.4W; 220-240V: 0.3 W Power Off: 120V: 0.1 W; 220-240V: 0.1 W

PRINTER SPECIFICATIONS

Standard Controller: ARM Cortex A53 single 1.0GHz + ARM Cortex-M3 100MHz PDLs / Emulations: PRESCRIBE, PCL6 (PCL-XL / PCL-5e), KPDL3 (PostScript3 compatible), PDF w/KPDL3 setting, XPS / Open XPS Fonts: Outline: 93 Fonts (PCL 6/KPDL3), 4 Calibri, 4 Cambria, Bitmap: 1 Font, 79 Outline Fonts Barcodes: 1 Dimensional: 45 Type; 2 Dimensional: PDF417 1 Type **Windows OS Compatibility:** Windows 10 (32/64), Windows 11 (64), Windows Server 2016, 2019, 2022

MAC OS Compatibility: MAC OS X 10.9 or Greater Linux Printer Driver: Ubuntu 20.04 or higher, Debian 11 or higher, OpenSUSE 15.5 or higher, Fedora 39 or higher, CentOS Stream 9 or higher

Chrome OS: Version 118 or Higher

Interfaces: 10 BASE-T/100 BASE-T/1000 BASE-T, USB 2.0, 1 USB Host

Mobile Printing: Apple AirPrint®, Mopria®, KYOCERA Mobile Print, KYOCERA MyPanel, KYOCERA Android Print Service Plugin

Network Print and Supported Protocols: TCP/IP V4/V6, NetBEUI, FTPS, LPR, Port9100, IPPS, WSD, SMTP, SNMP, Syslog/SIEM

Drivers: KX Driver, PCL Uni Driver, KPDL Uni Driver, MAC Driver, Linux Driver, ChromeOS Driver

Utilities: KYOCERA Print Center, KYOCERA Cloud Access, KYOCERA Net Direct Print, KYOCERA Net Viewer, KYOCERA Device Manager, KYOCERA Quick Network Setup, KYOCERA Fleet Services

¹SDHC or SD required for: Private Print, Quick Copy Box, Job Box, Proof & Hold, and Job Storage

SECURITY

Standard: Local & Network Authentication, IPsec, HTTPS, SNMPv3, IPPS, POP over TLS, LDAP

PAPER SUPPLY

Standard / Maximum Paper Capacity: 350 Sheets / 850 Sheets

Standard / Maximum Paper Sources: 2 / 4 Including Multipurpose Tray

Paper Output Capacity: 250 Sheets

Paper Size: Standard and MPT: Statement to Legal (5.5" \times 8.5" - 8.5" \times 14"), Custom

Paper Weight: Drawer 16 lb. Bond – 90 lb. Index (60 – 163gsm); MPT: 16 lb. Bond – 120 lb. Index (60 – 220gsm) Input Materials: Plain Paper, Bond Paper, Recycled Paper, Thin Paper, Thick Paper; MPT: Labels, OHP, Envelopes

ADDITIONAL OPTIONS

Print Management: ThinPrint (UG-33) Security: Card Authentication Kit (B) SDHC or SD Card: 16 / 32 GB UG-50: TPM (Trusted Platform Module)

NOTE:

SDHC or SD required for: Private Print, Quick Copy Box, Job Box, Proof & Hold, and Job Storage

Specifications and design are subject to change without notice. For the latest on connectivity visit kyoceradocumentsolutions.us. ECOSYS, PRESCRIBE, Kyocera Net Manager, Kyocera Net Viewer, Kyocera Device Manager, PDF Direct Print, Command Center RX, and KX Driver are trademarks of The Kyocera Companies. Mac OS and AirPrint are trademarks of Apple, Inc. Mopria is a trademark of Mopria Alliance, Inc. Windows is a trademark of Microsoft, Inc. All other trademarks are the property of their respective owners.

KYOCERA Document Solutions America 225 Sand Road, PO Box 40008 Fairfield, New Jersey 07004-0008, USA



www.decoffice.com

Kyocera Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged. ©2024 KYOCERA Document Solutions America, Inc.