



SLC Pro Ø205-220 mm White 350mA-1780, 500mA-2400, 700mA

29/11/2024

SLC1013



Product description

Good lighting technology

The downlight is available in two sizes and up to four different lumen outputs, depending on the driver. (Driver is not included)

UGR 19

20 cm SMT connector

With 2m cable and plug

Technical data

Suitable for built-in mounting	Yes
Suitable for ceiling mounting	Yes
Suitable for pedestal/floor mounting	No
Suitable for clamp-mounting	No
Adjustability	Not adjustable
With light sensor	No
With light source	Yes
Surface protection	Powder coating
Material cover	Plastic, transparent
Voltage type	DC
Nominal current	350 - 800 Milliampere
With control gear	No
Dimming 1-10 V	No
Dimming DMX	No

Suitable for suspended mounting	No
Suitable for traverse mounting	No
Suitable for light-track mounting	No
Suitable for low voltage cable system	No
With movement sensor	No
Lamp type	LED not exchangeable
Housing material	Aluminium
Housing colour	Aluminium
Surface brushed	No
Nominal voltage	220 - 240 Volt
Type of control gear	LED operating device current-controlled
Dimming 0-10 V	No
Dimming DALI	No
Dimming DSI	No





Dimming potentiometer (integrated)	No
Dimming manufacturer's proprietary system	No
Dimming phase cut-off	No
Dimming programmable	No
Dimming Sine Wave Reduction	No
Dimming Zigbee	No
No dim function	No
Light distributor	Reflector
Reflector colour	Silver
Light outlet	Direct
Protection class	II
Suitable for lamp power	15 - 35 Watt
Colour of light	White
Colour rendering index CRI	80-89
Rated luminous flux according to IEC 62722-	4000 Lumen
Colour of light adjustable	No
Beam angle adjustable	No
Height/depth	140 Millimetre
Outer diameter	230 Millimetre
Built-in height/depth	140 Millimetre
Built-in diameter	205 - 220 Millimetre
Number of poles	2
Colour consistency (McAdam ellipse)	SDCM3
Colour	White
Control type	Without driver
GTIN	7070938055390

Dimming LineSwitch	No
Dimming mains voltage modulation	No
Dimming phase cut-on	No
Dimming RF	No
Dimming Touch and Dim	No
Dimming with push-button	No
Reflector	High-gloss
Light sharing	Symmetric
Beam angle	Medium beam 21-40°
Degree of protection (IP)	IP20
Rated ambient temperature according to IEC	-20 - 45 Degrees celsius
Max. system power	35 Watt
Colour temperature	4000 - 4000 Kelvin
Luminous flux	1740 - 4000 Lumen
Power factor	0,9
Luminous flux adjustable	Continuously variable
Width	230 Millimetre
Length	230 Millimetre
Built-in width	205 Millimetre
Built-in length	205 Millimetre
Type of wiring	Suitable for through wiring
Luminaire efficacy	114 Lumen/Watt
Beam angle fixed	45
Operating temperature (Ta)	-20°C ~ +45°C
Brand	SLC
Produced by	The Light Group






| The Light Group || SLC1013



This luminaire
contains built-in
LED lamps.



The lamps cannot be changed
in the luminaire.

874/2012

