

Art. R776BU+D377AU
3-Way diverter with integrated volume control

- For remote installation
- 1/2" NPT inlets and outlets
- With shut-off valve
- Round backplate
- Handle included
- 8.7 GPM @ 60 PSI (primary outlet)
- 7.4 GPM @ 60 PSI (secondary outlet)
- 7.4 GPM @ 60 PSI (third outlet)

To be used with thermostatic valve (#R700BU+#D300AU)

Project:

Room:

Date:

Comments:

Trim
Finishes:

| | | |
|--------------------------|------------------------|--------------|
| <input type="checkbox"/> | Chrome | 53 02 R776BU |
| <input type="checkbox"/> | Matte Black | 53 13 R776BU |
| <input type="checkbox"/> | Nickel PVD | 53 95 R776BU |
| <input type="checkbox"/> | Matte Gun Metal PVD | 53 P5 R776BU |
| <input type="checkbox"/> | Matte British Gold PVD | 53 P6 R776BU |
| <input type="checkbox"/> | Matte Copper PVD | 53 P9 R776BU |
| <input type="checkbox"/> | Pure Brass PVD | 53 Q7 R776BU |
| <input type="checkbox"/> | Raw Metal PVD | 53 Q8 R776BU |
| <input type="checkbox"/> | Deep Black PVD | 53 S1 R776BU |

Rough
Finishes:

| | |
|--------------------------|--------------|
| <input type="checkbox"/> | 19 00 D277AU |
|--------------------------|--------------|

